



North Carolina Department of Environment and Natural Resources
Division of Air Quality

Michael F. Easley, Governor

William G. Ross, Jr., Secretary
B. Keith Overcash, P.E., Director

December 17, 2007

Mr. Jeff Allen
Vice President of Operations
Thomas Built Buses, Inc.
P.O. Box 2450
High Point, North Carolina 27261

SUBJECT: Air Quality Permit No. 03209T17
Facility ID 4100822
Thomas Built Buses, Inc. - Courtesy Road Facility
High Point, Guilford County
Fee Class: Title V

Dear Mr. Allen;

In accordance with your completed Air Quality Permit Application (4100822.07C) for minor modification [15A NCAC 2Q .0515] of a Title V permit received on August 21, 2007, we are forwarding herewith Air Quality Permit No. **03209T17** to Thomas Built Buses, Inc., 1408 Courtesy Road, High Point, North Carolina authorizing the construction and operation, of the emission source(s) and associated air pollution control device(s) specified herein. Additionally, any emissions activities determined from your Air Quality Permit Application as being insignificant per 15A North Carolina Administrative Code 2Q .0503(8) have been listed for informational purposes as an "ATTACHMENT." Please note the requirements for the annual compliance certification are contained in General Condition P in Section 3 of Part I. The current owner is responsible for submitting a compliance certification for the entire year regardless of who owned the facility during the year.

These emission sources (ID Nos. ES-BTH-1 and BTH-2) are listed under a Part II as a minor modification per 15A NCAC 2Q .0515. The compliance certification as described in General Condition P is required. Unless otherwise notified by NC DAQ, the affected Part I terms of this permit (excluding the permit shield as described General Condition R) for this source shall become final on February 15, 2008. Until this date, the affected Part I permit terms herein reflect the proposed operating language that the Permittee shall operate this source under pursuant to 15A NCAC 2Q .0515(f).

Permitting Section

1641 Mail Service Center, Raleigh, North Carolina 27699-1641
2728 Capital Blvd., Raleigh, North Carolina 27604
Phone: 919-715-6235 / FAX 919-733-5317 / Internet: www.ncair.org

One
North Carolina
Naturally

An Equal Opportunity/Affirmative Action Employer – 50% Recycled/10% Post Consumer Paper

Mr. Jeff Allen

As the designated responsible official it is your responsibility to review, understand, and abide by all of the terms and conditions of the attached permit. It is also your responsibility to ensure that any person who operates any emission source and associated air pollution control device subject to any term or condition of the attached permit reviews, understands, and abides by the condition(s) of the attached permit that are applicable to that particular emission source.

If any parts, requirements, or limitations contained in this Air Quality Permit are unacceptable to you, you have the right to request a formal adjudicatory hearing within 30 days following receipt of this permit, identifying the specific issues to be contested. This hearing request must be in the form of a written petition, conforming to NCGS (North Carolina General Statutes) 150B-23, and filed with **both** the Office of Administrative Hearings, 6714 Mail Service Center, Raleigh, North Carolina 27699-6714 and the Division of Air Quality, Permitting Section, 1641 Mail Service Center, Raleigh, North Carolina 27699-1641. The form for requesting a formal adjudicatory hearing may be obtained upon request from the Office of Administrative Hearings. Please note that this permit will be stayed in its entirety upon receipt of the request for a hearing. Unless a request for a hearing is made pursuant to NCGS 150B-23, this Air Quality Permit shall be final and binding 30 days after issuance.

You may request modification of your Air Quality Permit through informal means pursuant to NCGS 150B-22. This request must be submitted in writing to the Director and must identify the specific provisions or issues for which the modification is sought. Please note that this Air Quality Permit will become final and binding regardless of a request for informal modification unless a request for a hearing is also made under NCGS 150B-23.

The construction of new air pollution emission source(s) and associated air pollution control device(s), or modifications to the emission source(s) and air pollution control device(s) described in this permit must be covered under an Air Quality Permit issued by the Division of Air Quality prior to construction unless the Permittee has fulfilled the requirements of GS 143-215-108A(b) and received written approval from the Director of the Division of Air Quality to commence construction. Failure to receive an Air Quality Permit or written approval prior to commencing construction is a violation of GS 143-215.108A and may subject the Permittee to civil or criminal penalties as described in GS 143-215.114A and 143-215.114B.

This Air Quality Permit shall be effective from December 17, 1007 until September 30, 2010, is nontransferable to future owners and operators, and shall be subject to the conditions and limitations as specified therein. Should you have any questions concerning this matter, please contact Kevin Godwin at (919) 715-6255.

Sincerely yours,

Donald R. van der Vaart, Ph.D., P.E.
Chief

Enclosure

c: Gregg Worley, EPA Region 4 (permit only)
Margaret Love, Supervisor, Winston-Salem Regional Office
Central Files

ATTACHMENT

Insignificant Activities under 2Q .0503(8)

Emission Source Id. No.	Emission Source Description
IES-1, IES-2, and IES-3 MACT Subpart MMMM and PPPP	Three metal parts washing systems
IES-8	Antifreeze storage tank (1,500 gallons capacity)
IES-14	Spray booth used in R&D
IES-15	Various welding operations
IES-16 and IES-17 MACT Subpart MMMM and PPPP	Two parts washers
IES-20	Segmented horizontal storage tank (diesel fuel-2000 gallon capacity, transmission fluid-750 gallon capacity, antifreeze-1500 gallon capacity and engine oil-750 gallon capacity)
IES-21 MACT Subpart ZZZZ	564 HP diesel fired emergency generator

ATTACHMENT

Table of Changes

Page No.	Section	Description of Change
3	Table of Emission Sources	Included two new replacement paint lines (ID Nos. ES-BTH1 and BTH2) and associated curing oven and removed ES-CHASSIS.
5	2.1 B.	Included two new replacement paint lines (ID Nos. ES-BTH1 and BTH2) and associated curing oven and removed ES-CHASSIS.
8	2.1 B. 5.	Removed existing State-only TPER condition [2Q .0711] pertaining to xylene emissions.
8	2.1 B. 5.	Included new State-only toxic air pollutant condition for modeled pollutants: formaldehyde, manganese, MEK, and xylene [2D .1100].
20	3	Updated general conditions with most recent shell version.
28	Part II	Included two new replacement paint lines (ID Nos. ES-BTH1 and BTH2) and associated curing oven.

State of North Carolina,
Department of Environment,
and Natural Resources

Division of Air Quality



AIR QUALITY PERMIT

Permit No.	Replaces Permit No.	Effective Date	Expiration Date
03209T17	03209T16	December 17, 2007	September 30, 2010

Until such time as this permit expires or is modified or revoked, the below named Permittee is permitted to construct and operate the emission source(s) and associated air pollution control device(s) specified herein, in accordance with the terms, conditions, and limitations within this permit. This permit is issued under the provisions of Article 21B of Chapter 143, General Statutes of North Carolina as amended, and Title 15A North Carolina Administrative Codes (15A NCAC), Subchapters 2D and 2Q, and other applicable Laws.

Pursuant to Title 15A NCAC, Subchapter 2Q, the Permittee shall not construct, operate, or modify any emission source(s) or air pollution control device(s) without having first submitted a complete Air Quality Permit Application to the permitting authority and received an Air Quality Permit, except as provided in this permit.

Permittee: **Thomas Built Buses - Courtesy Road**
Facility ID: **4100822**

Facility Site Location: **1408 Courtesy Road**
City, County, State, Zip: **High Point, Guilford County, North Carolina 27260**

Mailing Address: **P.O. 2450**
City, County, State, Zip: **High Point, Guilford County, North Carolina 27261**

Application Number: **4100822.07C**
Complete Application Date: **August 21, 2007**
Primary SIC Code: **3713**
Division of Air Quality, **Winston-Salem Regional Office**
Regional Office Address: **585 Waughtown Street**
Winston-Salem, NC 27107

Permit issued this the 17th day of December, 2007.

Donald R. van der Vaart, Ph.D., P.E., Chief, Air Permits Section
By Authority of the Environmental Management Commission

Table Of Contents

PART I

- SECTION 1: PERMITTED EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES
- SECTION 2: SPECIFIC LIMITATIONS AND CONDITIONS
- 2.1- Emission Source(s) Specific Limitations and Conditions (Including specific requirements, testing, monitoring, recordkeeping, and reporting requirements)
- SECTION 3: GENERAL PERMIT CONDITIONS

PART II

- SECTION 1: EMISSION SOURCE (S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE (S) AND APPURTENANCES
- SECTION 2: SPECIFIC LIMITATIONS AND CONDITIONS
- SECTION 3: GENERAL PERMIT CONDITIONS

ATTACHMENT

List of Acronyms

PART I

The Division of Air Quality (DAQ), the United States Environmental Protection Agency (EPA), and citizens as defined under the Federal Clean Air Act have the authority to enforce the terms, conditions, and limitations contained in Part I of this permit unless otherwise specified.

Under Title 15A NCAC 2Q, the operation of emission source(s) and associated air pollution control device(s) and appurtenances listed in Part I of this permit is based on plans, specifications, operating parameters, and other information as submitted in the Air Quality Permit Application.

SECTION 1- PERMITTED EMISSION SOURCE (S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE (S) AND APPURTENANCES

The following table contains a summary of all permitted emission sources and associated air pollution control devices and appurtenances:

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
ES-1 NSPS Subpart DC	Natural gas-fired process hot water heater (15 million Btu per hour maximum permitted heat input)	NA	NA
ES-PP02	Electrostatic dry powder coating operation equipped with powder recovery including a curing oven consisting of one 22.5 million Btu per hour natural gas-fired heater	NA	NA
ES-CB600	Natural gas/No. 2 fuel oil-fired boiler (25.1 million Btu per hour heat input)	NA	NA
ES-CONT400	Natural gas/No. 2 fuel oil-fired boiler (16.7 million Btu per hour heat input)	NA	NA
ES-BTH1 and ES-BTH2* MACT Subpart MMMM and PPPP	Two dry-filter type paint lines each consisting of a sanding/prep booth (ES-BTH1a and ES-BTH2a), Top Coat paint booth (ES-BTH1b and ES-BTH2b) and associated natural gas-fired curing oven (1.5 million Btu per hour heat input, ES-CO)	NA	NA
ES-WD1	Woodworking operations	CDC1 CDB1	Simple cyclone (24 inches in diameter) Bagfilter (100 square feet of filter media)
ES-MJ MACT Subpart MMMM and PPPP	Metal body joining operation using adhesives		

* These emission sources (**ID Nos. ES-BTH-1 and BTH-2**) are listed as a minor modification per 15 A NCAC 2Q .0515. The compliance certification as described in General Condition P is required. Unless otherwise notified by NC DAQ, the affected Part I terms of this permit (excluding the permit shield as described General Condition R) for this source shall become final on February 15, 2008. Until this date, the affected Part I permit terms herein reflect the proposed operating language that the Permittee shall operate this source under pursuant to 15A NCAC 2Q .0515(f).

SECTION 2 - SPECIFIC LIMITATIONS AND CONDITIONS

2.1- Emission Source(s) and Control Devices(s) Specific Limitations and Conditions

The emission source(s) and associated air pollution control device(s) listed below are subject to the following specific terms, conditions, and limitations, including the monitoring, recordkeeping, and reporting requirements as specified herein:

A. Woodworking operations (ID No. ES-WD1) with simple cyclone (ID No. CDC1) in series with bagfilter (ID No. CDB1)

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	Adequate ductwork and properly designed collectors.	15A NCAC 2D .0512
Visible emissions	20 percent opacity	15A NCAC 2D .0521

1. 15A NCAC 2D .0512: PARTICULATES FROM MISCELLANEOUS WOOD PRODUCTS FINISHING PLANTS

- a. The Permittee shall not cause, allow, or permit particulate matter caused by the working, sanding, or finishing of wood to be discharged from any stack, vent, or building into the atmosphere without providing, as a minimum for its collection, adequate duct work and properly designed collectors. In no case shall the ambient air quality standards be exceeded beyond the property line.

Monitoring [15A NCAC 2Q .0508(f)]

- b. Particulate matter emissions from the wood material collection systems (ID No. ES-WD1) shall be controlled by a cyclone and a bagfilter. To assure compliance, the Permittee shall perform inspections and maintenance as recommended by the manufacturer, if any. As a minimum, the inspection and maintenance program shall include:
- monthly external inspection of the ductwork, cyclone and bagfilter noting the structural integrity; and
 - annual internal inspection of the bagfilter noting the structural integrity and the condition of the filters.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0512 if the ductwork, cyclone and bagfilter are not inspected and maintained.

Recordkeeping [15A NCAC 2Q .0508(f)]

- c. The results of inspection and maintenance for the cyclone and bagfilter shall be maintained in a log (written or electronic format) on-site and made available to an authorized representative upon request. The log shall record the following:
- the date and time of each recorded action;
 - the results of each inspection; and
 - the results of maintenance performed on any control device.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0512 if these records are not maintained.

Reporting [15A NCAC 2Q .0508 (f)]

- d. The Permittee shall submit the results of any maintenance performed on the control devices within 30 days of a written request by the DAQ.
- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

2. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources shall not be more than 20 percent opacity when averaged over a six-minute period except that six-minute periods averaging not more than 87 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(d)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .0501(c)(8) and General Condition JJ. If the results of this test are above the limit given in Section 2.1 A.2.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a week the Permittee shall observe the emission points of these sources for any visible emissions above normal. The weekly observation must be made for each week of the calendar year period to ensure compliance with this requirement. If visible emissions from these sources are observed to be above normal, the Permittee shall either:
 - i. take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or
 - ii. demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 A.2.a. above.

If the above-normal emissions are not corrected per (i) above or if the demonstration in (ii) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of inspection and maintenance shall be maintained in a log (written or electronic format) on site and made available to an authorized representative upon request. The log shall record the following:
 - i. the date and time of inspections;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508 (f)]

- e. The Permittee shall submit a summary report of the observations by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

B. Two dry-filter type paint lines (ID Nos. ES-BTH1 and ES-BTH2) and associated natural gas-fired curing oven, Electrostatic dry powder coating operation with powder recovery and a curing oven (ID No. ES-PP02), and Metal body joining operation using adhesives (ID No. ES-MJ).

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	Up to 30 ton/hour: $E=4.10P^{0.67}$ where E = allowable emission rate in pounds per hour P = process weight in tons per hour (30 tons/hr). Greater than 30 ton/hour; $E=55.0P^{0.11} - 40$ where E = allowable emission rate in pounds per hour P = process weight in tons per hour.	15A NCAC 2D .0515
Visible emissions	20 percent opacity	15A NCAC 2D .0521
Odors	State-enforceable only The facility may not operate without proper control of odorous emissions	15A NCAC 2D .1806
Volatile organic compounds	State-enforceable only Work Practice Standards	15A NCAC 2D .0958

Regulated Pollutant	Limits/Standards	Applicable Regulation
Toxic air pollutants (TAP)	State-enforceable only TAP emissions shall not exceed limits established using air dispersion modeling.	15A NCAC 2Q .1100
Hazardous Air Pollutants	40 CFR 63 Subpart PPPP 40 CFR 63 Subpart MMMM	15A NCAC 2D .1111
TAP	State Only Requirement Last MACT/air toxics demonstration	15A NCAC 2Q. 0705

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emissions of particulate matter from these sources shall not exceed an allowable emission rate as calculated by the following equation: [15A NCAC 2D .0515(a)]
 Up to 30 ton/hour: $E=4.10P^{0.67}$ where
 E = allowable emission rate in pounds per hour
 P = process weight in tons per hour

 Greater than 30 ton/hour; $E=55.0P^{0.11} - 40$ where
 E = allowable emission rate in pounds per hour
 P = process weight in tons per hour
 Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .0501 (c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 B.1.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. The Permittee shall maintain production records such that the process rates "P" in tons per hour, as specified in the formulas contained above can be derived, and shall make these records available to DAQ authorized representative upon request. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the production records are not maintained or the types of materials and finishes are not monitored.

2. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources shall not be more than 20 percent opacity when averaged over a six-minute period except that six-minute periods averaging not more than 87 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(d)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .0501(c)(8) and General Condition JJ. If the results of this test are above the limit given in Section 2.1 B.2.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a month the Permittee shall observe the emission points of these sources for any visible emissions above normal. The monthly observation must be made for each month of the calendar year period to ensure compliance with this requirement. If visible emissions from these sources are observed to be above normal, the Permittee shall either:
 - i. take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or
 - ii. demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 B.2.a. above.
 If the above-normal emissions are not corrected per (i) above or if the demonstration in (ii) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of inspection and maintenance shall be maintained in a log (written or electronic format) on site and made available to an authorized representative upon request. The log shall record the following:

- i. the date and time of inspections;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508 (f)]

- e. The Permittee shall submit a summary report of the observations by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

STATE-ONLY REQUIREMENT

3. 15A NCAC 2D .1806: CONTROL AND PROHIBITION OF ODOROUS EMISSIONS

The Permittee shall not operate the facility without implementing management practices or installing and operating odor control equipment sufficient to prevent odorous emissions from the facility from causing or contributing to objectionable odors beyond the facility's boundary.

4. 15A NCAC 2D .0958: WORK PRACTICES FOR SOURCES OF VOLATILE ORGANIC COMPOUNDS

- a. Pursuant to 15A NCAC 2D .0958 and 2D .0902, for all sources that use volatile organic compounds (VOC) as solvents, carriers, material processing media, or industrial chemical reactants, or in similar uses that mix, blend, or manufacture volatile organic compounds, or emit volatile organic compounds as a product of chemical reactions, and whose emissions of VOC are greater than 15 pounds per day; the Permittee shall:
 - i. store all material, including waste material, containing volatile organic compounds in tanks or in containers covered with a tightly fitting lid that is free of cracks, holes, or other defects, when not in use,
 - ii. clean up spills of volatile organic compounds as soon as possible following proper safety procedures,
 - iii. store wipe rags containing volatile organic compounds in closed containers,
 - iv. not clean sponges, fabric, wood, paper products, and other absorbent materials with volatile organic compounds,
 - v. transfer solvents containing volatile organic compounds used to clean supply lines and other coating equipment into closable containers and close such containers immediately after each use, or transfer such solvents to closed tanks, or to a treatment facility regulated under section 402 of the Clean Water Act,
 - vi. clean mixing, blending, and manufacturing vats and containers containing volatile organic compounds by adding cleaning solvent and close the vat or container before agitating the cleaning solvent. The spent cleaning solvent shall then be transferred into a closed container, a closed tank or a treatment facility regulated under section 402 of the Clean Water Act. [15A NCAC 2D .0958(c)]
- b. When cleaning parts with a solvent containing a volatile organic compound, the Permittee shall:
 - i. flush parts in the freeboard area,
 - ii. take precautions to reduce the pooling of solvent on and in the parts,
 - iii. tilt or rotate parts to drain solvent and allow a minimum of 15 seconds for drying or until all dripping has stopped, whichever is longer,
 - iv. not fill cleaning machines above the fill line,
 - v. not agitate solvent to the point of causing splashing. [15A NCAC 2D .0958(d)]

Monitoring [2Q .0508(f)]

- c. To assure compliance with paragraphs (a) and (b) above, the Permittee shall, at a minimum, perform a visual inspection once per month of all operations and processes utilizing volatile organic compounds. The inspections shall be conducted during normal operations. If the required inspections are not conducted the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0958.

Recordkeeping [2Q .0508(f)]

- d. The results of the inspections shall be maintained in a log (written or electronic format) on-site and made available to an authorized representative upon request. The log shall record the following:
 - i. the date and time of each inspection; and
 - ii. the results of each inspection noting whether or not noncompliant conditions were observed.If the required records are not maintained the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0958.

Reporting [2Q .0508(f)]

- e. The Permittee shall submit a summary report of the observations by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

STATE-ONLY REQUIREMENT

- 5. **TOXIC AIR POLLUTANT EMISSIONS LIMITATION AND REQUIREMENT** - Pursuant to 15A NCAC 2D .1100 and in accordance with the approved application for an air toxic compliance demonstration, the following permit limit shall not be exceeded:

EMISSION SOURCE(S)	TOXIC AIR POLLUTANT(S)	EMISSION LIMIT(S)
Facility-wide sources	Formaldehyde	0.13 pounds per hour
	Manganese	1.61 pounds per day
	Methyl ethyl ketone	76.56 pounds per hour 192.05 pounds per day
	Xylene	56.23 pounds per hour 140.15 pounds per day

The Permittee is allowed to paint small parts in the old paint booths up to 120 days after initial start-up of the new booths. After this date, the old booths shall be removed from operation.

For compliance purposes, within 30 days after each calendar year quarter the facility shall report emissions to the Regional Supervisor, DAQ.

- 6. **15A NCAC 2D .1111 [40 CFR Part 63 Subpart PPPP]:
NESHAP for Surface Coating of Plastic Parts and Products**

- a. The Permittee shall comply with all applicable provisions contained in Environmental Management Commission Standard 15A NCAC 2D .1111, “Maximum Achievable Control Technology” as promulgated in 40 CFR 63, Subpart PPPP, “National Emission Standards for Hazardous Air Pollutants for Surface Coating of Plastic Parts and Products”, by April 19, 2007 or as amended by the rule for the existing applicable sources as detailed in the equipment table.

Emission Limits [40 CFR 63.4490]

- b. For each existing general use coating affected source, the Permittee shall limit organic HAP emissions to no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.

Compliance Options [40 CFR 63.4491]

- c. The Permittee shall include all coatings, thinners and/or other additives, and cleaning materials used in the affected source when determining whether the organic HAP emission rate is equal to or less than the applicable emission limit in Section 2.1 B.6.b. above. To make this determination, the Permittee shall use at least one of the following two compliance options. The Permittee may apply any of the compliance options to an individual coating operation, or to multiple coating operations as a group, or to the entire affected source. The Permittee may use different compliance options for different coating operations, or at different times on the same coating operation. The Permittee may employ different compliance options when different coatings are applied to the same part, or when the same coating is applied to different parts. However, the Permittee may not use different compliance options at the same time on the same coating operation. If the Permittee switches between compliance options for any coating operation or group of coating operations, he shall document this switch as required by Section 2.1 B.6.g.iii below, and shall report it in the next semiannual compliance report required in Section 2.1 B.6.h below.
 - i. **Compliant material option.** Demonstrate that the organic HAP content of each coating used in the coating operation(s) is less than or equal to the applicable emission limit in Section 2.1 B.6.b. above, and that each thinner and/or other additive, and cleaning material used contains no organic HAP. The Permittee shall meet all of the following requirements to demonstrate compliance with the applicable emission limit using this option:
 - A. The Permittee shall complete the initial compliance demonstration for the initial compliance period ending **April 30, 2008** or as amended by the rule, according to the requirements in Section 2.1 B.6.c.i.B below. The demonstration shall include the calculations and supporting documentation showing that during the initial compliance period, the Permittee used no coating with an organic HAP content that exceeded the applicable emission limit in Section 2.1 B.6.b. above, and that he used no thinners and/or other additives, or cleaning materials that contained organic HAP.

- B. The Permittee may use the compliant material option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected source. The Permittee shall use the emission rate without add-on controls option for any coating operation in the affected source for which he does not use this option. To demonstrate initial compliance using the compliant material option, the coating operation or group of coating operations must use no coating with an organic HAP content that exceeds the applicable emission limits in Section 2.1 B.6.b. above and must use no thinner and/or other additive, or cleaning material that contains organic HAP. Use the procedures in this section on each coating, thinner and/or other additive, and cleaning material in the condition it is in when it is received from its manufacturer or supplier and prior to any alteration. The Permittee does not need to redetermine the organic HAP content of coatings, thinners and/or other additives, and cleaning materials that are reclaimed on-site (or reclaimed off-site if you have documentation showing that he received back the exact same materials that were sent off-site) and reused in the coating operation for which he uses the compliant material option, provided these materials in their condition as received were demonstrated to comply with the compliant material option.
1. Determine the mass fraction of organic HAP for each material used. The Permittee shall determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during the compliance period by using one of the following options:
 - (a). Method 311 (appendix A to 40 CFR part 63). The Permittee may use Method 311 for determining the mass fraction of organic HAP by using the following procedures:
 - (i). Count each organic HAP that is measured to be present at 0.1 percent by mass or more for Occupational Safety and Health Administration (OSHA)-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is measured to be 0.5 percent of the material by mass, the Permittee does not have to count it. Express the mass fraction of each organic HAP for which the Permittee counts, as a value truncated to four places after the decimal point (e.g., 0.3791)
 - (ii). Calculate the total mass fraction of organic HAP in the test material by adding up the individual organic HAP mass fractions and truncating the result to three places after the decimal point (e.g., 0.763).
 - (b). Method 24 (appendix A to 40 CFR part 60). For coatings, the Permittee may use Method 24 to determine the mass fraction of nonaqueous volatile matter and use that value as a substitute for mass fraction of organic HAP. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, the Permittee may use the alternative method contained in appendix A to subpart PPPP of this part, rather than Method 24. The Permittee may use the volatile fraction that is emitted, as measured by the alternative method in appendix A to this subpart, as a substitute for the mass fraction of organic HAP.
 - (c). Alternative method. The Permittee may use an alternative test method for determining the mass fraction of organic HAP once the Administrator has approved it. The Permittee shall follow the procedure in 63.7(f) to submit an alternative test method for approval.
 - (d). Information from the supplier or manufacturer of the material. The Permittee may rely on information other than that generated by the test methods specified in Section 2.1 B.6.c.i.B.1. (a) through (c) above, such as manufacturer's formulation data, if it represents each organic HAP that is present at 0.1 percent by mass or more for OSHA-defined carcinogens as specified in 29 CFR 1910.1200(d)(4) and at 1.0 percent by mass or more for other compounds. For example, if toluene (not an OSHA carcinogen) is 0.5 percent of the material by mass, the Permittee does not have to count it. For reactive adhesives in which some of the HAP react to form solids and are not emitted to the atmosphere, the Permittee may rely on manufacturer's data that expressly states the organic HAP or volatile matter mass fraction emitted. If there is a disagreement between such information and results of a test conducted according to Section 2.1 B.6.c.i.B.1. (a) through (c) above, then the test method results will take precedence unless, after consultation, the Permittee demonstrates to the satisfaction of DAQ that the formulation data are correct.
 - (e). Solvent blends. Solvent blends may be listed as single components for some materials in data provided by manufacturers or suppliers. Solvent blends may contain organic HAP, which must be counted toward the total organic HAP mass fraction of the materials. When test data and manufacturer's data for solvent blends are not available, the Permittee may use the default values for the mass fraction of organic HAP in these solvent blends listed in Table 3 or 4 to this Subpart. If the Permittee uses the tables, he shall use the values in Table 3 for all solvent blends that match Table 3 entries according to the instructions for Table 3, and may use Table 4 only if the solvent blends in the materials do not match any of the solvent blends in Table 3 and he knows only whether the blend is aliphatic or aromatic. However, if the results of a Method 311 (appendix A to

40 CFR part 63) test indicate higher values than those listed on Table 3 or 4 to this subpart, the Method 311 results will take precedence unless, after consultation, he demonstrates to the satisfaction of DAQ that the formulation data are correct.

2. Determine the mass fraction of coating solids for each coating. The Permittee shall determine the mass fraction of coating solids (kg (lb) of coating solids per kg (lb) of coating) for each coating used during the compliance period by a test, by information provided by the supplier or the manufacturer of the material, or by calculation, as specified in Section 2.1.B.6.c.i.B.2. (a) through (c) below.
 - (a). Method 24 (appendix A to 40 CFR part 60). The Permittee may use Method 24 for determining the mass fraction of coating solids. For reactive adhesives in which some of the liquid fraction reacts to form solids, you may use the alternative method contained in appendix A to this subpart, rather than Method 24, to determine the mass fraction of coating solids.
 - (b). Alternative method. The Permittee may use an alternative test method for determining the solids content of each coating once the Administrator has approved it. You must follow the procedure in Sec. 63.7(f) to submit an alternative test method for approval.
 - (c). Information from the supplier or manufacturer of the material. The Permittee may obtain the mass fraction of coating solids for each coating from the supplier or manufacturer. If there is disagreement between such information and the test method results, then the test method results will take precedence unless, after consultation the Permittee demonstrates to the satisfaction of the DAQ that the formulation data are correct.
3. Calculate the organic HAP content of each coating. The Permittee may determine the organic HAP content, kg (lb) organic HAP emitted per kg (lb) coating solids used, of each coating used during the compliance period using the following equation:

$$H_c = \frac{W_c}{S_c} \quad (\text{Eq. 1})$$

Where: Hc = Organic HAP content of the coating, kg (lb) of organic HAP emitted per kg (lb) coating solids used.

Wc = Mass fraction of organic HAP in the coating, kg organic HAP per kg coating, determined according to Section 2.1 B.6.c.i.B.1 above.

Sc = Mass fraction of coating solids, kg coating solids per kg coating, determined according to Section 2.1 B.6.c.i.B.2 above.

4. Compliance demonstration. The calculated organic HAP content for each coating used during the initial compliance period must be less than or equal to the applicable emission limit in Section 2.1 B.6.b. above; and each thinner and/or other additive, and cleaning material used during the initial compliance period must contain no organic HAP, determined according to Section 2.1 B.6.c.i.B.1 above. The Permittee shall keep all records required by Section 2.1 B.6.g below. As part of the notification of compliance status required in Section 2.1 B.6.f below, the Permittee shall identify the coating operation(s) for which he used the compliant material option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because he used no coatings for which the organic HAP content exceeded the applicable emission limit in Section 2.1 B.6.b. above, and he used no thinners and/or other additives, or cleaning materials that contained organic HAP, determined according to the procedures in Section 2.1 B.6.c.i.B.1 above.
 - C. 1. For each compliance period to demonstrate continuous compliance, the Permittee shall use no coating for which the organic HAP content (determined using Equation 1 of Section 2.1 B.6.c.i.B.3 above) exceeds the applicable emission limit in Section 2.1 B.6.b. above, and use no thinner and/or other additive, or cleaning material that contains organic HAP, determined according to Section 2.1 B.6.c.i.B.1 above. A compliance period consists of 12 months. Each month, after the end of the initial compliance period described in Section 2.1 B.6.c.i.A above, is the end of a compliance period consisting of that month and the preceding 11 months.
 2. If the Permittee chooses to comply with the emission limitations by using the compliant material option, the use of any coating, thinner and/or other additive, or cleaning material that does not meet the criteria specified in Section 2.1 B.6.c.i.C.1 above is a deviation from the emission limitations that must be reported as specified in Section 2.1 B.6.f.vi below and/or Section 2.1 B.6.h.ix below.
 3. As part of each semiannual compliance report required by Section 2.1 B.6.h below, the Permittee shall identify the coating operation(s) for which you used the compliant material option. If there were no deviations from the applicable emission limit in Section 2.1 B.6.b. above, submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because he used no coatings for which the organic HAP content exceeded the applicable emission limit

in Section 2.1 B.6.b. above, and he used no thinner and/or other additive, or cleaning material that contained organic HAP, determined according to Section 2.1 B.6.c.i.B.1 above.

4. The Permittee shall maintain records as specified in Section 2.1 B.6.g below.
- ii. Emission rate without add-on controls option. Demonstrate that, based on the coatings, thinners and/or other additives, and cleaning materials used in the coating operation(s), the organic HAP emission rate for the coating operation(s) is less than or equal to the applicable emission limit in Section 2.1 B.6.b. above, calculated as a rolling 12-month emission rate and determined on a monthly basis. The Permittee shall meet all of the following requirements to demonstrate compliance with the emission limit using this option.
 - A. The Permittee shall complete the initial compliance demonstration for the initial compliance period ending on **April 30, 2008** or as amended by the rule, according to the requirements of Section 2.1 B.6.c.ii.B below. The Permittee shall determine the mass of organic HAP emissions and mass of coating solids used each month and then calculate an organic HAP emission rate at the end of the initial compliance period. The demonstration shall include the calculations according to Section 2.1 B.6.c.ii.B below and supporting documentation showing that during the initial compliance period the organic HAP emission rate was equal to or less than the applicable emission limit in Section 2.1 B.6.b. above.
 - B. The Permittee may use the emission rate without add-on controls option for any individual coating operation, for any group of coating operations in the affected source, or for all the coating operations in the affected source. The Permittee shall use the compliant material option for any coating operation in the affected source for which he does not use this option. To demonstrate initial compliance using the emission rate without add-on controls option, the coating operation or group of coating operations must meet the applicable emission limit in Section 2.1 B.6.b. above. When calculating the organic HAP emission rate according to this section, do not include any coatings, thinners and/or other additives, or cleaning materials used on coating operations for which the Permittee uses the compliant material option. The Permittee does not need to re-determine the mass of organic HAP in coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site (or reclaimed off-site if you have documentation showing that he received back the exact same materials that were sent off-site) and reused in the coating operation for which he uses the emission rate without add-on controls option. If the Permittee uses coatings, thinners and/or other additives, or cleaning materials that have been reclaimed on-site, the amount of each used in a month may be reduced by the amount of each that is reclaimed. That is, the amount used may be calculated as the amount consumed to account for materials that are reclaimed.
 1. Determine the mass fraction of organic HAP for each material. Determine the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each month according to the requirements in Section 2.1 B.6.c.i.B.1 above.
 2. Determine the mass fraction of coating solids. Determine the mass fraction of coating solids (kg (lb) of coating solids per kg (lb) of coating) for each coating used during each month according to the requirements in Section 2.1 B.6.c.i.B.2 above.
 3. Determine the density of each material. Determine the density of each liquid coating, thinner and/or other additive, and cleaning material used during each month from test results using ASTM Method D1475-98, "Standard Test Method for Density of Liquid Coatings, Inks, and Related Products" (incorporated by reference, see 63.14), information from the supplier or manufacturer of the material, or reference sources providing density or specific gravity data for pure materials. If there is disagreement between ASTM Method D1475-98 and other such information sources, the test results will take precedence unless, after consultation you demonstrate to the satisfaction of DAQ that the formulation data are correct. If you purchase materials or monitor consumption by weight instead of volume, you do not need to determine material density. Instead, you may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, 1C, and 2 below.
 4. Determine the volume of each material used. Determine the volume (liters) of each coating, thinner and/or other additive, and cleaning material used during each month by measurement or usage records. If the Permittee purchases materials or monitors consumption by weight instead of volume, he does not need to determine the volume of each material used. Instead, the Permittee may use the material weight in place of the combined terms for density and volume in Equations 1A, 1B, 1C and 2 below.
 5. Calculate the mass of organic HAP emissions. The mass of organic HAP emissions is the combined mass of organic HAP contained in all coatings, thinners and/or other additives, and cleaning materials used during each month minus the organic HAP in certain waste materials. Calculate the mass of organic HAP emissions using Equation 1 of this section.

$$H_e = A + B + C - R_w \quad (\text{Eq. 1})$$

Where: H_e = Total mass of organic HAP emissions during the month, kg.

A = Total mass of organic HAP in the coatings used during the month, kg, as calculated in Equation 1A of this section.

B = Total mass of organic HAP in the thinners and/or other additives used during the month, kg, as calculated in Equation 1B of this section.

C = Total mass of organic HAP in the cleaning materials used during the month, kg, as calculated in Equation 1C of this section.

Rw = Total mass of organic HAP in waste materials sent or designated for shipment to a hazardous waste TSDF for treatment or disposal during the month, kg, determined according to Section 2.1 B.6.c.ii.B.5.d below. (The Permittee may assign a value of zero to RW if he does not wish to use this allowance.)

- (a). Calculate the kg of organic HAP in the coatings used during the month using Equation 1A below:

$$A = \sum_{i=1}^m (\text{Vol}_{c,i})(D_{c,i})(W_{c,i}) \quad (\text{Eq. 1A})$$

Where: A = Total mass of organic HAP in the coatings used during the month, kg
 $\text{Vol}_{c,i}$ = Total volume of coating, i, used during the month, liters.
 $D_{c,i}$ = Density of coating, i, kg coating per liter coating.
 $W_{c,i}$ = Mass fraction of organic HAP in coating, i, kg organic HAP per kg coating. For reactive adhesives, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to this subpart.
 m = Number of different coatings used during the month.

- (b). Calculate the kg of organic HAP in the thinners and/or other additives used during the month using Equation 1B of this section:

$$B = \sum_{j=1}^n (\text{Vol}_{t,j})(D_{t,j})(W_{t,j}) \quad (\text{Eq. 1B})$$

Where: B = Total mass of organic HAP in the thinners and/or other additives used during the month, kg.
 $\text{Vol}_{t,j}$ = Total volume of thinner and/or other additive, j, used during the month, liters.
 $D_{t,j}$ = Density of thinner and/or other additive, j, kg per liter.
 $W_{t,j}$ = Mass fraction of organic HAP in thinner and/or other additive, j, kg organic HAP per kg thinner and/or other additive. For reactive adhesives, use the mass fraction of organic HAP that is emitted as determined using the method in appendix A to this subpart.
 n = Number of different thinners and/or other additives used during the month.

- (c). Calculate the kg of organic HAP in the cleaning materials used during the month using Equation 1C of this section:

$$C = \sum_{k=1}^p (\text{Vol}_{s,k})(D_{s,k})(W_{s,k}) \quad (\text{Eq. 1C})$$

Where: C = Total mass of organic HAP in the cleaning materials used during the month, kg.
 $\text{Vol}_{s,k}$ = Total volume of cleaning material, k, used during the month, liters.
 $D_{s,k}$ = Density of cleaning material, k, kg per liter.
 $W_{s,k}$ = Mass fraction of organic HAP in cleaning material, k, kg organic HAP per kg material.
 p = Number of different cleaning materials used during the month.

- (d). If the Permittee chooses to account for the mass of organic HAP contained in waste materials sent or designated for shipment to a hazardous waste TSDF in Equation 1 of this section, then he shall determine the mass according to the procedures in 40 CFR 63.4551 (e)(4).

6. Calculate the total mass of coating solids used. Determine the total mass of coating solids used, kg, which is the combined mass of coating solids for all the coatings used during each month, using Equation 2 of this section:

$$M_{st} = \sum_{i=1}^m (Vol_{c,i})(D_{c,i})(M_{s,i}) \quad (\text{Eq. 2})$$

Where: M_{st} = Total mass of coating solids used during the month, kg.
 $Vol_{c,i}$ = Total volume of coating, i, used during the month, liters.
 $D_{c,i}$ = Density of coating, i, kgs per liter coating, determined according to Section 2.1 B.6.d.ii.B.3 above
 $M_{s,i}$ = Mass fraction of coating solids for coating, i, kgs solids per kg coating, determined according to Section 2.1 B.6.d.i.B.2 above
 m = Number of coatings used during the month.

7. Calculate the organic HAP emission rate. Calculate the organic HAP emission rate for the compliance period, kg (lb) organic HAP emitted per kg (lb) coating solids used, using Equation 3 of this section:

$$H_{yr} = \frac{\sum_{y=1}^n H_e}{\sum_{y=1}^n M_{st}} \quad (\text{Eq. 3})$$

Where: H_{yr} = Average organic HAP emission rate for the compliance period, kg organic HAP emitted per kg coating solids used.
 H_e = Total mass of organic HAP emissions from all materials used during month, y, kg, as calculated by Equation 1 of this section.
 M_{st} = Total mass of coating solids used during month, y, kg, as calculated by Equation 2 of this section.
 y = Identifier for months.
 n = Number of full or partial months in the compliance period (for the initial compliance period, n equals 12 if the compliance date falls on the first day of a month; otherwise n equals 13; for all following compliance periods, n equals 12).

8. Compliance demonstration. The organic HAP emission rate for the initial compliance period calculated using Equation 3 of this section must be less than or equal to the emission limit in Section 2.1 B.6.b. above. The Permittee shall keep all records as required by Section 2.1 B.6.g below. As part of the notification of compliance status required by Section 2.1 B.6.f below, the Permittee shall identify the coating operation(s) for which he used the emission rate without add-on controls option and submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the initial compliance period because the organic HAP emission rate was less than or equal to the applicable emission limit in Section 2.1 B.6.b. above, determined according to the procedures in this section.
- C. 1. To demonstrate continuous compliance, the organic HAP emission rate for each compliance period, determined according to Section 2.1 B.6.c.ii.B.1 through 7 above, must be less than or equal to the applicable emission limit in Section 2.1 B.6.b. above. A compliance period consists of 12 months. Each month after the end of the initial compliance period described in Section 2.1 B.6.c.ii.A above is the end of a compliance period consisting of that month and the preceding 11 months. The Permittee shall perform the calculations in Section 2.1 B.6.c.ii.B.1 through 7 above on a monthly basis using data from the previous 12 months of operation.
2. If the organic HAP emission rate for any 12-month compliance period exceeded the applicable emission limit in Section 2.1 B.6.b. above, this is a deviation from the emission limitation for that compliance period and must be reported as specified in Sections 2.1 B.6.f.vi and 2.1 B.6.h.x below.
3. As part of each semiannual compliance report required by Section 2.1 B.6.h below, the Permittee shall identify the coating operation(s) for which he used the emission rate without add-on controls option. If there were no deviations from the emission limitations, the Permittee shall submit a statement that the coating operation(s) was (were) in compliance with the emission limitations during the reporting period because the organic HAP emission rate for each compliance period was less than or equal to the applicable

emission limit in Section 2.1 B.6.b. above, determined according to Section 2.1 B.6.c.ii.B.1 through 7 above.

4. The Permittee shall maintain records as specified in Section 2.1 B.6.g below.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if it does not conduct a monthly compliance demonstration as required above or if the compliance demonstration shows an exceedance of the emission limitations in Section 2.1 B.6.b. above.

Operating Limits/Work Practice Standards [63.4492 and 63.4493]

- d. For the above existing sources on which the Permittee uses the compliant material option in Section 2.1 B.6.c.i above or the emission rate without add-on controls option in Section 2.1 B.6.c.ii above, the Permittee is not required to meet any operating limits or work practice standards.

Notifications [63.4510]

- e. The Permittee shall submit the notifications in 63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) that apply to you by the dates specified in those sections, except as provided in Section 2.1 B.6.f below.
- f. The Permittee shall submit the notification of compliance status required by 63.9(h) by **May 30, 2008**. The notification of compliance status must contain the following information and the information in 63.9(h).
- i. Company name and address;
 - ii. Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report;
 - iii. Date of the report and beginning and ending dates of the reporting period;
 - iv. Identification of the compliance option or options specified in Section 2.1 B.6.c above that you used on each coating operation during the initial compliance period;
 - v. Statement of whether or not the affected source achieved the emission limitations for the initial compliance period;
 - vi. If the Permittee had a deviation, include the following information:
 - A. A description and statement of the cause of the deviation; and
 - B. If the Permittee failed to meet the applicable emission limit in Section 2.1 B.6.b. above, include all the calculations used to determine the kg (lb) of organic HAP emitted per kg (lb) coating solids used. The Permittee does not need to submit information provided by the materials' suppliers or manufacturers, or test reports;
 - vii. For each of the following data items that are required by the compliance option(s) the Permittee used to demonstrate compliance with the emission limit, an example of how the Permittee determined the value, including calculations and supporting data. Supporting data may include a copy of the information provided by the supplier or manufacturer of the example coating or material, or a summary of the results of testing conducted according to Sections 2.1 B.6.c.i.B.1, 2 or 3 above. The Permittee does not need to submit copies of any test reports.
 - A. Mass fraction of organic HAP for one coating, for one thinner and/or other additive, and for one cleaning material;
 - B. Mass fraction of coating solids for one coating;
 - C. Density for one coating, one thinner and/or other additive, and one cleaning material, except that if the Permittee uses the compliant material option, only the example coating density is required; and
 - D. The amount of waste materials and the mass of organic HAP contained in the waste materials for which the Permittee is claiming an allowance in Equation 1 of Section 2.1 B.6.c.ii.B.5 above;
 - viii. The calculation of kg (lb) of organic HAP emitted per kg (lb) coating solids used for the compliance option(s) the Permittee used, as specified below:
 - A. For the compliant material option, an example calculation of the organic HAP content for one coating, using Equation 1 of Section 2.1 B.6.c.i.B.3 above; and
 - B. For the emission rate without add-on controls option, the calculation of the total mass of organic HAP emissions for each month; the calculation of the total mass of coating solids used each month; and the calculation of the 12-month organic HAP emission rate using Equations 1 and 1A through 1C, 2, and 3, respectively, of Sections 2.1 B.6.c.ii.B.5 through 7 above;

Recordkeeping [63.4530]

- g. The Permittee shall collect and keep records of the data and information specified below. Failure to collect and keep these records is a deviation from the applicable standard.
- i. A copy of each notification and report submitted to comply with this subpart, and the documentation supporting each notification and report;

- ii. A current copy of information provided by materials suppliers or manufacturers, such as manufacturer's formulation data, or test data used to determine the mass fraction of organic HAP and density for each coating, thinner and/or other additive, and cleaning material, and the mass fraction of coating solids for each coating. If the Permittee conducted testing to determine mass fraction of organic HAP, density, or mass fraction of coating solids, he shall keep a copy of the complete test report. If the Permittee uses information provided by the manufacturer or supplier of the material that was based on testing, he shall keep the summary sheet of results provided by the manufacturer or supplier. The Permittee is not required to obtain the test report or other supporting documentation from the manufacturer or supplier;
- iii. For each compliance period, the records specified below:
 - A. A record of the coating operations on which the Permittee used each compliance option and the time periods (beginning and ending dates and times) for each option;
 - B. For the compliant material option, a record of the calculation of the organic HAP content for each coating, using Equation 1 of Section 2.1 B.6.c.i.B.3 above; and
 - C. For the emission rate without add-on controls option, a record of the calculation of the total mass of organic HAP emissions for the coatings, thinners and/or other additives, and cleaning materials used each month using Equations 1, 1A through 1C, and 2 of Sections 2.1 B.6.c.ii.B.5 through 7 above; and, if applicable, the calculation used to determine mass of organic HAP in waste materials according to Section 2.1 B.6.c.ii.B.5.(d) above; the calculation of the total mass of coating solids used each month using Equation 2 of Section 2.1 B.6.c.ii.B.6 above; and the calculation of each 12-month organic HAP emission rate using Equation 3 of Section 2.1 B.6.c.ii.B.7 above.
- iv. A record of the name and mass of each coating, thinner and/or other additive, and cleaning material used during each compliance period. If the Permittee is using the compliant material option for all coatings at the source, he may maintain purchase records for each material used rather than a record of the mass used;
- v. A record of the mass fraction of organic HAP for each coating, thinner and/or other additive, and cleaning material used during each compliance period;
- vi. A record of the mass fraction of coating solids for each coating used during each compliance period;
- vii. If the Permittee uses an allowance in Equation 1 of Section 2.1 B.6.c.ii.B.5 above for organic HAP contained in waste materials sent to or designated for shipment to a treatment, storage, and disposal facility (TSDF), he shall keep records in accordance with 40 CFR 63.4350(g).

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if the above records are not maintained.

Reporting [63.4520]

- h. The Permittee shall submit a summary report of the monitoring and recordkeeping activities postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. The first semiannual reporting period begins on February 01, 2008 ends on June 30, 2008. All instances of deviations from the requirements of this permit must be clearly identified. The report shall contain the following information:
 - i. Company name and address;
 - ii. Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report
 - iii. Date of report and beginning and ending dates of the reporting period;
 - iv. Identification of the compliance option or options specified in Section 2.1 B.6.c above that you used on each coating operation during the reporting period. If the Permittee switched between compliance options during the reporting period, he shall report the beginning and ending dates for each option used;
 - v. If the Permittee used the emission rate without add-on controls compliance option (Section 2.1 B.6.c.ii above), the calculation results for each rolling 12-month organic HAP emission rate during the 6-month reporting period
 - viii. If there were no deviations from the emission limitations in Section 2.1 B.6.b. above that apply, a statement that there were no deviations from the emission limitations during the reporting period
 - ix. If the Permittee used the compliant material option and there was a deviation from the applicable organic HAP content requirements in Section 2.1 B.6.b. above, the following information:
 - A. Identification of each coating used that deviated from the applicable emission limit, and each thinner and/or other additive, and cleaning material used that contained organic HAP, and the dates and time periods each was used;
 - B. The calculation of the organic HAP content (using Equation 1 of Section 2.1 B.6.c.i.B.3 above) for each coating identified above. The Permittee does not need to submit background data supporting this calculation (e.g., information provided by coating suppliers or manufacturers, or test reports);
 - C. The determination of mass fraction of organic HAP for each thinner and/or other additive, and cleaning material identified above. The Permittee does not need to submit background data supporting this calculation (e.g., information provided by material suppliers or manufacturers, or test reports); and

- D A statement of the cause of each deviation; and
- x. If the Permittee used the emission rate without add-on controls option and there was a deviation from the applicable emission limit in Section 2.1 B.6.b. above, the following information:
 - A. The beginning and ending dates of each compliance period during which the 12-month organic HAP emission rate exceeded the applicable emission limit in Section 2.1 B.6.b. above;
 - B. The calculations used to determine the 12-month organic HAP emission rate for the compliance period in which the deviation occurred. The Permittee shall submit the calculations for Equations 1, 1A through 1C, 2, and 3 of Sections 2.1 B.6.c.ii.B.5 through 7 above; and if applicable, the calculation used to determine mass of organic HAP in waste materials according to Section 2.1 B.6.c.ii.B.5 above. The Permittee does not need to submit background data supporting these calculations (e.g., information provided by materials suppliers or manufacturers, or test reports); and
 - C. A statement of the cause of each deviation.

**7. 15A NCAC 2D .1111 [40 CFR Part 63 Subpart Mmmm]:
NESHAP for Surface Coating of Miscellaneous Metal Parts and Products**

- a. The Permittee shall comply with all applicable provisions contained in Environmental Management Commission Standard 15A NCAC 2D .1111, "Maximum Achievable Control Technology" as promulgated in 40 CFR 63, Subpart Mmmm, "National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products", by January 2, 2007 or as amended by the rule for the applicable existing sources as detailed in the equipment table.

Emission Limits [63.3890]

- b. For each existing general use coating affected source, the Permittee shall limit organic HAP emissions to no more than 0.31 kg (2.6 lb) organic HAP per liter (gal) coating solids used during each 12-month compliance period.

Compliance Options [40 CFR 63.3891]

- c. As of the compliance date stated in section 2.1.B.7.a, the Permittee shall demonstrate compliance with 40 CFR 63, Subpart Mmmm by demonstrating compliance with 40 CFR 63, Subpart Pppp as detailed in Section 2.1.B.6 above.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if it does not conduct a monthly compliance demonstration as required by Section 2.1.B.6.c above or if the compliance demonstration shows an exceedance of the emission limitations in Section 2.1.B.6.b. above.

Notifications [63.3910]

- d. The Permittee shall submit the notifications in 63.7(b) and (c), 63.8(f)(4), and 63.9(b) through (e) and (h) that apply to you by the dates specified in those sections, except as provided in Section 2.1.B.7.e below.
- e. The Permittee shall submit the notification of compliance status required by 63.9(h) by **March 1, 2008** or as amended by the rule. The notification of compliance status must contain the following information and the information in 63.9(h).
 - i. Company name and address;
 - ii. Statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report;
 - iii. Date of the report and beginning and ending dates of the reporting period;
 - iv. Identification of the compliance option or options specified in Section 2.1.B.6 .c above that you used on each coating operation during the initial compliance period;
 - v. Statement of whether or not the affected source achieved the emission limitations for the initial compliance period;
 - vi. If the Permittee had a deviation, include the following information:
 - A. A description and statement of the cause of the deviation; and
 - B. If the Permittee failed to meet the applicable emission limit in Section 2.1.B.6.b above, include all the calculations used to determine the kg (lb) of organic HAP emitted per kg (lb) coating solids used. The Permittee does not need to submit information provided by the materials' suppliers or manufacturers, or test reports
 - vii. For each of the following data items that are required by the compliance option(s) the Permittee used to demonstrate compliance with the emission limit, an example of how the Permittee determined the value, including calculations and supporting data. Supporting data may include a copy of the information provided by the supplier or manufacturer of the example coating or material, or a summary of the results of testing conducted according to Sections 2.1.B.6.c.i.B.1, 2 or 3 above. The Permittee does not need to submit copies of any test reports.

- A. Mass fraction of organic HAP for one coating, for one thinner and/or other additive, and for one cleaning material;
 - B. Mass fraction of coating solids for one coating;
 - C. Density for one coating, one thinner and/or other additive, and one cleaning material, except that if the Permittee uses the compliant material option, only the example coating density is required; and
 - D. The amount of waste materials and the mass of organic HAP contained in the waste materials for which the Permittee is claiming an allowance in Equation 1 of Section 2.1.B.6.c.ii.B.5 above;
- viii. The calculation of kg (lb) of organic HAP emitted per kg (lb) coating solids used for the compliance option(s) the Permittee used, as specified below:
- A. For the compliant material option, an example calculation of the organic HAP content for one coating, using Equation 1 of Section 2.1.B.6.c.i.B.3 above; and
 - B. For the emission rate without add-on controls option, the calculation of the total mass of organic HAP emissions for each month; the calculation of the total mass of coating solids used each month; and the calculation of the 12-month organic HAP emission rate using Equations 1 and 1A through 1C, 2, and 3, respectively, of Sections 2.1.B.6.c.ii.B.5 through 7 above.

Recordkeeping [63.3930]

- f. The Permittee shall collect and keep records of the data and information as specified in Section 2.1.B.6.g above.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if the records are not maintained as required by Section 2.1.B.6 .g above.

Reporting [63.3920]

- g. The Permittee shall submit report as specified in Section 2.1.B.6 .h above.

8. 15A NCAC 2D .0705 - EXISTING FACILITIES AND SIC CALLS for TOXIC AIR POLLUTANT EMISSIONS LIMITATION REQUIREMENT

Pursuant to 15 A NCAC 2Q .0705(B)(1), the Permittee shall submit to the DAQ by March 28, 2008 (date for submittal of notification of compliance status and permit application for last applicable MACT - 40 CFR 63, Subpart M), a demonstration that facility wide emissions (does not include emissions from boilers burning virgin fuel) of toxic air pollutants do not exceed acceptable ambient levels contained in 15A NCAC 2D .1100, or demonstrate that emissions from the affected sources are less than the toxic pollutant exemption rates (TPERs) contained in 15A NCAC 2Q .0711. The submittal shall include:

- a. calculations for the determination of each TAP,
- b. a list that pairs emission sources to emission points using the permit identification numbers (for modeled sources),
- c. the emissions rates for each emission source and emission point for each TAP above the TPER,
- d. the list of TAPs that are emitted below the TPERs,
- e. modeling protocol for all TAPs above the TPERs, and
- f. ambient impact analysis for each TAP above its respective TPER.

Application forms required include forms AA, D1 (TAPS only), and B (for each TAP emission unit, TAPS only).

C. Combustion Sources

**22.5 million Btu per hour natural gas-fired heater (ID No. ES-PP02),
Two natural gas/No. 2 fuel oil-fired boilers (25.1 and 16.7 million Btu per hour heat input, ID Nos. ES-CB600 and ES-CONT400, respectively), and
Natural gas-fired process hot water heater (15 million Btu per hour heat input; ID No. ES-1)**

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	Firing natural gas and/or No. 2 fuel oil	15A NCAC 2D .0503

	Particulate emissions shall not exceed 0.37 pounds per million Btu heat input from each of the three boilers (ID Nos. ES-PP02, ES-CB600, and ES-CONT400); and 0.34 pounds per million Btu heat input from the hot water heater (ID No. ES-1)	
Sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 2D .0516
Visible emissions	20 percent opacity	15A NCAC 2D .0521
NA	Recordkeeping requirements for hot water heat <i>ID No. ES-1 only</i>	15A NCAC 2D .0524 40 CFR 60, Subpart Dc

1. 15A NCAC 2D .0503: PARTICULATES FROM FUEL BURNING INDIRECT HEAT EXCHANGERS

- a. Emissions of particulate matter from the combustion of natural gas and/or No. 2 fuel oil that are discharged from each of the three boilers (ID Nos. ES-PP02, ES-CB600, and ES-CONT400) shall not exceed 0.37 pounds per million Btu heat input.
- b. Emissions of particulate matter from the combustion of natural gas that are discharged from the hot water heater (ID No. ES-1) shall not exceed 0.34 pounds per million Btu heat input.

Testing [15A NCAC 2D .0501(c)(3)]

- c. If emissions testing is required, the testing shall be performed in accordance General Condition JJ. If the results of this test are above the limit given in Section 2.1 C.a. or b. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0503.

Monitoring/Recordkeeping/Reporting [15A NCAC 2Q .0508 (f)]

No monitoring/recordkeeping/reporting is required for particulate emissions from the firing of natural gas or No. 2 fuel oil in these sources.

2. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

- a. Emissions of sulfur dioxide from these sources shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard.

Testing [15A NCAC 2D .0501(c)(4)]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .0501(c)(4) and General Condition JJ found in Section 3. If the results of this test are above the limit given in Section 2.1 C.2.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

Monitoring/Recordkeeping/Reporting [15A NCAC 2Q .0508(f)]

- c. No monitoring/recordkeeping/reporting is required for sulfur dioxide emissions from the firing of natural gas or No. 2 fuel oil in these sources.

3. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources shall not be more than 20 percent opacity when averaged over a six-minute period except that six-minute periods averaging not more than 87 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(d)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .0501(c)(8) and General Condition JJ. If the results of this test are above the limit given in Section 2.1 C.3.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a month the Permittee shall observe the emission points of these sources for any visible emissions above normal. The monthly observation must be made for each month of the calendar year period to ensure compliance with this requirement. If visible emissions from these sources are observed to be above normal, the Permittee shall either:
 - i. take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or
 - ii. demonstrate that the percent opacity from the emission points of the emission source in accordance with

15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 C.3.a. above.

If the above-normal emissions are not corrected per (i) above or if the demonstration in (ii) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of inspection and maintenance shall be maintained in a log (written or electronic format) on site and made available to an authorized representative upon request. The log shall record the following:
- i. the date and time of inspections;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508 (f)]

- e. The Permittee shall submit a summary report of the observations by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

4. 15A NCAC 2D .0524: NSPS 40 CFR PART 60 SUBPART Dc (Hot water heater ID No. ES-1 ONLY)

- a. The Permittee shall comply with all applicable provisions, including the notification, testing, reporting, recordkeeping, and monitoring requirements contained in Environmental Management Commission Standard 15A NCAC 2D .0524 "New Source Performance Standards (NSPS) as promulgated in 40 CFR Part 60 Subpart Dc, including Subpart A "General Provisions." [15A NCAC 2D .0524]

Recordkeeping [15A NCAC 2Q .0508(f)]

- b. In addition to any other recordkeeping required by 40 CFR, 60.48c or recordkeeping requirements of the EPA, the Permittee shall record and maintain records of the amounts of natural gas fired during each month for the hot water heater (ID No. ES-1).

SECTION 3 - GENERAL CONDITIONS

This section describes terms and conditions applicable to this Title V facility. All references to the "permit" in this section apply only to Part I of the permit.

A. General Provisions [NCGS 143-215 and 15A NCAC 2Q .0508(i)(16)]

1. Terms not otherwise defined in this permit shall have the meaning assigned to such terms as defined in 15A NCAC 2D and 2Q.
2. The terms, conditions, requirements, limitations, and restrictions set forth in this permit are binding and enforceable pursuant to NCGS 143-215.114A and 143-215.114B, including assessment of civil and/or criminal penalties. Any unauthorized deviation from the conditions of this permit may constitute grounds for revocation and/or enforcement action by the DAQ.
3. This permit is not a waiver of or approval of any other Department permits that may be required for other aspects of the facility, which are not addressed in this permit.
4. This permit does not relieve the Permittee from liability for harm or injury to human health or welfare, animal or plant life, or property caused by the construction or operation of this permitted facility, or from penalties therefore, nor does it allow the Permittee to cause pollution in contravention of state laws or rules, unless specifically authorized by an order from the North Carolina Environmental Management Commission.
5. Except as identified as state-only requirements in this permit, all terms and conditions contained herein shall be enforceable by the DAQ, the EPA, and citizens of the United States as defined in the Federal Clean Air Act.
6. Any stationary source of air pollution shall not be operated, maintained, or modified without the appropriate and valid permits issued by the DAQ, unless the source is exempted by rule. The DAQ may issue a permit only after it receives reasonable assurance that the installation will not cause air pollution in violation of any of the applicable requirements. A permitted installation may only be operated, maintained, constructed, expanded, or modified in a manner that is consistent with the terms of this permit.

B. Permit Availability [15A NCAC 2Q .0507(k) and .0508(i)(9)(B)]

The Permittee shall have available at the facility a copy of this permit and shall retain for the duration of the permit term one complete copy of the application and any information submitted in support of the application package. The permit and application shall be made available to an authorized representative of Department of Environment and Natural Resources upon request.

C. **Severability Clause** [15A NCAC 2Q .0508(i)(2)]

In the event of an administrative challenge to a final and binding permit in which a condition is held to be invalid, the provisions in this permit are severable so that all requirements contained in the permit, except those held to be invalid, shall remain valid and must be complied with.

D. **Submissions** [15A NCAC 2Q .0507(e) and 2Q .0508(i)(16)]

Except as otherwise specified herein, two copies of all documents, reports, test data, monitoring data, notifications, request for renewal, and any other information required by this permit shall be submitted to the appropriate Regional Office. Refer to the Regional Office address on the cover page of this permit. For continuous emissions monitoring systems (CEMS) reports, continuous opacity monitoring systems (COMS) reports, quality assurance (QA)/quality control (QC) reports, acid rain CEM certification reports, and NOx budget CEM certification reports, one copy shall be sent to the appropriate Regional Office and one copy shall be sent to:

Supervisor, Stationary Source Compliance
North Carolina Division of Air Quality
1641 Mail Service Center
Raleigh, NC 27699-1641

E. **Duty to Comply** [15A NCAC 2Q .0508(i)(2)]

The Permittee shall comply with all terms, conditions, requirements, limitations and restrictions set forth in this permit. Noncompliance with any permit condition except conditions identified as state-only requirements constitutes a violation of the Federal Clean Air Act. Noncompliance with any permit condition is grounds for enforcement action, for permit termination, revocation and reissuance, or modification, or for denial of a permit renewal application.

F. **Circumvention** - STATE ENFORCEABLE ONLY

The facility shall be properly operated and maintained at all times in a manner that will effect an overall reduction in air pollution. Unless otherwise specified by this permit, no emission source may be operated without the concurrent operation of its associated air pollution control device(s) and appurtenances.

G. **Permit Modifications**

1. Administrative Permit Amendments [15A NCAC 2Q .0514]
The Permittee shall submit an application for an administrative permit amendment in accordance with 15A NCAC 2Q .0514.
2. Transfer in Ownership or Operation and Application Submittal Content [15A NCAC 2Q .0524 and 2Q .0505]
The Permittee shall submit an application for an ownership change in accordance with 15A NCAC 2Q.0524 and 2Q .0505.
3. Minor Permit Modifications [15A NCAC 2Q .0515]
The Permittee shall submit an application for a minor permit modification in accordance with 15A NCAC 2Q .0515.
4. Significant Permit Modifications [15A NCAC 2Q .0516]
The Permittee shall submit an application for a significant permit modification in accordance with 15A NCAC 2Q .0516.
5. Reopening for Cause [15A NCAC 2Q .0517]
The Permittee shall submit an application for reopening for cause in accordance with 15A NCAC 2Q .0517.

H. **Changes Not Requiring Permit Modifications**

1. Section 502(b)(10) Changes [15A NCAC 2Q .0523(a)]
 - a. "Section 502(b)(10) changes" means changes that contravene an express permit term or condition. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.
 - b. The Permittee may make Section 502(b)(10) changes without having the permit revised if:
 - i. the changes are not a modification under Title I of the Federal Clean Air Act;

- ii. the changes do not cause the allowable emissions under the permit to be exceeded;
 - iii. the Permittee notifies the Director and EPA with written notification at least seven days before the change is made; and
 - iv. the Permittee shall attach the notice to the relevant permit.
- c. The written notification shall include:
- i. a description of the change;
 - ii. the date on which the change will occur;
 - iii. any change in emissions; and
 - iv. any permit term or condition that is no longer applicable as a result of the change.
- d. Section 502(b)(10) changes shall be made in the permit the next time that the permit is revised or renewed, whichever comes first.
2. Off Permit Changes [15A NCAC 2Q .0523(b)]
The Permittee may make changes in the operation or emissions without revising the permit if:
- a. the change affects only insignificant activities and the activities remain insignificant after the change; or
 - b. the change is not covered under any applicable requirement.
3. Emissions Trading [15A NCAC 2Q .0523(c)]
To the extent that emissions trading is allowed under 15A NCAC 2D, including subsequently adopted maximum achievable control technology standards, emissions trading shall be allowed without permit revision pursuant to 15A NCAC 2Q .0523(c).

I.A. Reporting Requirements for Excess Emissions and Permit Deviations

[15A NCAC 2D .0535(f) and 2Q .0508(f)(2)]

“Excess Emissions” - means an emission rate that exceeds any applicable emission limitation or standard allowed by any rule in Sections .0500, .0900, .1200, or .1400 of Subchapter 2D; or by a permit condition; or that exceeds an emission limit established in a permit issued under 15A NCAC 2Q .0700. (*Note: Definitions of excess emissions under 2D .1110 and 2D .1111 shall apply where defined by rule.*)

“Deviations” - for the purposes of this condition, any action or condition not in accordance with the terms and conditions of this permit including those attributable to upset conditions as well as excess emissions as defined above lasting less than four hours.

Excess Emissions

1. If a source is required to report excess emissions under NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or the operating permit provides for periodic (e.g., quarterly) reporting of excess emissions, reporting shall be performed as prescribed therein.
2. If the source is not subject to NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or these rules do NOT define "excess emissions," the Permittee shall report excess emissions in accordance with 15A NCAC 2D .0535 as follows:
 - a. Pursuant to 15A NCAC 2D .0535, if excess emissions last for more than four hours resulting from a malfunction, a breakdown of process or control equipment, or any other abnormal condition, the owner or operator shall:
 - i. notify the Regional Supervisor or Director of any such occurrence by 9:00 a.m. Eastern Time of the Division's next business day of becoming aware of the occurrence and provide:
 - name and location of the facility;
 - nature and cause of the malfunction or breakdown;
 - time when the malfunction or breakdown is first observed;
 - expected duration; and
 - estimated rate of emissions;
 - ii. notify the Regional Supervisor or Director immediately when corrective measures have been accomplished; and
 - iii. submit to the Regional Supervisor or Director within 15 days a written report as described in 15A NCAC 2D .0535(f)(3).

Permit Deviations

3. Pursuant to 15A NCAC 2Q .0508(f)(2), the Permittee shall report deviations from permit requirements (terms and conditions) as follows:
 - a. Notify the Regional Supervisor or Director of all other deviations from permit requirements not covered under 15A NCAC 2D .0535 quarterly. A written report to the Regional Supervisor shall include the probable cause of such deviation and any corrective actions or preventative actions taken. The responsible official shall certify all deviations from permit requirements.

I.B. **Other Requirements under 15A NCAC 2D .0535**

The Permittee shall comply with all other applicable requirements contained in 15A NCAC 2D .0535, including 15A NCAC 2D .0535(c) as follows:

1. Any excess emissions that do not occur during start-up and shut-down shall be considered a violation of the appropriate rule unless the owner or operator of the sources demonstrates to the Director, that the excess emissions are a result of a malfunction. The Director shall consider, along with any other pertinent information, the criteria contained in 15A NCAC 2D .0535(c)(1) through (7).
2. 15A NCAC 2D .0535(g). Excess emissions during start-up and shut-down shall be considered a violation of the appropriate rule if the owner or operator cannot demonstrate that excess emissions are unavoidable.

J. **Emergency Provisions** [40 CFR 70.6(g)]

The Permittee shall be subject to the following provisions with respect to emergencies:

1. An emergency means any situation arising from sudden and reasonably unforeseeable events beyond the control of the facility, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation, or operator error.
2. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in 3. below are met.
3. The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that include information as follows:
 - a. an emergency occurred and the Permittee can identify the cause(s) of the emergency;
 - b. the permitted facility was at the time being properly operated;
 - c. during the period of the emergency the Permittee took all reasonable steps to minimize levels of emissions that exceeded the standards or other requirements in the permit; and
 - d. the Permittee submitted notice of the emergency to the DAQ within two working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, steps taken to mitigate emissions, and corrective actions taken.
4. In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
5. This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein.

K. **Permit Renewal** [15A NCAC 2Q .0508(e) and 2Q .0513(b)]

This permit is issued for a fixed term of five years for facilities subject to Title IV requirements and for a term not to exceed five years in the case of all other facilities. This permit shall expire at the end of its term. Permit expiration terminates the facility's right to operate unless a complete renewal application is submitted at least nine months before the date of permit expiration. If the Permittee or applicant has complied with 15A NCAC 2Q .0512(b)(1), this permit shall not expire until the renewal permit has been issued or denied. All terms and conditions of this permit shall remain in effect until the renewal permit has been issued or denied.

L. **Need to Halt or Reduce Activity Not a Defense** [15A NCAC 2Q .0508(i)(4)]

It shall not be a defense for a Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

M. **Duty to Provide Information (submittal of information)** [15A NCAC 2Q .0508(i)(9)]

1. The Permittee shall furnish to the DAQ, in a timely manner, any reasonable information that the Director may request in **writing** to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit.
2. The Permittee shall furnish the DAQ copies of records required to be kept by the permit when such copies are requested by the Director. For information claimed to be confidential, the Permittee may furnish such records directly to the EPA upon request along with a claim of confidentiality.

N. **Duty to Supplement** [15A NCAC 2Q .0507(f)]

The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to the DAQ. The Permittee

shall also provide additional information as necessary to address any requirement that becomes applicable to the facility after the date a complete permit application was submitted but prior to the release of the draft permit.

O. **Retention of Records** [15A NCAC 2Q .0508(f) and 2Q .0508 (l)]

The Permittee shall retain records of all required monitoring data and supporting information for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring information, and copies of all reports required by the permit. These records shall be maintained in a form suitable and readily available for expeditious inspection and review. Any records required by the conditions of this permit shall be kept on site and made available to DAQ personnel for inspection upon request.

P. **Compliance Certification** [15A NCAC 2Q .0508(n)]

The Permittee shall submit to the DAQ and the EPA (Air and EPCRA Enforcement Branch, EPA, Region 4, 61 Forsyth Street, Atlanta, GA 30303) postmarked on or before March 1 a compliance certification (for the preceding calendar year) by a responsible official with all federally-enforceable terms and conditions in the permit, including emissions limitations, standards, or work practices. It shall be the responsibility of the current owner to submit a compliance certification for the entire year regardless of who owned the facility during the year. The compliance certification shall comply with additional requirements as may be specified under Sections 114(a)(3) or 504(b) of the Federal Clean Air Act. The compliance certification shall specify:

1. the identification of each term or condition of the permit that is the basis of the certification;
2. the compliance status (with the terms and conditions of the permit for the period covered by the certification);
3. whether compliance was continuous or intermittent; and
4. the method(s) used for determining the compliance status of the source during the certification period.

Q. **Certification by Responsible Official** [15A NCAC 2Q .0520]

A responsible official shall certify the truth, accuracy, and completeness of any application form, report, or compliance certification required by this permit. All certifications shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

R. **Permit Shield for Applicable Requirements** [15A NCAC 2Q .0512]

1. Compliance with the terms and conditions of this permit shall be deemed compliance with applicable requirements, where such applicable requirements are included and specifically identified in the permit as of the date of permit issuance.
2. A permit shield shall not alter or affect:
 - a. the power of the Commission, Secretary of the Department, or Governor under NCGS 143-215.3(a)(12), or EPA under Section 303 of the Federal Clean Air Act;
 - b. the liability of an owner or operator of a facility for any violation of applicable requirements prior to the effective date of the permit or at the time of permit issuance;
 - c. the applicable requirements under Title IV; or
 - d. the ability of the Director or the EPA under Section 114 of the Federal Clean Air Act to obtain information to determine compliance of the facility with its permit.
3. A permit shield does not apply to any change made at a facility that does not require a permit or permit revision made under 15A NCAC 2Q .0523.
4. A permit shield does not extend to minor permit modifications made under 15A NCAC 2Q .0515.

S. **Termination, Modification, and Revocation of the Permit** [15A NCAC 2Q .0519]

The Director may terminate, modify, or revoke and reissue this permit if:

1. the information contained in the application or presented in support thereof is determined to be incorrect;
2. the conditions under which the permit or permit renewal was granted have changed;
3. violations of conditions contained in the permit have occurred;
4. the EPA requests that the permit be revoked under 40 CFR 70.7(g) or 70.8(d); or
5. the Director finds that termination, modification, or revocation and reissuance of the permit is necessary to carry out the purpose of NCGS Chapter 143, Article 21B.

T. **Insignificant Activities** [15A NCAC 2Q .0503]

Because an emission source or activity is insignificant does not mean that the emission source or activity is exempted from any applicable requirement or that the owner or operator of the source is exempted from demonstrating compliance with any applicable requirement. The Permittee shall have available at the facility at all times and made available to an

authorized representative upon request, documentation, including calculations, if necessary, to demonstrate that an emission source or activity is insignificant.

U. **Property Rights** [15A NCAC 2Q .0508(i)(8)]

This permit does not convey any property rights in either real or personal property or any exclusive privileges.

V. **Inspection and Entry** [15A NCAC 2Q .0508(l) and NCGS 143-215.3(a)(2)]

1. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow the DAQ, or an authorized representative, to perform the following:
 - a. enter the Permittee's premises where the permitted facility is located or emissions-related activity is conducted, or where records are kept under the conditions of the permit;
 - b. have access to and copy, at reasonable times, any records that are required to be kept under the conditions of the permit;
 - c. inspect at reasonable times and using reasonable safety practices any source, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - d. sample or monitor substances or parameters, using reasonable safety practices, for the purpose of assuring compliance with the permit or applicable requirements at reasonable times.Nothing in this condition shall limit the ability of the EPA to inspect or enter the premises of the Permittee under Section 114 or other provisions of the Federal Clean Air Act.
2. No person shall refuse entry or access to any authorized representative of the DAQ who requests entry for purposes of inspection, and who presents appropriate credentials, nor shall any person obstruct, hamper, or interfere with any such authorized representative while in the process of carrying out his official duties. Refusal of entry or access may constitute grounds for permit revocation and assessment of civil penalties.

W. **Annual Fee Payment** [15A NCAC 2Q .0508(i)(10)]

1. The Permittee shall pay all fees in accordance with 15A NCAC 2Q .0200.
2. Payment of fees may be by check or money order made payable to the N.C. Department of Environment and Natural Resources. Annual permit fee payments shall refer to the permit number.
3. If, within 30 days after being billed, the Permittee fails to pay an annual fee, the Director may initiate action to terminate the permit under 15A NCAC 2Q .0519.

X. **Annual Emission Inventory Requirements** [15A NCAC 2Q .0207]

The Permittee shall report by **June 30 of each year** the actual emissions of each air pollutant listed in 15A NCAC 2Q .0207(a) from each emission source within the facility during the previous calendar year. The report shall be in or on such form as may be established by the Director. The accuracy of the report shall be certified by a responsible official of the facility.

Y. **Confidential Information** [15A NCAC 2Q .0107 and 2Q. 0508(i)(9)]

Whenever the Permittee submits information under a claim of confidentiality pursuant to 15A NCAC 2Q .0107, the Permittee may also submit a copy of all such information and claim directly to the EPA upon request. All requests for confidentiality must be in accordance with 15A NCAC 2Q .0107.

Z. **Construction and Operation Permits** [15A NCAC 2Q .0100 and .0300]

A construction and operating permit shall be obtained by the Permittee for any proposed new or modified facility or emission source which is not exempted from having a permit prior to the beginning of construction or modification, in accordance with all applicable provisions of 15A NCAC 2Q .0100 and .0300.

AA. **Standard Application Form and Required Information** [15A NCAC 2Q .0505 and .0507]

The Permittee shall submit applications and required information in accordance with the provisions of 15A NCAC 2Q .0505 and .0507.

BB. **Financial Responsibility and Compliance History** [15A NCAC 2Q .0507(d)(3)]

The DAQ may require an applicant to submit a statement of financial qualifications and/or a statement of substantial compliance history.

CC. **Refrigerant Requirements (Stratospheric Ozone and Climate Protection)** [15A NCAC 2Q .0501(e)]

1. If the Permittee has appliances or refrigeration equipment, including air conditioning equipment, which use Class I or II ozone-depleting substances such as chlorofluorocarbons and hydrochlorofluorocarbons listed as refrigerants in 40

CFR Part 82 Subpart A Appendices A and B, the Permittee shall service, repair, and maintain such equipment according to the work practices, personnel certification requirements, and certified recycling and recovery equipment specified in 40 CFR Part 82 Subpart F.

2. The Permittee shall not knowingly vent or otherwise release any Class I or II substance into the environment during the repair, servicing, maintenance, or disposal of any such device except as provided in 40 CFR Part 82 Subpart F.
3. The Permittee shall comply with all reporting and recordkeeping requirements of 40 CFR 82.166. Reports shall be submitted to the EPA or its designee as required.

DD. **Prevention of Accidental Releases - Section 112(r)** [15A NCAC 2Q .0508(h)]

If the Permittee is required to develop and register a Risk Management Plan with EPA pursuant to Section 112(r) of the Clean Air Act, then the Permittee is required to register this plan in accordance with 40 CFR Part 68.

EE. **Prevention of Accidental Releases General Duty Clause - Section 112(r)(1) - FEDERALLY-ENFORCEABLE ONLY**

Although a risk management plan may not be required, if the Permittee produces, processes, handles, or stores any amount of a listed hazardous substance, the Permittee has a general duty to take such steps as are necessary to prevent the accidental release of such substance and to minimize the consequences of any release.

FF. **Title IV Allowances** [15A NCAC 2Q .0508(i)(1)]

This permit does not limit the number of Title IV allowances held by the Permittee, but the Permittee may not use allowances as a defense to noncompliance with any other applicable requirement. The Permittee's emissions may not exceed any allowances that the facility lawfully holds under Title IV of the Federal Clean Air Act.

GG. **Air Pollution Emergency Episode** [15A NCAC 2D .0300]

Should the Director of the DAQ declare an Air Pollution Emergency Episode, the Permittee will be required to operate in accordance with the Permittee's previously approved Emission Reduction Plan or, in the absence of an approved plan, with the appropriate requirements specified in 15A NCAC 2D .0300.

HH. **Registration of Air Pollution Sources** [15A NCAC 2D .0200]

The Director of the DAQ may require the Permittee to register a source of air pollution. If the Permittee is required to register a source of air pollution, this registration and required information will be in accordance with 15A NCAC 2D .0202(b).

II. **Ambient Air Quality Standards** [15A NCAC 2D .0501(e)]

In addition to any control or manner of operation necessary to meet emission standards specified in this permit, any source of air pollution shall be operated with such control or in such manner that the source shall not cause the ambient air quality standards in 15A NCAC 2D .0400 to be exceeded at any point beyond the premises on which the source is located. When controls more stringent than named in the applicable emission standards in this permit are required to prevent violation of the ambient air quality standards or are required to create an offset, the permit shall contain a condition requiring these controls.

JJ. **General Emissions Testing and Reporting Requirements** [15A NCAC 2Q .0508(i)(16)]

If emissions testing is required by this permit or the DAQ or if the Permittee submits emissions testing to the DAQ in support of a permit application, the Permittee shall perform such testing in accordance with the appropriate EPA reference method(s) as approved by the DAQ and follow the procedures outlined below. The Permittee must request **in writing** and receive approval from the DAQ for an alternate test method or procedure.

1. The Permittee shall submit a completed Protocol Submittal Form to the DAQ Regional Supervisor at least 45 days prior to the scheduled test date. A copy of the Protocol Submittal Form may be obtained from the Regional Supervisor.
2. The Permittee shall notify the Regional Supervisor of the specific test dates at least 15 days prior to testing in order to afford the DAQ the opportunity to have an observer on-site during the sampling program.
3. During all sampling periods, the Permittee shall operate the emission source(s) under maximum normal operating conditions or alternative operating conditions as deemed appropriate by the Regional Supervisor or his delegate.
4. The Permittee shall submit **two** copies of the test report to the DAQ. The test report shall contain at a minimum the following information:
 - a. a certification of the test results by sampling team leader and facility representative;
 - b. a summary of emissions results and text detailing the objectives of the testing program, the applicable state and federal regulations, and conclusions about the testing and compliance status of the emission source(s);

- c. a detailed description of the tested emission source(s) and sampling location(s) process flow diagrams, engineering drawings, and sampling location schematics should be included as necessary;
 - d. all field, analytical, and calibration data necessary to verify that the testing was performed as specified in the applicable test methods;
 - e. example calculations for at least one test run using equations in the applicable test methods and all test results including intermediate parameter calculations; and
 - f. documentation of facility operating conditions during all testing periods and an explanation relating these operating conditions to maximum normal operation. If necessary, provide historical process data to verify maximum normal operation.
5. The testing requirement(s) shall be considered satisfied only upon written approval of the test results by the DAQ.
 6. The DAQ will review emission test results with respect exclusively to the specified testing objectives as proposed by the Permittee and approved by the DAQ. The use of the test results beyond the stated objectives remains subject to the approval of the DAQ.

KK. Reopening for Cause [15A NCAC 2Q .0517]

1. A permit shall be reopened and revised under the following circumstances:
 - a. additional applicable requirements become applicable to a facility with remaining permit term of three or more years;
 - b. additional requirements (including excess emission requirements) become applicable to a source covered by Title IV;
 - c. the Director or EPA finds that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit; or
 - d. the Director or EPA determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
2. Any permit reopening shall be completed or a revised permit issued within 18 months after the applicable requirement is promulgated. No reopening is required if the effective date of the requirement is after the expiration of the permit term unless the term of the permit was extended pursuant to 15A NCAC 2Q .0513(c).
3. Except for the state-enforceable only portion of the permit, the procedures set out in 15A NCAC 2Q .0507, .0521, or .0522 shall be followed to reissue the permit. If the State-enforceable only portion of the permit is reopened, the procedures in 15A NCAC 2Q .0300 shall be followed. The proceedings shall affect only those parts of the permit for which cause to reopen exists.
4. The Director shall notify the Permittee at least 60 days in advance of the date that the permit is to be reopened, except in cases of imminent threat to public health or safety the notification period may be less than 60 days.
5. Within 90 days, or 180 days if the EPA extends the response period, after receiving notification from the EPA that a permit needs to be terminated, modified, or revoked and reissued, the Director shall send to the EPA a proposed determination of termination, modification, or revocation and reissuance, as appropriate.

LL. Reporting Requirements for Non-Operating Equipment [15A NCAC 2Q .0508(i)(16)]

The Permittee shall maintain a record of operation for permitted equipment noting whenever the equipment is taken from and placed into operation. During operation the monitoring recordkeeping and reporting requirements as prescribed by the permit shall be implemented within the monitoring period.

PART II

SECTION- 1 EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES

Table 1: The following table contains a summary of all emission sources and associated air pollution control devices and appurtenances **associated with Air Quality Permit Application (4100822.07C)**:

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
ES-BTH1 and ES-BTH2*	Two dry filter-type paint lines each consisting of a sanding/prep booth (ES-	N/A	N/A

	BTH1a and ES-BTH2a), Top coat paint booth (ES-BTH1b and ES-BTH2b) and associated natural gas-fired curing oven (1.5 million Btu per hour heat input, ES-CO)		
--	-------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

* These emission sources (**ID Nos. ES-BTH-1 and ES-BTH-2**) are listed as a minor modification per 15 A NCAC 2Q .0515. The compliance certification as described in General Condition P is required. Unless otherwise notified by NC DAQ, the affected Part I terms of this permit (excluding the permit shield as described General Condition R) for this source shall become final on February 15, 2008. Until this date, the affected Part I permit terms herein reflect the proposed operating language that the Permittee shall operate this source under pursuant to 15A NCAC 2Q .0515(f).

SECTION 2: SPECIFIC LIMITATIONS AND CONDITIONS

The air emission source(s) and associated air pollution control device(s) and appurtenances listed in Section 1 are subject to the following specific terms, conditions, and limitations, including the monitoring, recordkeeping, and reporting requirements as specified herein:

1. Any air emission sources or control devices listed in Section 1 must be constructed and maintained in accordance with the provisions contained herein and constructed and operated in accordance with provisions contained in Part I of this permit. The Permittee shall comply with applicable Environmental Management Commission Regulations, including Title 15A NCAC, Subchapter 2D .0515, .0516, .0521, .0958, and .1100.
2. The Permittee shall file a Title V Air Quality Permit Application for the air emission source(s) and associated air pollution control device(s) listed in Section 1 on or before 12 months after commencing operation.
3. **NOTIFICATION REQUIREMENT** - If the proposed operational date of November 1, 2008 is not met, a revised permit is not needed. However, within 15 days after the proposed operational date is not met, the Permittee shall notify in writing the Regional Supervisor of the new proposed operational date. Any existing equipment being replaced is permitted to operate in compliance until the replacement equipment is operational

SECTION 3: GENERAL CONDITIONS:

This section describes terms and conditions applicable to the construction of the air emission source(s) and associated air pollution control device(s) listed in Section 1 and State-only emission sources listed in Part I of the permit. Unless otherwise specified herein all references to the "permit" in this section apply only to Part II of the permit.

A. Operating Conditions

All conditions for the air emission source(s) and associated air pollution control device(s) listed in Section 1 are under Part I of this permit.

B. General Provisions

1. This permit is nontransferable by the Permittee. Future owners and operators must obtain a new Air Quality Permit from the DAQ.
2. This issuance of this permit in no way absolves the Permittee of liability for any potential civil penalties which may be assessed for violations of state law which have occurred prior to the issuance date of this permit.
3. A violation of any term or condition of Part II of this permit shall subject the Permittee to enforcement pursuant to NCGS 143-215.114A, 143-215.114B, and 143-215.114C, including assessment of civil and/or criminal penalties.

C. Submissions (reports, test data, monitoring data, notifications, and requests for renewal)

Except as otherwise specified herein, two copies of all documents, reports, test data, monitoring data, notifications, request for renewal, and any other information required by this permit shall be submitted to the appropriate Regional Office. Refer to the Regional Office address on the cover page of this permit.

D. **Part II Renewal Request**

The Permittee shall request renewal of the emission source(s) and associated air pollution control device(s) listed in Section 1 at the same time as specified in Part I, Section 3 - General Condition K of this permit.

E. **Annual Fee Payment**

The Permittee shall pay all fees in accordance with 15A NCAC 2Q .0200 and in conjunction with Part I, Section 3 - General Condition W of this Air Quality Permit.

F. **Reporting Requirements**

Any of the following that would result in new or increased emissions from the emission source(s) listed in Section 1 must be reported to the Regional Supervisor, DAQ:

1. changes in the information submitted in the application;
2. changes that modify equipment or processes; or
3. changes in the quantity or quality of materials processed.

If appropriate, modifications to the permit may then be made by the DAQ to reflect any necessary changes in the permit conditions. In no case are any new or increased emissions allowed that will cause a violation of the emission limitations specified herein.

G. **Termination, Modification, and Revocation of the Permit**

The Director may terminate, modify, or revoke and reissue this permit if:

1. the information contained in the application or presented in support thereof is determined to be incorrect;
2. the conditions under which the permit or permit renewal was granted have changed;
3. violations of conditions contained in the permit have occurred; or
4. the Director finds that termination, modification, or revocation and reissuance of the permit is necessary to carry out the purpose of NCGS Chapter 143, Article 21B.

H. **Inspection and Entry**

Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow the DAQ, or an authorized representative, to perform the following:

1. enter the Permittee's premises where the permitted facility is located or emissions-related activity is conducted, or where records are kept under the conditions of the permit;
2. have access to and copy, at reasonable times, any records that are required to be kept under the conditions of the permit;
3. inspect at reasonable times and using reasonable safety practices any source, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
4. sample or monitor substances or parameters, using reasonable safety practices, for the purpose of assuring compliance with the permit or applicable requirements at reasonable times.

I. **Circumvention** - STATE ENFORCEABLE ONLY

The facility shall be properly operated and maintained at all times in a manner that will effect an overall reduction in air pollution. Unless otherwise specified by this permit, no emission source may be operated without the concurrent operation of its associated air pollution control device(s) and appurtenances.

ATTACHMENT
List of Acronyms

AOS	Alternate Operating Scenario
BACT	Best Available Control Technology
Btu	British thermal unit
CEM	Continuous Emission Monitor
CFR	Code of Federal Regulations
CAA	Clean Air Act
DAQ	Division of Air Quality
DENR	Department of Environment and Natural Resources
EMC	Environmental Management Commission
EPA	Environmental Protection Agency

FR	Federal Register
GACT	Generally Available Control Technology
HAP	Hazardous Air Pollutant
MACT	Maximum Achievable Control Technology
NCAC	North Carolina Administrative Code
NCGS	North Carolina General Statutes
NESHAPS	National Emission Standards for Hazardous Air Pollutants
NO_x	Nitrogen Oxides
NSPS	New Source Performance Standard
OAH	Office of Administrative Hearings
PM	Particulate Matter
PM₁₀	Particulate Matter with Nominal Aerodynamic Diameter of 10 Micrometers or Less
POS	Primary Operating Scenario
PSD	Prevention of Significant Deterioration
SIC	Standard Industrial Classification
SIP	State Implementation Plan
SO₂	Sulfur Dioxide
tpy	Tons Per Year
VOC	Volatile Organic Compound

