

DRAFT

date, 2008

Mr. Todd Farley
Plant Manager
Ball Metal Beverage Container Corp.
1900 Barns Street
P.O. Box 1170
Reidsville, North Carolina 27320

Dear Mr. Farley:

SUBJECT: **Air Quality Permit No. 03662T22**
 Facility ID: 7900093
 Ball Metal Beverage Container Corporation
 Reidsville Can Plant
 Reidsville, North Carolina
 Rockingham County
 Fee Class: Title V

In accordance with your completed Air Quality Permit Application for **renewal** of your Title V permit received **June 14, 2006**, we are forwarding herewith Air Quality Permit No. **03662T22** to Ball Metal Beverage Container Corporation, 1900 Barns Street, Reidsville, North Carolina 27320 authorizing the **construction and operation** of the emission source(s) and associated air pollution control device(s) specified herein. Additionally, any emissions activities determined from your Air Quality Permit Application as being insignificant per 15A North Carolina Administrative Code **2Q .0503(8)** have been listed for informational purposes as an "ATTACHMENT". Please note the requirements for the annual compliance certification are contained in General Condition P in Section 3. **The current owner is responsible for submitting a compliance certification for the entire year regardless of who owned the facility during the year.**

As the designated responsible official it is your responsibility to review, understand, and abide by all of the terms and conditions of the attached permit. It is also your responsibility to ensure that any person who operates any emission source and associated air pollution control device subject to any term or condition of the attached permit reviews, understands, and abides by the condition(s) of the attached permit that are applicable to that particular emission source.

Mr. Todd Farley
Date, 2008
Page 2

If any parts, requirements, or limitations contained in this Air Quality Permit are unacceptable to you, you have the right to request a formal adjudicatory hearing within 30 days following receipt of this permit, identifying the specific issues to be contested. This hearing request must be in the form of a written petition, conforming to NCGS (North Carolina General Statutes) 150B-23, and filed with **both** the Office of Administrative Hearings, 6714 Mail Service Center, Raleigh, North Carolina 27699-6714 and the Division of Air Quality, Permitting Section, 1641 Mail Service Center, Raleigh, North Carolina 27699-1641. The form for requesting a formal adjudicatory hearing may be obtained upon request from the Office of Administrative Hearings. **Please note that this permit will be stayed in its entirety upon receipt of a request for a hearing.** Unless a request for a hearing is made pursuant to NCGS 150B-23, this Air Quality Permit shall be final and binding **30 days after issuance.**

You may request modification of your Air Quality Permit through informal means pursuant to NCGS 150B-22. This request must be submitted in **writing** to the Director and must identify the specific provisions or issues for which the modification is sought. Please note that this Air Quality Permit will become final and binding regardless of a request for informal modification unless a request for a hearing is also made under NCGS 150B-23.

The construction of new air pollution emission source(s) and associated air pollution control device(s), or modifications to the emission source(s) and air pollution control device(s) described in this permit must be covered under an Air Quality Permit issued by the Division of Air Quality prior to construction unless the Permittee has fulfilled the requirements of GS 143-215.108A(b) and received written approval from the Director of the Division of Air Quality to commence construction. Failure to receive an Air Quality Permit or written approval prior to commencing construction is a violation of GS 143-215.108A and may subject the Permittee to civil or criminal penalties as described in GS 143-215.114A and 143-215.114B.

This Air Quality Permit shall be effective from **date, 2008** until **date, 2013**, is nontransferable to future owners and operators, and shall be subject to the conditions and limitations as specified therein.

Should you have any questions concerning this matter, please contact Mr. Mark J. Cuilla, E.I.T. (mark.cuilla@ncmail.net) at (919) 733-1499.

Sincerely yours,

Donald R. van der Vaart, Ph.D., P.E.
Chief

Enclosure

c: Gregg Worley, EPA Region 4 (with review)
Mr. Bob Hall/Ball Metal Beverage Container Corp./9300 W. 108th Circle/Bloomfield, CO 80021
Winston-Salem Regional Office
Central Files

ATTACHMENT**Insignificant Activities under 15A NCAC 2Q .0503(8) under Permit No. 03662T22**

Emission Source ID	Emission Source Description
I1.1 through I1.3	Three washer and natural gas-fired dry off ovens
I-ESB-1 I-ESB-2 I-ESB-3	Three natural gas-fired boilers (4, 4, and 2.1 million Btu per hour maximum heat input capacity, respectively)
I3.1 and I3.2	Two over varnish tanks
I4.1 and I4.2	Two inside spray tanks
I5	Tab lube tank
I7	2300 gallon separated oil tank
I8.1 through I8.3	Three used oil tanks
I9	Hydraulic oil tank
I10	Gear oil tank
I11	2300 gallon cupped oil tank
I12	D&I lube tank
I13	Wastewater and oil tank
I14	Fluoride tank
I15	Cleaner tank
I16	Flock tank
I18	Wastewater system
I19	Lime storage silo
IELECO1	Grieve electric oven

ATTACHMENT

The following table lists all modifications associated with this permit action:

Page(s)	Section	Description of Change(s)
Attachment	Insignificant Activities	-amended permit revision number
Cover	-	-amended permit revision numbers and all dates
All	Header	-amended permit revision number
3-4	Equipment Table	-added NSPS Subpart reference where needed -updated equipment descriptions where needed -removed reference to aluminum can end production lines 1 and 2 permit Permittee
5	2.1 A	-clarified applicable equipment listing
5-6	2.1 A (table)	-added source ID numbers where needed
6	2.1 A.1.a 2.1 A.1.b 2.1 A.1.c 2.1 A.1.d	-updated shell language -corrected regulatory reference -updated shell language -updated shell language -added "no reporting" language
7	2.1 A.2.a 2.1 A.2.b 2.1 A.3.a 2.1 A.3.b 2.1 A.3.c	-added ID numbers -corrected regulatory reference -updated shell language -added ID numbers -corrected regulatory reference -updated shell language -updated shell language and added ID numbers
8	2.1 A.4.a 2.1 A.4.c	-updated shell language -corrected regulatory reference -updated shell language
9	2.1 A.4.i	-added NSPS reporting requirement clarification
-	2.1 B (old)	-removed original section corresponding to removal of aluminum can end production lines 1 and 2 (renumbered remaining sections)
10	2.1 B (new) 2.1 B (table) 2.1 B.1.a 2.1 B.1.b 2.1 B.1.c	-clarified equipment description -clarified emission limit for particulate -added ID numbers and updated shell language -corrected regulatory reference -updated shell language -added ID numbers
11	2.1 B.1.e 2.1 B.2.a 2.1 B.2.b 2.1 B.2.c	-added ID numbers -added ID numbers -corrected regulatory reference -updated shell language -added ID numbers and updated shell language
12	2.1 C	-clarified applicable equipment
14	2.2 A.1.e 2.2 A.2 2.2 A.2.d	-updated shell language -clarified regulatory citation -updated shell language
15	2.2 A.3 2.2 A.3.c	-clarified regulatory citation -updated shell language

Page(s)	Section	Description of Change(s)
17	2.2 B 2.2 B.1.b	-clarified applicable equipment -updated shell language
18-28	General Conditions	-updated shell conditions (v2.22.1)
29	Attachment	-updated shell language



AIR QUALITY PERMIT

Permit No.	Replaces Permit No.(s)	Effective Date	Expiration Date
03662T22	03662T21	Date, 2008	Date, 2013

Until such time as this permit expires or is modified or revoked, the below named Permittee is **permitted to construct and operate** the emission source(s) and associated air pollution control device(s) specified herein, in accordance with the terms, conditions, and limitations within this permit. This permit is issued under the provisions of Article 21B of Chapter 143, General Statutes of North Carolina as amended, and Title 15A North Carolina Administrative Codes (15A NCAC), Subchapters 2D and 2Q, and other applicable Laws.

Pursuant to Title 15A NCAC, Subchapter 2Q, the Permittee shall not construct, operate, or modify any emission source(s) or air pollution control device(s) without having first submitted a complete Air Quality Permit Application to the permitting authority and received an Air Quality Permit, except as provided in this permit.

Permittee: **Ball Metal Beverage Container Corp.**

Facility ID: **7900093**

Facility Site Location: **1900 Barns Street**
City, County, State, Zip: **Reidsville, Rockingham County, North Carolina 27320**
Mailing Address: **P.O. Box 1170**
City, State, Zip: **Reidsville, North Carolina 27320**

Application Number: **7900093.06A**
Complete Application Date: **June 14, 2006**

Primary SIC Code: **3411**

Division of Air Quality, **Winston-Salem Regional Office**
Regional Office Address: **585 Waughtown Street**
Winston-Salem, NC 27107

Permit issued this the xxth day of xxxxxx, 2008

Donald R, van der Vaart, Ph.D., P.E., Chief, Air Permits Section
By Authority of the Environmental Management Commission

Table Of Contents

SECTION 1: PERMITTED EMISSION SOURCE(S) AND ASSOCIATED
AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES

SECTION 2: SPECIFIC LIMITATIONS AND CONDITIONS

2.1- Emission Source(s) Specific Limitations and Conditions
(Including specific requirements, testing, monitoring, recordkeeping, and
reporting requirements)

2.2- Multiple Emission Source(s) Specific Limitations and Conditions
(Including specific requirements, testing, monitoring, recordkeeping, and
reporting requirements)

SECTION 3: GENERAL PERMIT CONDITIONS

ATTACHMENT

List of Acronyms

The Division of Air Quality (DAQ), the United States Environmental Protection Agency (EPA), and citizens as defined under the Federal Clean Air Act have the authority to enforce the terms, conditions, and limitations contained in this permit unless otherwise specified.

Under Title 15A NCAC 2Q, the operation of emission source(s) and associated air pollution control device(s) and appurtenances listed in this permit is based on plans, specifications, operating parameters, and other information as submitted in the Air Quality Permit Application.

SECTION 1- PERMITTED EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES

The following table contains a summary of all permitted emission sources and associated air pollution control devices and appurtenances:

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
Aluminum Can Production Line #1			
ESIVDD1 (NSPS, Subpart WW)	Printing, rim coating, and over varnish coating operation consisting of a dry filter unit (five individual filters) installed on decorator hood and natural gas-fired decorator (pin) oven (4.1 million Btu per hour maximum heat input capacity)	NA	NA
ESICS1 (NSPS, Subpart WW)	Dry baffle type inside spray coating operation consisting of six spraying stations and natural gas-fired internal coating oven (2.4 million Btu per hour maximum heat input capacity)	NA	NA
Aluminum Can Production Line #2			
ESRCS02 (NSPS, Subpart WW)	Ultraviolet rim coating applicator	NA	NA
ESIVDD2 (NSPS, Subpart WW)	Printing and over varnish coating operation consisting of a dry filter unit (five individual filters) installed on decorator hood and natural gas-fired decorator (pin) oven (3.2 million Btu per hour maximum heat input capacity)	NA	NA
ESICS2 (NSPS, Subpart WW)	Dry baffle type inside spray coating operation consisting of six spraying stations and natural gas-fired internal coating oven (2.4 million Btu per hour maximum heat input capacity)	NA	NA

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
Aluminum Can Production Line #3			
ESRCS03 (NSPS, Subpart WW)	Ultraviolet rim coating applicator	NA	NA
ESIVDD3 (NSPS, Subpart WW)	Printing and over varnish coating operation consisting of a dry filter unit (five individual filters) installed on decorator hood and natural gas-fired decorator (pin) oven (3.2 million Btu per hour maximum heat input capacity)	NA	NA
ESICS3 (NSPS, Subpart WW)	Dry baffle type inside spray coating operation consisting of six spraying stations and natural gas-fired internal coating oven (2.4 million Btu per hour maximum heat input capacity)	NA	NA
Miscellaneous			
CFU	Cup forming unit consisting of three identical cupping presses (Nos. 1 through 3)	C1 C2	Two simple cyclones (144 inches in diameter each)
DIMS.1 through DIMS.19	Nineteen draw and iron (D&I) machines serving three lines (Nos. 1 through 3)	CTV1 CTV2 CTV3 CTV4	Four simple cyclones (36 inches in diameter each)
CT.1 through CT.11	Eleven can trimmers	CTR1	One simple cyclone (108 inches in diameter)
ESIDS.1 through ESIDS.3	Three ink dot systems	NA	NA

SECTION 2 - SPECIFIC LIMITATIONS AND CONDITIONS

2.1- Emission Source(s) and Control Devices(s) Specific Limitations and Conditions

The emission source(s) and associated air pollution control device(s) and appurtenances listed below are subject to the following specific terms, conditions, and limitations, including the testing, monitoring, recordkeeping, and reporting requirements as specified herein:

- A. Aluminum Can Production Line #1 consisting of:**
Printing, rim coating, and over varnish coating operation (ID No. ESIVDD1)
Dry baffle type inside spray coating operation (ID No. ESICS1)
- Aluminum Can Production Line #2 consisting of:**
Ultraviolet rim coating applicator (ID No. ESRCS02)
Printing and over varnish coating operation (ID No. ESIVDD2)
Dry baffle type inside spray coating operation (ID No. ESICS2)
- Aluminum Can Production Line #3 consisting of:**
Ultraviolet rim coating applicator (ID No. ESRCS03)
Printing and over varnish coating operation (ID No. ESIVDD3)
Dry baffle type inside spray coating operation (ID No. ESICS3)

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	<p>(ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3 only)</p> <p>For P ≤ 30 tons per hour $E = 4.10 \times P^{0.67}$</p> <p>For P > 30 tons per hour $E = 55.0 \times P^{0.11} - 40$</p> <p>Where E = allowable emission rate in pounds per hour P = process weight rate in tons per hour</p>	15A NCAC 2D .0515
Sulfur Dioxide	<p>(ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3 only)</p> <p>2.3 pounds per million Btu heat input</p>	15A NCAC 2D .0516
Visible emissions	<p>(ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3 only)</p> <p>20 percent opacity</p>	15A NCAC 2D .0521
Volatile organic compounds	<p>Less than 0.46 kg of VOC/L of coating solids from each clear base coating operations and each two-piece can over varnish coating operation</p> <p>Less than 0.89 kg of VOC/L of coating solids from each two-piece can inside spray coating operation</p>	15A NCAC 2D .0524 (40 CFR 60, Subpart WW)
Volatile organic compounds	See Section 2.2 A.1	15A NCAC 2D .0958

Regulated Pollutant	Limits/Standards	Applicable Regulation
Volatile organic compounds	See Section 2.2 A.2	15A NCAC 2Q .0317 (PSD Avoidance)
HAPs	(ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3 only) See Section 2.2 A.3	15A NCAC 2Q .0317 (MACT Avoidance)
Odors	State-enforceable only See Section 2.2 A.4	15A NCAC 2D .1806
TAPs	(ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3 only) State-enforceable only See Section 2.2 A.5	15A NCAC 2Q .0711
TAPs	(ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3 only) State-enforceable only See Section 2.2 B.1	15A NCAC 2D .1100

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emission of particulate matter from **these sources** (ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3) shall not exceed an allowable emission rate as calculated by the following equations:

For P ≤ 30 tons per hour

$$E = 4.10 \times P^{0.67}$$

For P > 30 tons per hour

$$E = 55.0 \times P^{0.11} - 40$$

Where E = allowable emission rate in pounds per hour

P = process weight rate in tons per hour

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .2601]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .2601 and General Condition JJ. If the results of this test are above the limit given in Section 2.1 A.1.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring/Recordkeeping/Reporting [15A NCAC 2Q .0508(f)]

- c. The Permittee shall maintain production records **such that the process rates “P” in tons per hour, as specified by the formulas contained above can be derived**, and shall make these records available to a DAQ authorized representative upon request. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the production records are not maintained or the types of materials and finishes are not monitored.
- d. **No reporting is required for particulate from these sources (ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3).**

2. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

- a. Emissions of sulfur dioxide from the combustion units of the pin ovens and the interior coating bake ovens of these sources (**ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3**) shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard.

Testing [15A NCAC 2D .2601]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .2601 and General Condition JJ. If the results of this test are above the limit given in Section 2.1 A.2.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. No monitoring/recordkeeping/reporting is required for sulfur dioxide emissions from the firing of natural gas or propane in the pin ovens or the interior coating bake ovens of these sources (**ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, and ESICS3**).

3. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources (**ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, ESICS3, ESRCS02, and ESRCS03**) shall not be more than 20 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 20 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 87 percent opacity.

Testing [15A NCAC 2D .2601]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .2601 and General Condition JJ. If the results of this test are above the limit given in Section 2.1 A.3.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a month the Permittee shall observe the emission points of these sources (**ID Nos. ESIVDD1, ESIVDD2, ESIVDD3, ESICS1, ESICS2, ESICS3, ESRCS02, and ESRCS03**) for any visible emissions above normal. **The monthly observation must be made for each month of the calendar year period to ensure compliance with this requirement.** If visible emissions from these sources are observed to be above normal, the Permittee shall either:

- i. **take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or**
- ii. demonstrate that the percent opacity from the emission points of the emission sources in accordance with 15A NCAC 2D .2601 (**Method 9**) for **12 minutes** is below the limit given in Section 2.1 A.3.a above.

If the **above-normal emissions are not corrected per i. above** or if the demonstration in **ii. above** cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;

- ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
- iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of the observations postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

4. 15A NCAC 2D .0524: NEW SOURCE PERFORMANCE STANDARDS

- a. For the clear base coating operations (**ID Nos. ESRCs02 and ESRCs03**) and over varnish coating operations (**ID Nos. ESIVDD1, ESIVDD2, and ESIVDD3**) and the inside spray coating operations (**ID Nos. ESICS1, ESICS2, and ESICS3**) on the three aluminum can production lines, the Permittee shall comply with all applicable provisions, including the notification, testing, recordkeeping, and monitoring requirements contained in Environmental Management Commission Standard 15A NCAC 2D .0524 “New Source Performance Standards” as promulgated in 40 CFR 60 Subpart WW “Standards for Performance for the Beverage Can Surface Coating Industry” including Subpart A “General Provisions”.

Emission Limitations [15A NCAC 2D .0524]

- b. As required by 40 CFR 60.492, no owner or operator subject to the provisions of this Subpart shall discharge or cause the discharge of VOC emissions to the atmosphere that exceed the following volume-weighted calendar-month average emissions:
 - i. 0.46 kilogram of VOC per liter of coating solids from each two-piece can clear base coating operation and from each over varnish coating operation; and
 - ii. 0.89 kilogram of VOC per liter of coating solids from each two-piece can inside spray coating operation.

Testing [15A NCAC 2D .2601]

- c. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .2601 and General Condition JJ. If the results of this test are above the limit given in **Section 2.1 A.4.b** above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0524.
- d. Test methods and procedures. For determining compliance with 15A NCAC 2D .0524, the following reference method, as defined in 40 CFR 60, Appendix A, except as provided in 40 CFR 60.8, shall be used to conduct performance tests.
 - i. Method 24, an equivalent or alternative method approved by the Administrator of EPA, or manufacturer’s formulation data from which the VOC content of the coatings used for each affected facility can be calculated. In the event of a dispute, Method 24 data shall govern. When VOC content of water-borne coatings, determined from data generated by Method 24, is used to determine compliance of affected facilities, the results of the Method 24 analysis shall be adjusted as described in Section 12.6 of Method 24.
 - ii. For Method 24, the coating sample must be a 1-liter sample collected in a 1-liter container at a point where the sample will be representative of the coating material.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- e. For the clear base coating operations (**ID Nos. ESRCs02 and ESRCs03**) and printer/over varnish units (**ID Nos. ESIVDD1, ESIVDD2, and ESIVDD3**), the Permittee shall use the procedures prescribed in 40 CFR 60.493(b)(1) for determining monthly volume-weighted average emissions of volatile organic compounds in kilogram per liter of coating solids applied during operation.
- f. For the inside spray units (**ID Nos. ESICS1, ESICS2, and ESICS3**), the Permittee shall use the procedures prescribed in 40 CFR 60.493(b)(1) for determining monthly volume-weighted average emissions of volatile organic compounds in kilograms per liter of coating solids applied during operation.
- g. In addition to any other recordkeeping requirements of the Environmental Protection Agency (EPA), as required by 15A NCAC 2D .0524, the Permittee is required to maintain records as follows:
 - i. all data and calculations (including purchase records and MSDS sheets) used to determine VOC emissions from each affected facility.
 - ii. all records required under this Section shall be maintained by the owner or operator of an affected facility for a period of two years following the date of such record.
- h. As required by 15A NCAC 2D .0524 (and 40 CFR 60.495(d)), the Permittee shall maintain at aluminum can production lines Nos. 1, 2, and 3, for a period of at least 2 years, records of all data and calculations used to determine monthly VOC emissions from each affected facility and to determine the monthly emission limit, where applicable. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0524 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- i. In addition to any other reporting requirements of the Environmental Protection Agency (EPA), within 30 days after each calendar year quarter, the Permittee is required to report in writing to the Regional Air Quality Supervisor, Division of Air Quality (DAQ) as follows:
 - i. the Permittee must submit a report of each instance in which the volume-weighted average of the total mass of VOC per volume of coating solids exceeds the limits specified in this regulation.
 - ii. if no such instances occur during a particular quarter, a report stating this shall be submitted **semiannually, postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June.**

- B. One cup forming unit consisting of three identical cupping presses (Nos. 1, 2, and 3; ID No. CFU) with associated simple cyclones (ID Nos. C1 and C2)
Nineteen draw and iron machines serving Lines 1, 2, and 3 (ID Nos. DIMS.1 through DIMS.19) with associated simple cyclones (ID Nos. CTV1 through CTV4)
Eleven can trimmers (ID Nos. CT.1 through CT.11) with associated simple cyclone (ID No. CTR1)**

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	<p>For P ≤ 30 tons per hour $E = 4.10 \times P^{0.67}$</p> <p>For P > 30 tons per hour $E = 55.0 \times P^{0.11} - 40$</p> <p>Where E = allowable emission rate in pounds per hour P = process weight rate in tons per hour</p>	15A NCAC 2D .0515
Visible emissions	20 percent opacity	15A NCAC 2D .0521

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emission of particulate matter from **these sources (ID Nos. CFU, CT.1 through CT.11, and DIMS.1 through DIMS.19)** shall not exceed an allowable emission rate as calculated by the following equations:

For P ≤ 30 tons per hour

$$E = 4.10 \times P^{0.67}$$

For P > 30 tons per hour

$$E = 55.0 \times P^{0.11} - 40$$

Where E = allowable emission rate in pounds per hour

P = process weight rate in tons per hour

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .2601]

- b. If emissions testing is required, the testing shall be performed in accordance with **15A NCAC 2D .2601 and General Condition JJ**. If the results of this test are above the limit given in **Section 2.1 B.1.a** above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. Particulate matter emissions from these sources **(ID Nos. CFU, CT.1 through CT.11, and DIMS.1 through DIMS.19)** shall be controlled **with seven cyclones (ID Nos. C1, C2, CTR1, and CTV1 through CTV4) as described above**. To assure compliance, the Permittee shall perform inspections and maintenance as recommended by the manufacturer. In addition to the manufacturer's inspection and maintenance recommendations, or if there are not manufacturer's inspection and maintenance recommendations, as a minimum, the inspection and maintenance requirement shall include the following:

- i. a monthly visual inspection of the system ductwork and material collection units for leaks; and
- ii. an annual (for each 12 month period following the initial inspection) **internal** inspection of the cyclones' structural integrity.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the ductwork and cyclones are not inspected and maintained.

- d. The results of the inspection and maintenance activities shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request.

The logbook shall record the following:

- i. the date and time of each recorded action;
- ii. the results of each inspection;
- iii. the results of any maintenance performed on the cyclones; and
- iv. any variance from manufacturer's recommendations, if any, and corrections made.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit the results of any maintenance performed on the cyclones (**ID Nos. C1, C2, CTR1, and CTV1 through CTV4**) within 30 days of a written request by the DAQ.
- f. The Permittee shall submit a summary report of monitoring and recordkeeping activities postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

2. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources (**ID Nos. CFU, CT.1 through CT.11, and DIMS.1 through DIMS.19**) shall not be more than 20 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 20 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 87 percent opacity.

Testing [15A NCAC 2D .2601]

- b. If emissions testing is required, the testing shall be performed in accordance with 15A NCAC 2D .2601 and General Condition JJ. If the results of this test are above the limit given in **Section 2.1 B.2.a** above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a **month** the Permittee shall observe the emission points of these sources (**ID Nos. CFU, CT.1 through CT.11, and DIMS.1 through DIMS.19**) for any visible emissions above normal. **The monthly observation must be made for each month of the calendar year period to ensure compliance with this requirement.** If visible emissions from these sources are observed to be above normal, the Permittee shall either:
 - i. **take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or**
 - ii. **demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 2D .2601 (Method 9) for 12 minutes are below the limit given in Section 2.1 B.2.a above.**

If the **above-normal emissions are not corrected per i. above or if the** demonstration in **ii. above** cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of the observations postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

C. Three ink dot systems (ID Nos. ESIDS.1 through ESIDS.3)

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
Volatile organic compounds	See Section 2.2 A.1	15A NCAC 2D .0958
Volatile organic compounds	See Section 2.2 A.2	15A NCAC 2Q .0317 (PSD Avoidance)
HAPs	See Section 2.2 A.3	15A NCAC 2Q .0307 (MACT Avoidance)
Odors	State-enforceable only See Section 2.2 A.4	15A NCAC 2D .1806
TAPs	State-enforceable only See Section 2.2 A.5	15A NCAC 2Q .0711

2.2- Multiple Emission Source(s) Specific Limitations and Conditions

A. Facility-wide affected sources

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
Volatile organic compounds	Work practice standards	15A NCAC 2D .0958
Volatile organic compounds	Less than 250 tons per consecutive 12-month period	15A NCAC 2Q .0317 (PSD Avoidance)
HAPs	Less than 10 tons per year any individual HAP Less than 25 tons per year any combination of HAPs	15A NCAC 2Q .0317 (MACT Avoidance)
Odors	State-enforceable only Odorous emissions must be controlled	15A NCAC 2D .1806
TAPs	State-enforceable only TAPs shall not exceed the levels in 2Q .0711 without a permit	15A NCAC 2Q .0711

1. 15A NCAC 2D .0958: WORK PRACTICES FOR SOURCES OF VOLATILE ORGANIC COMPOUNDS

- a. Pursuant to 15A NCAC 2D .0958, for all sources that use volatile organic compounds (VOCs) as solvents, carriers, material processing media, or industrial chemical reactants, or in similar uses that mix, blend, or manufacture VOCs, or emit VOCs as a product of chemical reactions, and whose emissions of VOCs are greater than 15 pounds per day, the Permittee shall:
 - i. store all material, including waste material, containing VOCs in tanks or in containers covered with a tightly fitting lid that is free of cracks, holes, or other defects, when not in use,
 - ii. clean up spills of VOCs as soon as possible following proper safety procedures,
 - iii. store wipe rags containing VOCs in closed containers,
 - iv. not clean sponges, fabric, wood, paper products, and other absorbent materials with VOCs,
 - v. transfer solvents containing VOCs used to clean supply lines and other coating equipment into closable containers and close such containers immediately after each use, or transfer such solvents to closed tanks, or to a treatment facility regulated under Section 402 of the Clean Water Act,
 - vi. clean mixing, blending, and manufacturing vats and containers containing VOCs by adding cleaning solvent and close the vat or container before agitating the cleaning solvent. The spent cleaning solvent shall then be transferred into a closed container, a closed tank or a treatment facility regulated under Section 402 of the Clean Water Act.
- b. When cleaning parts with solvent containing a VOC, the Permittee shall:
 - i. flush parts in the freeboard area,
 - ii. take precautions to reduce the pooling of solvent on and in the parts,
 - iii. tilt or rotate parts to drain solvent and allow a minimum of 15 seconds for drying or until all dripping has stopped, whichever is longer,
 - iv. not fill cleaning machines above the fill line,
 - v. not agitate solvent to the point of causing splashing.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. To assure compliance with Section 2.2 A.1.a and b above, the Permittee shall, at a minimum, perform a visual inspection once per month of all operations and processes utilizing VOCs. The inspections shall be conducted during normal operations. If the required inspections are not conducted the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0958.
- d. The results of the inspections shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each inspection, and
 - ii. the results of each inspection noting whether or not noncompliant conditions were observed.If the required records are not maintained the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0958.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of the observations **postmarked on or before** January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

2. 15A NCAC 2Q .0317: AVOIDANCE CONDITIONS

for 15A NCAC 2D .0530: PREVENTION OF SIGNIFICANT DETERIORATION

- a. To comply with this Permit and to avoid the applicability of 15A NCAC 2D .0530, Prevention of Significant Deterioration, as requested by the Permittee, volatile organic compound (VOC) emissions from the facility must be less than 250 tons per consecutive 12-month period.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- b. Calculations of facility wide VOC emissions shall be made each month. VOC emissions shall be determined by multiplying the total amount of each type of VOC-containing material consumed or used during the month by the VOC content of the coating material. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530 if the amounts of VOC-containing materials are not monitored and recorded.
- c. Calculations of the total amount of VOC emissions shall be recorded monthly in a logbook (written or electronic format). The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530 if the VOC emissions exceed the limit in Section 2.2 A.2.a above.

Reporting [15A NCAC 2Q .0508(f)]

- d. The Permittee shall submit a semi-annual summary report of VOC emissions postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between **January and June**. The report shall contain the following:
 - i. the total monthly VOC emissions for the previous 17 months, and
 - ii. the six 12-consecutive month totals for each of the months of the reporting period.

**3. 15A NCAC 2Q .0317: AVOIDANCE CONDITIONS
for 15A NCAC 2D .1111: MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY**

- a. To comply with this Permit and to avoid applicability to 15A NCAC 2D .1111, Maximum Achievable Control Technology, as requested by the Permittee, facility wide emissions shall be less than 10 tons per consecutive 12-month period for any single hazardous air pollutants and less than 25 tons per consecutive 12-month period for all hazardous air pollutants.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- b. Calculation of facility wide HAP emissions shall be made each month. HAP emissions shall be determined by multiplying the total amount of each type of HAP containing material consumed or used during the month by the HAP content of the coating material. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if the HAP containing materials are not monitored or recorded.
- c. Calculations on the individual HAP amounts and total HAP amount shall be recorded monthly in a logbook (written or electronic format). The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if HAP emissions exceed the limits in Section 2.2 A.3.a above.
- d. The Permittee must keep records demonstrating that HAP emissions are less than 10 tons for any single HAP or 25 tons for total of all HAPs on site at the source for a period of five years after the determination, or until the source changes its operations to become an affected source, whichever comes first. The records must be signed by the person making the determination and include an analysis (or other information) that demonstrates why the Permittee believes the source is unaffected (e.g., because the source is an area source). The analysis (or other information) must be sufficiently detailed to allow the DAQ to make a finding about the source's applicability status with regard to the relevant standard or other requirement.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a semi-annual summary report of HAP emissions postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 for each calendar year for the preceding six-month period between **January and June**. The report shall contain the following:
 - i. the monthly individual HAP and total HAP emissions for the previous 17 months, and
 - ii. the six 12-consecutive month totals of individual HAP and total HAP emissions for each of the months of the reporting period.

State-enforceable only

4. 15A NCAC 2D .1806: CONTROL AND PROHIBITION OF ODOROUS EMISSIONS

- a. The Permittee shall not operate the facility without implementing management practices or installing and operating odor control equipment sufficient to prevent odorous emissions from the facility from causing or contributing to objectionable odors beyond the facility's boundary.

State-enforceable only

5. 15A NCAC 2Q .0711: EMISSION RATES REQUIRING A PERMIT

Pursuant to 15A NCAC 2Q .0711, Emission Rates Requiring a Permit, for each of the toxic air pollutants (TAPs) listed below, the Permittee has made a demonstration that facility-wide actual emissions do not exceed the Toxic Permit Emission Rates (TPERs) listed in 15A NCAC 2Q .0711. The facility shall be operated and maintained in such a manner that emissions of any listed TAPs from the facility, including fugitive emissions, will not exceed TPERs listed in 15A NCAC 2Q .0711.

- a. A permit to emit any of the below listed TAPs shall be required for this facility if actual emissions from all sources will become greater than the corresponding TPERs.
- b. Prior to exceeding any of these listed TPERs, the Permittee shall be responsible for obtaining a permit to emit TAPs and for demonstrating compliance with the requirements of 15A NCAC 2D .1100, Control of Toxic Air Pollutants.
- c. In accordance with the approved application, the Permittee shall maintain records of operational information demonstrating that the TAP emissions do not exceed the TPERs as listed below:

TPERs Limitations				
Pollutant (CAS Number)	Carcinogens (lbs/yr)	Chronic Toxicants (lbs/day)	Acute Systemic Toxicants (lbs/hr)	Acute Irritants (lbs/hr)
Ammonia (7664-41-7)				0.68
Ethyl acetate (141-78-6)			36	
Methyl ethyl ketone (78-93-3)		78		22.4

- B. Aluminum Can Production Line #1 consisting of:**
 - Printing, rim coating, and over varnish coating operation (ID No. ESIVDD1)**
 - Dry baffle type inside spray coating operation (ID No. ESICS1)**
- Aluminum Can Production Line #2 consisting of:**
 - Printing and over varnish coating operation (ID No. ESIVDD2)**
 - Dry baffle type inside spray coating operation (ID No. ESICS2)**
- Aluminum Can Production Line #3 consisting of:**
 - Printing and over varnish coating operation (ID No. ESIVDD3)**
 - Dry baffle type inside spray coating operation (ID No. ESICS3)**

The following table provides a summary of limits and standards for the emission source(s) described above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
TAPs	Permit limits for TAPs shall not be exceeded	15A NCAC 2D .1100

State-enforceable only

1. 15A NCAC 2D .1100: CONTROL OF TOXIC AIR POLLUTANTS

- a. Pursuant to 15A NCAC 2D .1100, Control of Toxic Air Pollutants, and in accordance with the approved application for an air toxic compliance demonstration, the following permit limits shall not be exceeded:

Emission Point	Toxic Air Pollutant	Emission Limit(s) (lbs/hr)
ESIVDD1	Formaldehyde	0.55
ESICS1		0.12
ESIVDD2		0.55
ESICS2		0.12
ESIVDD3		0.55
ESICS3		0.12

- b. To ensure compliance with the above limits, aluminum can production in the three aluminum can production lines shall be limited to a combined production of 2,300,000,000 cans **per year**.
- c. The Permittee shall maintain records to verify compliance with the operational restriction listed above on site for a minimum of two years and make these available to DAQ personnel upon request.
- d. For compliance purposes, within 30 days after each calendar year quarter, regardless of the actual emissions, the combined aluminum can production in the three aluminum can production lines during the previous 12-months for each of the three 12-month periods ending during the quarter shall be reported to the Regional Supervisor, DAQ.

SECTION 3 - GENERAL CONDITIONS (v2.22.1)

This section describes terms and conditions applicable to this Title V facility.

A. General Provisions [NCGS 143-215 and 15A NCAC 2Q .0508(i)(16)]

1. Terms not otherwise defined in this permit shall have the meaning assigned to such terms as defined in 15A NCAC 2D and 2Q.
2. The terms, conditions, requirements, limitations, and restrictions set forth in this permit are binding and enforceable pursuant to NCGS 143-215.114A and 143-215.114B, including assessment of civil and/or criminal penalties. Any unauthorized deviation from the conditions of this permit may constitute grounds for revocation and/or enforcement action by the DAQ.
3. This permit is not a waiver of or approval of any other Department permits that may be required for other aspects of the facility which are not addressed in this permit.
4. This permit does not relieve the Permittee from liability for harm or injury to human health or welfare, animal or plant life, or property caused by the construction or operation of this permitted facility, or from penalties therefore, nor does it allow the Permittee to cause pollution in contravention of state laws or rules, unless specifically authorized by an order from the North Carolina Environmental Management Commission.
5. Except as identified as state-only requirements in this permit, all terms and conditions contained herein shall be enforceable by the DAQ, the EPA, and citizens of the United States as defined in the Federal Clean Air Act.
6. Any stationary source of air pollution shall not be operated, maintained, or modified without the appropriate and valid permits issued by the DAQ, unless the source is exempted by rule. The DAQ may issue a permit only after it receives reasonable assurance that the installation will not cause air pollution in violation of any of the applicable requirements. A permitted installation may only be operated, maintained, constructed, expanded, or modified in a manner that is consistent with the terms of this permit.

B. Permit Availability [15A NCAC 2Q .0507(k) and .0508(i)(9)(B)]

The Permittee shall have available at the facility a copy of this permit and shall retain for the duration of the permit term one complete copy of the application and any information submitted in support of the application package. The permit and application shall be made available to an authorized representative of Department of Environment and Natural Resources upon request.

C. Severability Clause [15A NCAC 2Q .0508(i)(2)]

In the event of an administrative challenge to a final and binding permit in which a condition is held to be invalid, the provisions in this permit are severable so that all requirements contained in the permit, except those held to be invalid, shall remain valid and must be complied with.

D. Submissions [15A NCAC 2Q .0507(e) and 2Q .0508(i)(16)]

Except as otherwise specified herein, two copies of all documents, reports, test data, monitoring data, notifications, request for renewal, and any other information required by this permit shall be submitted to the appropriate Regional Office. Refer to the Regional Office address on the cover page of this permit. For continuous emissions monitoring systems (CEMS) reports, continuous opacity monitoring systems (COMS) reports, quality assurance (QA)/quality control (QC) reports, acid rain CEM certification reports, and NOx budget CEM certification reports, one copy shall be sent to the appropriate Regional Office and one copy shall be sent to:

Supervisor, Stationary Source Compliance
North Carolina Division of Air Quality
1641 Mail Service Center
Raleigh, NC 27699-1641

E. **Duty to Comply** [15A NCAC 2Q .0508(i)(2)]

The Permittee shall comply with all terms, conditions, requirements, limitations and restrictions set forth in this permit. Noncompliance with any permit condition except conditions identified as state-only requirements constitutes a violation of the Federal Clean Air Act. Noncompliance with any permit condition is grounds for enforcement action, for permit termination, revocation and reissuance, or modification, or for denial of a permit renewal application.

F. **Circumvention** - STATE ENFORCEABLE ONLY

The facility shall be properly operated and maintained at all times in a manner that will effect an overall reduction in air pollution. Unless otherwise specified by this permit, no emission source may be operated without the concurrent operation of its associated air pollution control device(s) and appurtenances.

G. **Permit Modifications**

1. Administrative Permit Amendments [15A NCAC 2Q .0514]

The Permittee shall submit an application for an administrative permit amendment in accordance with 15A NCAC 2Q .0514.

2. Transfer in Ownership or Operation and Application Submittal Content [15A NCAC 2Q .0524 and 2Q .0505]

The Permittee shall submit an application for an ownership change in accordance with 15A NCAC 2Q.0524 and 2Q .0505.

3. Minor Permit Modifications [15A NCAC 2Q .0515]

The Permittee shall submit an application for a minor permit modification in accordance with 15A NCAC 2Q .0515.

4. Significant Permit Modifications [15A NCAC 2Q .0516]

The Permittee shall submit an application for a significant permit modification in accordance with 15A NCAC 2Q .0516.

5. Reopening for Cause [15A NCAC 2Q .0517]

The Permittee shall submit an application for reopening for cause in accordance with 15A NCAC 2Q .0517.

H. **Changes Not Requiring Permit Modifications**

1. Reporting Requirements

Any of the following that would result in new or increased emissions from the emission source(s) listed in Section 1 must be reported to the Regional Supervisor, DAQ:

- a. changes in the information submitted in the application;
- b. changes that modify equipment or processes; or
- c. changes in the quantity or quality of materials processed.

If appropriate, modifications to the permit may then be made by the DAQ to reflect any necessary changes in the permit conditions. In no case are any new or increased emissions allowed that will cause a violation of the emission limitations specified herein.

2. Section 502(b)(10) Changes [15A NCAC 2Q .0523(a)]
 - a. "Section 502(b)(10) changes" means changes that contravene an express permit term or condition. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.
 - b. The Permittee may make Section 502(b)(10) changes without having the permit revised if:
 - i. the changes are not a modification under Title I of the Federal Clean Air Act;
 - ii. the changes do not cause the allowable emissions under the permit to be exceeded;
 - iii. the Permittee notifies the Director and EPA with written notification at least seven days before the change is made; and
 - iv. the Permittee shall attach the notice to the relevant permit.
 - c. The written notification shall include:
 - i. a description of the change;
 - ii. the date on which the change will occur;
 - iii. any change in emissions; and
 - iv. any permit term or condition that is no longer applicable as a result of the change.
 - d. Section 502(b)(10) changes shall be made in the permit the next time that the permit is revised or renewed, whichever comes first.
3. Off Permit Changes [15A NCAC 2Q .0523(b)]

The Permittee may make changes in the operation or emissions without revising the permit if:

 - a. the change affects only insignificant activities and the activities remain insignificant after the change; or
 - b. the change is not covered under any applicable requirement.
4. Emissions Trading [15A NCAC 2Q .0523(c)]

To the extent that emissions trading is allowed under 15A NCAC 2D, including subsequently adopted maximum achievable control technology standards, emissions trading shall be allowed without permit revision pursuant to 15A NCAC 2Q .0523(c).

I.A. Reporting Requirements for Excess Emissions and Permit Deviations

[15A NCAC 2D .0535(f) and 2Q .0508(f)(2)]

"Excess Emissions" - means an emission rate that exceeds any applicable emission limitation or standard allowed by any rule in Sections .0500, .0900, .1200, or .1400 of Subchapter 2D; or by a permit condition; or that exceeds an emission limit established in a permit issued under 15A NCAC 2Q .0700. *(Note: Definitions of excess emissions under 2D .1110 and 2D .1111 shall apply where defined by rule.)*

"Deviations" - for the purposes of this condition, any action or condition not in accordance with the terms and conditions of this permit including those attributable to upset conditions as well as excess emissions as defined above lasting less than four hours.

Excess Emissions

1. If a source is required to report excess emissions under NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or the operating permit provides for periodic (e.g., quarterly) reporting of excess emissions, reporting shall be performed as prescribed therein.
2. If the source is not subject to NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or these rules do NOT define "excess emissions," the Permittee shall report excess emissions in accordance with 15A NCAC 2D .0535 as follows:
 - a. Pursuant to 15A NCAC 2D .0535, if excess emissions last for more than four hours resulting from a malfunction, a breakdown of process or control equipment, or any other abnormal condition, the owner or operator shall:
 - i. notify the Regional Supervisor or Director of any such occurrence by 9:00 a.m. Eastern Time of the Division's next business day of becoming aware of the occurrence and provide:

- name and location of the facility;
 - nature and cause of the malfunction or breakdown;
 - time when the malfunction or breakdown is first observed;
 - expected duration; and
 - estimated rate of emissions;
- ii. notify the Regional Supervisor or Director immediately when corrective measures have been accomplished; and
 - iii. submit to the Regional Supervisor or Director within 15 days a written report as described in 15A NCAC 2D .0535(f)(3).

Permit Deviations

3. Pursuant to 15A NCAC 2Q .0508(f)(2), the Permittee shall report deviations from permit requirements (terms and conditions) as follows:
 - a. Notify the Regional Supervisor or Director of all other deviations from permit requirements not covered under 15A NCAC 2D .0535 quarterly. A written report to the Regional Supervisor shall include the probable cause of such deviation and any corrective actions or preventative actions taken. The responsible official shall certify all deviations from permit requirements.

I.B. Other Requirements under 15A NCAC 2D .0535

The Permittee shall comply with all other applicable requirements contained in 15A NCAC 2D .0535, including 15A NCAC 2D .0535(c) as follows:

1. Any excess emissions that do not occur during start-up and shut-down shall be considered a violation of the appropriate rule unless the owner or operator of the sources demonstrates to the Director, that the excess emissions are a result of a malfunction. The Director shall consider, along with any other pertinent information, the criteria contained in 15A NCAC 2D .0535(c)(1) through (7).
2. 15A NCAC 2D .0535(g). Excess emissions during start-up and shut-down shall be considered a violation of the appropriate rule if the owner or operator cannot demonstrate that excess emissions are unavoidable.

J. Emergency Provisions [40 CFR 70.6(g)]

The Permittee shall be subject to the following provisions with respect to emergencies:

1. An emergency means any situation arising from sudden and reasonably unforeseeable events beyond the control of the facility, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation, or operator error.
2. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in 3. below are met.
3. The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that include information as follows:
 - a. an emergency occurred and the Permittee can identify the cause(s) of the emergency;
 - b. the permitted facility was at the time being properly operated;
 - c. during the period of the emergency the Permittee took all reasonable steps to minimize levels of emissions that exceeded the standards or other requirements in the permit; and
 - d. the Permittee submitted notice of the emergency to the DAQ within two working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, steps taken to mitigate emissions, and corrective actions taken.

4. In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
5. This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein.

K. Permit Renewal [15A NCAC 2Q .0508(e) and 2Q .0513(b)]

This permit is issued for a fixed term of five years for facilities subject to Title IV requirements and for a term not to exceed five years in the case of all other facilities. This permit shall expire at the end of its term. Permit expiration terminates the facility's right to operate unless a complete renewal application is submitted at least nine months before the date of permit expiration. If the Permittee or applicant has complied with 15A NCAC 2Q .0512(b)(1), this permit shall not expire until the renewal permit has been issued or denied. All terms and conditions of this permit shall remain in effect until the renewal permit has been issued or denied.

L. Need to Halt or Reduce Activity Not a Defense [15A NCAC 2Q .0508(i)(4)]

It shall not be a defense for a Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

M. Duty to Provide Information (submittal of information) [15A NCAC 2Q .0508(i)(9)]

1. The Permittee shall furnish to the DAQ, in a timely manner, any reasonable information that the Director may request in **writing** to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit.
2. The Permittee shall furnish the DAQ copies of records required to be kept by the permit when such copies are requested by the Director. For information claimed to be confidential, the Permittee may furnish such records directly to the EPA upon request along with a claim of confidentiality.

N. Duty to Supplement [15A NCAC 2Q .0507(f)]

The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to the DAQ. The Permittee shall also provide additional information as necessary to address any requirement that becomes applicable to the facility after the date a complete permit application was submitted but prior to the release of the draft permit.

O. Retention of Records [15A NCAC 2Q .0508(f) and 2Q .0508 (l)]

The Permittee shall retain records of all required monitoring data and supporting information for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring information, and copies of all reports required by the permit. These records shall be maintained in a form suitable and readily available for expeditious inspection and review. Any records required by the conditions of this permit shall be kept on site and made available to DAQ personnel for inspection upon request.

P. Compliance Certification [15A NCAC 2Q .0508(n)]

The Permittee shall submit to the DAQ and the EPA (Air and EPCRA Enforcement Branch, EPA, Region 4, 61 Forsyth Street, Atlanta, GA 30303) postmarked on or before March 1 a compliance certification (for the preceding calendar year) by a responsible official with all federally-enforceable terms and conditions in the permit, including emissions limitations, standards, or work practices. It shall be the responsibility of the current owner to submit a compliance certification for the entire year regardless of who owned the facility during the year. The compliance certification shall comply with additional requirements as may be specified under Sections 114(a)(3) or 504(b) of the Federal Clean Air

Act. The compliance certification shall specify:

1. the identification of each term or condition of the permit that is the basis of the certification;
2. the compliance status (with the terms and conditions of the permit for the period covered by the certification);
3. whether compliance was continuous or intermittent; and
4. the method(s) used for determining the compliance status of the source during the certification period.

Q. Certification by Responsible Official [15A NCAC 2Q .0520]

A responsible official shall certify the truth, accuracy, and completeness of any application form, report, or compliance certification required by this permit. All certifications shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

R. Permit Shield for Applicable Requirements [15A NCAC 2Q .0512]

1. Compliance with the terms and conditions of this permit shall be deemed compliance with applicable requirements, where such applicable requirements are included and specifically identified in the permit as of the date of permit issuance.
2. A permit shield shall not alter or affect:
 - a. the power of the Commission, Secretary of the Department, or Governor under NCGS 143-215.3(a)(12), or EPA under Section 303 of the Federal Clean Air Act;
 - b. the liability of an owner or operator of a facility for any violation of applicable requirements prior to the effective date of the permit or at the time of permit issuance;
 - c. the applicable requirements under Title IV; or
 - d. the ability of the Director or the EPA under Section 114 of the Federal Clean Air Act to obtain information to determine compliance of the facility with its permit.
3. A permit shield does not apply to any change made at a facility that does not require a permit or permit revision made under 15A NCAC 2Q .0523.
4. A permit shield does not extend to minor permit modifications made under 15A NCAC 2Q .0515.

S. Termination, Modification, and Revocation of the Permit [15A NCAC 2Q .0519]

The Director may terminate, modify, or revoke and reissue this permit if:

1. the information contained in the application or presented in support thereof is determined to be incorrect;
2. the conditions under which the permit or permit renewal was granted have changed;
3. violations of conditions contained in the permit have occurred;
4. the EPA requests that the permit be revoked under 40 CFR 70.7(g) or 70.8(d); or
5. the Director finds that termination, modification, or revocation and reissuance of the permit is necessary to carry out the purpose of NCGS Chapter 143, Article 21B.

T. Insignificant Activities [15A NCAC 2Q .0503]

Because an emission source or activity is insignificant does not mean that the emission source or activity is exempted from any applicable requirement or that the owner or operator of the source is exempted from demonstrating compliance with any applicable requirement. The Permittee shall have available at the facility at all times and made available to an authorized representative upon request, documentation, including calculations, if necessary, to demonstrate that an emission source or activity is insignificant.

U. Property Rights [15A NCAC 2Q .0508(i)(8)]

This permit does not convey any property rights in either real or personal property or any exclusive privileges.

V. **Inspection and Entry** [15A NCAC 2Q .0508(l) and NCGS 143-215.3(a)(2)]

1. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow the DAQ, or an authorized representative, to perform the following:
 - a. enter the Permittee's premises where the permitted facility is located or emissions-related activity is conducted, or where records are kept under the conditions of the permit;
 - b. have access to and copy, at reasonable times, any records that are required to be kept under the conditions of the permit;
 - c. inspect at reasonable times and using reasonable safety practices any source, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - d. sample or monitor substances or parameters, using reasonable safety practices, for the purpose of assuring compliance with the permit or applicable requirements at reasonable times.Nothing in this condition shall limit the ability of the EPA to inspect or enter the premises of the Permittee under Section 114 or other provisions of the Federal Clean Air Act.
2. No person shall refuse entry or access to any authorized representative of the DAQ who requests entry for purposes of inspection, and who presents appropriate credentials, nor shall any person obstruct, hamper, or interfere with any such authorized representative while in the process of carrying out his official duties. Refusal of entry or access may constitute grounds for permit revocation and assessment of civil penalties.

W. **Annual Fee Payment** [15A NCAC 2Q .0508(i)(10)]

1. The Permittee shall pay all fees in accordance with 15A NCAC 2Q .0200.
2. Payment of fees may be by check or money order made payable to the N.C. Department of Environment and Natural Resources. Annual permit fee payments shall refer to the permit number.
3. If, within 30 days after being billed, the Permittee fails to pay an annual fee, the Director may initiate action to terminate the permit under 15A NCAC 2Q .0519.

X. **Annual Emission Inventory Requirements** [15A NCAC 2Q .0207]

The Permittee shall report by **June 30 of each year** the actual emissions of each air pollutant listed in 15A NCAC 2Q .0207(a) from each emission source within the facility during the previous calendar year. The report shall be in or on such form as may be established by the Director. The accuracy of the report shall be certified by a responsible official of the facility.

Y. **Confidential Information** [15A NCAC 2Q .0107 and 2Q. 0508(i)(9)]

Whenever the Permittee submits information under a claim of confidentiality pursuant to 15A NCAC 2Q .0107, the Permittee may also submit a copy of all such information and claim directly to the EPA upon request. All requests for confidentiality must be in accordance with 15A NCAC 2Q .0107.

Z. **Construction and Operation Permits** [15A NCAC 2Q .0100 and .0300]

A construction and operating permit shall be obtained by the Permittee for any proposed new or modified facility or emission source which is not exempted from having a permit prior to the beginning of construction or modification, in accordance with all applicable provisions of 15A NCAC 2Q .0100 and .0300.

AA. **Standard Application Form and Required Information** [15A NCAC 2Q .0505 and .0507]

The Permittee shall submit applications and required information in accordance with the provisions of 15A NCAC 2Q .0505 and .0507.

BB. Financial Responsibility and Compliance History [15A NCAC 2Q .0507(d)(3)]

The DAQ may require an applicant to submit a statement of financial qualifications and/or a statement of substantial compliance history.

CC. Refrigerant Requirements (Stratospheric Ozone and Climate Protection) [15A NCAC 2Q .0501(e)]

1. If the Permittee has appliances or refrigeration equipment, including air conditioning equipment, which use Class I or II ozone-depleting substances such as chlorofluorocarbons and hydrochlorofluorocarbons listed as refrigerants in 40 CFR Part 82 Subpart A Appendices A and B, the Permittee shall service, repair, and maintain such equipment according to the work practices, personnel certification requirements, and certified recycling and recovery equipment specified in 40 CFR Part 82 Subpart F.
2. The Permittee shall not knowingly vent or otherwise release any Class I or II substance into the environment during the repair, servicing, maintenance, or disposal of any such device except as provided in 40 CFR Part 82 Subpart F.
3. The Permittee shall comply with all reporting and recordkeeping requirements of 40 CFR 82.166. Reports shall be submitted to the EPA or its designee as required.

DD. Prevention of Accidental Releases - Section 112(r) [15A NCAC 2Q .0508(h)]

If the Permittee is required to develop and register a Risk Management Plan with EPA pursuant to Section 112(r) of the Clean Air Act, then the Permittee is required to register this plan in accordance with 40 CFR Part 68.

EE. Prevention of Accidental Releases General Duty Clause - Section 112(r)(1) - FEDERALLY-ENFORCEABLE ONLY

Although a risk management plan may not be required, if the Permittee produces, processes, handles, or stores any amount of a listed hazardous substance, the Permittee has a general duty to take such steps as are necessary to prevent the accidental release of such substance and to minimize the consequences of any release.

FF. Title IV Allowances [15A NCAC 2Q .0508(i)(1)]

This permit does not limit the number of Title IV allowances held by the Permittee, but the Permittee may not use allowances as a defense to noncompliance with any other applicable requirement. The Permittee's emissions may not exceed any allowances that the facility lawfully holds under Title IV of the Federal Clean Air Act.

GG. Air Pollution Emergency Episode [15A NCAC 2D .0300]

Should the Director of the DAQ declare an Air Pollution Emergency Episode, the Permittee will be required to operate in accordance with the Permittee's previously approved Emission Reduction Plan or, in the absence of an approved plan, with the appropriate requirements specified in 15A NCAC 2D .0300.

HH. Registration of Air Pollution Sources [15A NCAC 2D .0200]

The Director of the DAQ may require the Permittee to register a source of air pollution. If the Permittee is required to register a source of air pollution, this registration and required information will be in accordance with 15A NCAC 2D .0202(b).

II. **Ambient Air Quality Standards** [15A NCAC 2D .0501(c)]

In addition to any control or manner of operation necessary to meet emission standards specified in this permit, any source of air pollution shall be operated with such control or in such manner that the source shall not cause the ambient air quality standards in 15A NCAC 2D .0400 to be exceeded at any point beyond the premises on which the source is located. When controls more stringent than named in the applicable emission standards in this permit are required to prevent violation of the ambient air quality standards or are required to create an offset, the permit shall contain a condition requiring these controls.

JJ. **General Emissions Testing and Reporting Requirements** [15A NCAC 2Q .0508(i)(16)]

If emissions testing is required by this permit or the DAQ or if the Permittee submits emissions testing to the DAQ in support of a permit application or to demonstrate compliance, the Permittee shall perform such testing in accordance with 15A NCAC 2D .2600 and follow the procedures outlined below:

1. The Permittee shall submit a completed Protocol Submittal Form to the DAQ Regional Supervisor at least 45 days prior to the scheduled test date. A copy of the Protocol Submittal Form may be obtained from the Regional Supervisor.
2. The Permittee shall notify the Regional Supervisor of the specific test dates at least 15 days prior to testing in order to afford the DAQ the opportunity to have an observer on-site during the sampling program.
3. During all sampling periods, the Permittee shall operate the emission source(s) under maximum normal operating conditions or alternative operating conditions as deemed appropriate by the Regional Supervisor or his delegate.
4. The Permittee shall submit **two** copies of the test report to the DAQ. The test report shall contain at a minimum the following information:
 - a. a description of the training and air testing experience of the person directing the test;
 - b. a certification of the test results by sampling team leader and facility representative;
 - c. a summary of emissions results and text detailing the objectives of the testing program, the applicable state and federal regulations, and conclusions about the testing and compliance status of the emission source(s);
 - d. a detailed description of the tested emission source(s) and sampling location(s) process flow diagrams, engineering drawings, and sampling location schematics should be included as necessary;
 - e. all field, analytical, and calibration data necessary to verify that the testing was performed as specified in the applicable test methods;
 - f. example calculations for at least one test run using equations in the applicable test methods and all test results including intermediate parameter calculations; and
 - g. documentation of facility operating conditions during all testing periods and an explanation relating these operating conditions to maximum normal operation. If necessary, provide historical process data to verify maximum normal operation.
5. The testing requirement(s) shall be considered satisfied only upon written approval of the test results by the DAQ.
6. The DAQ will review emission test results with respect exclusively to the specified testing objectives as proposed by the Permittee and approved by the DAQ.

KK. **Reopening for Cause** [15A NCAC 2Q .0517]

1. A permit shall be reopened and revised under the following circumstances:
 - a. additional applicable requirements become applicable to a facility with remaining permit term of three or more years;
 - b. additional requirements (including excess emission requirements) become applicable to a source covered by Title IV;

- c. the Director or EPA finds that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit; or
 - d. the Director or EPA determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
2. Any permit reopening shall be completed or a revised permit issued within 18 months after the applicable requirement is promulgated. No reopening is required if the effective date of the requirement is after the expiration of the permit term unless the term of the permit was extended pursuant to 15A NCAC 2Q .0513(c).
 3. Except for the state-enforceable only portion of the permit, the procedures set out in 15A NCAC 2Q .0507, .0521, or .0522 shall be followed to reissue the permit. If the State-enforceable only portion of the permit is reopened, the procedures in 15A NCAC 2Q .0300 shall be followed. The proceedings shall affect only those parts of the permit for which cause to reopen exists.
 4. The Director shall notify the Permittee at least 60 days in advance of the date that the permit is to be reopened, except in cases of imminent threat to public health or safety the notification period may be less than 60 days.
 5. Within 90 days, or 180 days if the EPA extends the response period, after receiving notification from the EPA that a permit needs to be terminated, modified, or revoked and reissued, the Director shall send to the EPA a proposed determination of termination, modification, or revocation and reissuance, as appropriate.

LL. Reporting Requirements for Non-Operating Equipment [15A NCAC 2Q .0508(i)(16)]

The Permittee shall maintain a record of operation for permitted equipment noting whenever the equipment is taken from and placed into operation. During operation the monitoring recordkeeping and reporting requirements as prescribed by the permit shall be implemented within the monitoring period.

MM. Fugitive Dust Control Requirement [15A NCAC 2D .0540] - STATE ENFORCEABLE ONLY

As required by 15A NCAC 2D .0540 "Particulates from Fugitive Dust Emission Sources," the Permittee shall not cause or allow fugitive dust emissions to cause or contribute to substantive complaints or excess visible emissions beyond the property boundary. If substantive complaints or excessive fugitive dust emissions from the facility are observed beyond the property boundaries for six minutes in any one hour (using Reference Method 22 in 40 CFR, Appendix A), the owner or operator may be required to submit a fugitive dust plan as described in 2D .0540(f).

"Fugitive dust emissions" means particulate matter from process operations that does not pass through a process stack or vent and that is generated within plant property boundaries from activities such as: unloading and loading areas, process areas stockpiles, stock pile working, plant parking lots, and plant roads (including access roads and haul roads).

- NN. 1. For modifications made pursuant to 15A NCAC 2Q .0501(c)(2), the Permittee shall file a Title V Air Quality Permit Application for the air emission source(s) and associated air pollution control device(s) on or before 12 months after commencing operation.
2. For modifications made pursuant to 15A NCAC 2Q .0501(d)(2), the Permittee shall not begin operation of the air emission source(s) and associated air pollution control device(s) until a Title V Air Quality Permit Application is filed and a construction and operation permit following the procedures of Section .0500 (except for Rule .0504 of this Section) is obtained.
 3. For modifications made pursuant to 502(b)(10), in accordance with 15A NCAC 2Q .0523(a)(1)(C), the Permittee shall notify the Director and EPA (EPA - Air Planning Branch, 61 Forsyth St., Atlanta, GA 30303) in writing at least seven days before the change is made. The written notification shall include:
 - a. a description of the change at the facility;
 - b. the date on which the change will occur;

c. any change in emissions; and

d. any permit term or condition that is no longer applicable as a result of the change.

In addition to this notification requirement, with the next significant modification or Air Quality Permit renewal, the Permittee shall submit a page "E5" of the application forms signed by the responsible official verifying that the application for the 502(b)(10) change/modification, is true, accurate, and complete. Further note that modifications made pursuant to 502(b)(10) do not relieve the Permittee from satisfying preconstruction requirements.

ATTACHMENT

List of Acronyms

AOS	Alternate Operating Scenario
BACT	Best Available Control Technology
Btu	British thermal unit
CEM	Continuous Emission Monitor
CFR	Code of Federal Regulations
CAA	Clean Air Act
DAQ	Division of Air Quality
DENR	Department of Environment and Natural Resources
EMC	Environmental Management Commission
EPA	Environmental Protection Agency
FR	Federal Register
GACT	Generally Available Control Technology
HAP	Hazardous Air Pollutant
MACT	Maximum Achievable Control Technology
NCAC	North Carolina Administrative Code
NCGS	North Carolina General Statutes
NESHAPS	National Emission Standards for Hazardous Pollutants
NO_x	Nitrogen Oxides
NSPS	New Source Performance Standard
OAH	Office of Administrative Hearings
PM	Particulate Matter
PM₁₀	Particulate Matter with Nominal Aerodynamic Diameter of 10 Micrometers or Less
POS	Primary Operating Scenario
PSD	Prevention of Significant Deterioration
RACT	Reasonable Available Control Technology
SIC	Standard Industrial Classification
SIP	State Implementation Plan
SO₂	Sulfur Dioxide
tpy	Tons Per Year
VOC	Volatile Organic Compound