



North Carolina Department of Environment and Natural Resources  
Division of Air Quality

Beverly Eaves Perdue  
Governor

Sheila C. Holman  
Director

Dee Freeman  
Secretary

date, 2011

Mr. Robb Hitch  
General Manager  
Woodgrain Millwork Inc.  
P.O. Box 948  
Marion, Virginia 24354

Dear Mr. Hitch:

SUBJECT: Air Quality Permit No. **07568T11**  
Facility ID: 1400167  
Woodgrain Millwork Inc.  
Lenoir, North Carolina  
Caldwell County  
Fee Class: Title V

In accordance with your completed Air Quality Permit Application for **renewal** of your Title V permit **and consolidation of synthetic minor permit No. 02151R25 received February 11, 2011**, we are forwarding herewith Air Quality Permit No. **07568T11** to Woodgrain Millwork Inc., 700 Complex Place., Lenoir, Caldwell County, North Carolina, authorizing **the construction and operation** of the emission source(s) and associated air pollution control device(s) specified herein. Additionally, any emissions activities determined from your Air Quality Permit Application as being insignificant per 15A North Carolina Administrative Code **2Q .0503(8)** have been listed for informational purposes as an "ATTACHMENT." Please note the requirements for the annual compliance certification are contained in General Condition P in Section 3. The current owner is responsible for submitting a compliance certification for the entire year regardless of who owned the facility during the year.

As the designated responsible official it is your responsibility to review, understand, and abide by all of the terms and conditions of the attached permit. It is also your responsibility to ensure that any person who operates any emission source and associated air pollution control device subject to any term or condition of the attached permit reviews, understands, and abides by the condition(s) of the attached permit that are applicable to that particular emission source.

Permitting Section  
1641 Mail Service Center, Raleigh, North Carolina 27699-1641  
2728 Capital Blvd., Raleigh, NC 27604  
Phone: 919-715-6237 \ FAX: 919-733-5317 \ Internet: [www.daq.state.nc.us](http://www.daq.state.nc.us)

An Equal Opportunity \ Affirmative Action Employer

One  
North Carolina  
*Naturally*

If any parts, requirements, or limitations contained in this Air Quality Permit are unacceptable to you, you have the right to request a formal adjudicatory hearing within 30 days following receipt of this permit, identifying the specific issues to be contested. This hearing request must be in the form of a written petition, conforming to NCGS (North Carolina General Statutes) 150B-23, and filed with both the Office of Administrative Hearings, 6714 Mail Service Center, Raleigh, North Carolina 27699-6714 and the Division of Air Quality, Permitting Section, 1641 Mail Service Center, Raleigh, North Carolina 27699-1641. The form for requesting a formal adjudicatory hearing may be obtained upon request from the Office of Administrative Hearings. Please note that this permit will be stayed in its entirety upon receipt of the request for a hearing. Unless a request for a hearing is made pursuant to NCGS 150B-23, this Air Quality Permit shall be final and binding 30 days after issuance.

You may request modification of your Air Quality Permit through informal means pursuant to NCGS 150B-22. This request must be submitted in writing to the Director and must identify the specific provisions or issues for which the modification is sought. Please note that this Air Quality Permit will become final and binding regardless of a request for informal modification unless a request for a hearing is also made under NCGS 150B-23.

The construction of new air pollution emission source(s) and associated air pollution control device(s), or modifications to the emission source(s) and air pollution control device(s) described in this permit must be covered under an Air Quality Permit issued by the Division of Air Quality prior to construction unless the Permittee has fulfilled the requirements of GS 143-215.108A(b) and received written approval from the Director of the Division of Air Quality to commence construction. Failure to receive an Air Quality Permit or written approval prior to commencing construction is a violation of GS 143-215.108A and may subject the Permittee to civil or criminal penalties as described in GS 143-215.114A and 143-215.114B.

This Air Quality Permit shall be effective from **date, 2011** to **date, 2016**, is nontransferable to future owners and operators, and shall be subject to the conditions and limitations as specified therein.

Should you have any questions concerning this matter, please contact Mr. Mark J. Cuilla, E.I.T., at (919) 733-1499 or [Mark.Cuilla@ncdenr.gov](mailto:Mark.Cuilla@ncdenr.gov).

Sincerely yours,

Donald R. van der Vaart, Ph.D., P.E., J.D.  
Chief

Enclosure

c: Gregg Worley, EPA Region 4 (with review)  
Asheville Regional Office  
Central Files

**ATTACHMENT to Cover Letter to Air Quality Permit Number 07568T11**

**Table of Changes**

<b>Pages</b>	<b>Section</b>	<b>Description of Changes</b>
Attachment	Insignificant activities	-amended permit revision number -amended equipment description per ARO request
Cover	-	-amended all dates and permit revision numbers -added physical address for former Woodgrain Millwork (1400022) -corrected mailing address -added SIC grouping of former Woodgrain Millwork (1400022)
All	Header	-amended permit revision number
3-4	Equipment table	-added location groupings for collection of sources associated with former plants (1400167 and 1400022) -added equipment from former Woodgrain Millwork (1400022) -added GACT designations where necessary
5	2.1 A (table) 2.1 A.1.b	-added reference to combustion source GACT -corrected testing rule cross reference
6	2.1 A.2.d  2.1 A.2.e 2.1 A.2.g	-added testing requirement to be effective 90 days from restart of sources -corrected regulatory authority reference -updated shell reporting language
8	2.1 B (table) 2.1 B.1.c	-added reference to combustion source GACT -corrected testing rule cross reference
9	2.1 B.2.b 2.1 B.3.b	-corrected testing rule cross reference -corrected testing rule cross reference
10-13	2.1 C  2.1 C.3	-added regulatory requirements for Woodgrain Millwork (1400022) -added CAM requirements to be effective 30 days from restart of source (if applicable)
14	2.2 A (table) 2.2 A.1.b	-added reference to combustion source GACT -corrected testing rule cross reference
16	2.2 A.2	-added combustion source GACT placeholder language
17-27	General Conditions	-updated general conditions (v3.4)
28	List of Acronyms	-Added acronyms for CAIR/NAA/RACT per current shell

ATTACHMENT to Cover Letter to Air Quality Permit Number **07568T11**

Insignificant Activities under 15A NCAC 2Q .0503(8)

Emission Source ID No.	Emission Source Description
<b>I-Wood</b>	Wood handling and storage (includes two woodwaste storage silos and screw conveyor systems) <a href="#">associated with boilers (ID Nos. ES-1 and ES-2)</a>
<b>I-Tank</b>	One fuel oil storage tank (20,000 gallon capacity)
<b>I-Vents</b>	Two emergency relief vents associated, one each, with the three-pass scotch marine gasifiers installed on wood boilers



## AIR QUALITY PERMIT

Permit No.	Replaces Permit No.(s)	Effective Date	Expiration Date
<b>07568T11</b>	<b>07568T10 and 02151R25</b>	<b>date, 2011</b>	<b>date, 2016</b>

Until such time as this permit expires or is modified or revoked, the below named Permittee is permitted to construct and operate the emission source(s) and associated air pollution control device(s) specified herein, in accordance with the terms, conditions, and limitations within this permit. This permit is issued under the provisions of Article 21B of Chapter 143, General Statutes of North Carolina as amended, and Title 15A North Carolina Administrative Codes (15A NCAC), Subchapters 2D and 2Q, and other applicable Laws.

Pursuant to Title 15A NCAC, Subchapter 2Q, the Permittee shall not construct, operate, or modify any emission source(s) or air pollution control device(s) without having first submitted a complete Air Quality Permit Application to the permitting authority and received an Air Quality Permit, except as provided in this permit.

**Permittee:** **Woodgrain Millwork Inc.**

**Facility ID:** **1400167**

**Facility Site Location:** **700 Complex Place**  
**City, County, State, Zip:** **Lenoir, Caldwell County, North Carolina 28645**  
**810 Complex Street SW**  
**Lenoir, Caldwell County, North Carolina 28645**

**Mailing Address:** **P.O. Box 948**  
**City, State, Zip:** **Marion, Virginia 24354**

**Application Number:** **1400167.11A**  
**Complete Application Date:** **February 11, 2011**

**Primary SIC Code:** **4961 and 2511**  
**Division of Air Quality,**  
**Regional Office Address:** **Asheville Regional Office**  
**2090 US Highway 70**  
**Swannanoa, North Carolina 28778**

Permit issued this the xxx day of xxxx, 2011

## **Table Of Contents**

SECTION 1: PERMITTED EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES

SECTION 2: SPECIFIC LIMITATIONS AND CONDITIONS

- 2.1- Emission Source(s) Specific Limitations and Conditions (Including specific requirements, testing, monitoring, recordkeeping, and reporting requirements)
- 2.2- Multiple Emission Source(s) Specific Limitations and Conditions (Including specific requirements, testing, monitoring, recordkeeping, and reporting requirements)
- 2.3- Permit Shield for Non-applicable Requirements

SECTION 3: GENERAL PERMIT CONDITIONS

ATTACHMENT

List of Acronyms

## SECTION 1- PERMITTED EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES

The following table contains a summary of all permitted emission sources and associated air pollution control devices and appurtenances:

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
<b>Boilers</b>			
ES-1 (NSPS, Subpart Dc; MACT, Subpart JJJJJJ)	One three-pass scotch marine gasified woodwaste-fired boiler (55.5 million Btu per hour maximum heat input capacity). Site generated used oil may be utilized on boiler start-up only.	C1  CD-2	One multicyclone (40 nine-inch diameter cones) One electric precipitator (5,478 square feet of collection plate area)
ES-2 (NSPS, Subpart Dc; MACT, Subpart JJJJJJ)	One three-pass scotch marine gasified woodwaste-fired boiler (55.5 million Btu per hour maximum heat input capacity). Site generated used oil may be used on boiler start-up only.	C2  F2	One multicyclone (40 nine-inch diameter cones) One bagfilter (5,529 square feet of filter area)
ES-3 (MACT, Subpart JJJJJJ)	One No. 2 fuel oil-fired boiler (97.5 million Btu per hour maximum heat input capacity). Propane may be used as light-off fuel.	NA	NA
ES-4 (MACT, Subpart JJJJJJ)	One No. 2 fuel oil/natural gas-fired boiler (23.7 million Btu per hour maximum heat input capacity). Propane may be used as light-off fuel.	NA	NA

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
<b>Woodworking and Kilns</b>			
ES-13	Woodworking operations	CD-11	One cyclone (80 inches in diameter)
		CD-17	One bagfilter (3,825 square feet of filter area)
		CD-54	One cyclone (104 inches in diameter)
		CD-17	One bagfilter (3,825 square feet of filter area)
		CD-13	One cyclone (48 inches in diameter)
		CD-14	One cyclone (160 inches in diameter)
		CD-18	One bagfilter (3,255 square feet of filter area)
		CD-23	One transfer cyclone (128 inches in diameter)
		CD-24	One bagfilter (1,912 square feet of filter area)
		CD-55	One cyclone (72 inches in diameter)
		CD-17	One bagfilter (3,825 square feet of filter area)
ES-22* ES-22A*	Lumber drying operations	NA	NA

\* Sources with no applicable requirements.

## SECTION 2 - SPECIFIC LIMITATIONS AND CONDITIONS

### 2.1- Emission Source(s) and Control Devices(s) Specific Limitations and Conditions

The emission source(s) and associated air pollution control device(s) and appurtenances listed below are subject to the following specific terms, conditions, and limitations, including the testing, monitoring, recordkeeping, and reporting requirements as specified herein:

- A. One gasified woodwaste-fired boiler (ID No. ES-1) with associated multicyclone (ID No. C1) installed in series with one electrostatic precipitator (ID No. CD-2)**  
**One gasified woodwaste-fired boiler (ID No. ES-2) with associated multicyclone (ID No. C2) installed in series with one bagfilter (ID No. F2)**

The following provides a summary of limits and/or standards for the emission source(s) described above.

Regulated Pollutant	Limits/Standards	Applicable Regulation
Sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 2D .0516
Particulate matter	0.10 pounds per million Btu heat input	15A NCAC 2D .0524 (40 CFR 60, Subpart Dc)
Visible emissions	20 percent opacity	15A NCAC 2D .0524 (40 CFR 60, Subpart Dc)
Particulate matter	Control device – inspection and maintenance	15A NCAC 2D .0502
PM <sub>10</sub> Sulfur dioxide Nitrogen oxide Carbon monoxide Volatile organic compounds	<a href="#">See Section 2.2 A.1</a>	15A NCAC 2Q .0317 (PSD Avoidance)
Hazardous air pollutants	National Emission Standards for Hazardous Air Pollutants for Area Sources: Industrial, Commercial, and Institutional Boilers <a href="#">See Section 2.2 A.2</a>	15A NCAC 2D .1111 (40 CFR 63, Subpart JJJJJ)

#### 1. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

- a. Emissions of sulfur dioxide from these sources (**ID Nos. ES-1 and ES-2**) shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard.

**Testing** [15A NCAC 2Q .0508(f)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 A.1.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

**Monitoring/Recordkeeping/Reporting** [15A NCAC 2Q .0508(f)]

- c. No monitoring/recordkeeping/reporting is required for sulfur dioxide emissions from the firing of woodwaste in these sources (**ID Nos. ES-1 and ES-2**).

## 2. 15A NCAC 2D .0524: NEW SOURCE PERFORMANCE STANDARDS

- a. The Permittee shall comply with all applicable provisions, including the testing, reporting, recordkeeping, and monitoring requirements contained in Environmental Management Commission Standard 15A NCAC 2D .0524 “New Source Performance Standards (NSPS)” as promulgated in 40 CFR 60 Subpart Dc, including Subpart A “General Provisions.”

### Emission Limitation [15A NCAC 2D .0524]

- b. Particulate matter emissions from these sources (**ID Nos. ES-1 and ES-2**) shall not exceed 0.10 pounds per million Btu heat input. [60.43c(b)]
- c. Each source (**ID Nos. ES-1 and ES-2**) shall not cause to be discharged into the atmosphere any gases than exhibit greater than 20 percent opacity (six-minute average), except for one six-minute period per hour of not more than 27 percent opacity. [60.43c(c)]

### Testing [15A NCAC 2D .0524]

- d. Under the provisions of NCGS 143-215.108 and 40 CFR 60.8a, the Permittee shall demonstrate compliance with the emission limits above by testing these sources (**ID Nos. ES-1 and ES-2**) for particulate matter in accordance with a testing protocol approved by the DAQ. Details of the emissions testing and reporting requirements can be found in General Condition JJ. Testing shall be completed **within 90 days of emission source restart**, unless an alternative date is approved by the DAQ. **The Permittee shall notify the Regional Supervisor, ARO of source restart within seven days of restart.** If the results of this test are above the limit given in Section 2.1 A.2.b above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0524.

### Monitoring/Recordkeeping/Reporting [15A NCAC 2Q .0508(f)]

- e. As required by 15A NCAC 2D .0524 under 40 CFR Subpart Dc, 60.47(c):
  - i. the Permittee shall install, calibrate, maintain, test, and operate a continuous opacity monitoring system (COMS) for measuring the opacity of the emissions discharged to the atmosphere and recording the output of the measured opacity on these sources (**ID Nos. ES-1 and ES-2**);
  - ii. the COMS shall be installed and certified in accordance with 40 CFR Part 60, Appendix B, Performance Specifications – Specification and Test Procedures for Opacity Continuous Emission Monitoring Systems in Stationary Sources;
  - iii. the COMS shall be calibrated, audited, and maintained in accordance with 40 CFR Part 60, Subpart A (General Provisions), Section 60.13 and the manufacturer’s written recommendations for inspection, preventative maintenance, and audit;
  - iv. the COMS and the facility shall be assessed for good operation and maintenance (O&M) practices in accordance with 40 CFR Part 60, Subpart A, Section 60.11(d); Subpart Dc, Section 60.47c(a);
  - v. the opacity excess emissions report (EER) shall be submitted in accordance with 40 CFR 60, Subpart 60.7(c) and (d), and 40 CFR Part 60, Subpart Dc, Section 60.48c(c); and
  - vi. the COMS shall meet the “Notification and Recordkeeping Requirements” specified in 40 CFR Part 60, Subpart A, Sections 60.7(a), (b), and (e).
- f. Per 40 CFR 60.48c(g), the Permittee shall keep records of the amounts of each fuel fired each day in these sources (**ID Nos. ES-1 and ES-2**) including used oil combusted upon start-up only.
- g. Per 40 CFR 60.48c(j), the Permittee shall submit a summary report of monitoring and recordkeeping activities **postmarked on or before** January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

### 3. 15A NCAC 2D .0502: PURPOSE

- a. All sources shall be provided with the maximum feasible control. To ensure that maximum feasible control is maintained for particulate matter from these sources (**ID Nos. ES-1 and ES-2**), the following monitoring, recordkeeping, and reporting shall apply with the electrostatic precipitator (**ID No. CD-2**), bagfilter (**ID No. F2**), and multicyclones (**ID Nos. C1 and C2**).

**Monitoring/Recordkeeping** [15A NCAC 2Q .0508(f)]

- b. Particulate matter from these sources (**ID Nos. ES-1 and ES-2**) shall be controlled by two multicyclones (**ID Nos. C1 and C2**), installed one per source. To assure compliance, the Permittee shall perform inspections and maintenance as recommended by the manufacturer. In addition to the manufacturer's inspection and maintenance recommendations, or if there are no manufacturer's inspection and maintenance recommendations, as a minimum, the inspection and maintenance requirement must include the following:
  - i. a monthly external visual inspection of the system ductwork and material collection units for leaks; and
  - ii. an annual (for each 12-month period following the initial inspection) internal inspection of the multicyclones for structural integrity.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0502 if the multicyclones and ductwork are not inspected and maintained.

- c. Particulate matter from this source (**ID No. ES-2**) shall be controlled by one bagfilter (**ID No. F2**). To assure compliance, the Permittee shall perform inspections and maintenance as recommended by the manufacturer. In addition to the manufacturer's inspection and maintenance recommendations, or if there are no manufacturer's inspection and maintenance recommendations, as a minimum, the inspection and maintenance requirement must include the following:
  - i. a monthly external visual inspection of the system ductwork and material collection unit for leaks; and
  - ii. an annual (for each 12-month period following the initial inspection) internal inspection of the bagfilter for structural and fabric integrity.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0502 if the bagfilter and ductwork are not inspected and maintained.

- d. Particulate matter from this source (**ID No. ES-1**) shall be controlled by one electrostatic precipitator (**ID No. CD-2**). To assure compliance, the Permittee shall perform inspections and maintenance as recommended by the manufacturer. In addition to the manufacturer's inspection and maintenance recommendations, or if there are no manufacturer's inspection and maintenance recommendations, as a minimum, the inspection and maintenance requirement must include the following:
  - i. a monthly external visual inspection of the system ductwork and electrostatic precipitator; and
  - ii. an annual (for each 12-month period following the initial inspection) internal inspection of the electrostatic precipitator to ensure structural and component integrity.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0502 if the electrostatic precipitator and ductwork are not inspected and maintained.

- e. The results of inspection and maintenance shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized DAQ representative upon request. The logbook shall record the following:
  - i. the date and time of each recorded action;
  - ii. the results of each inspection;
  - iii. the results of any maintenance performed on any control device; and
  - iv. any variance from manufacturer's recommendations, if any, and corrections made.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0502 if these records are not maintained.

**Reporting** [15A NCAC 2Q .0508(f)]

- f. Within 30 days of a receipt of a written request from the DAQ, the Permittee shall submit a report of any maintenance performed on any control device.
- g. The Permittee shall submit a summary report of monitoring and recordkeeping activities postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

**B. One No. 2 fuel oil-fired boiler (ID No. ES-3)  
One No. 2 fuel oil/natural gas-fired boiler (ID No. ES-4)**

The following provides a summary of limits and/or standards for the emission source(s) described above.

Regulated Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	<b>(ID No. ES-3 only)</b> 0.33 pounds per million Btu heat input <b>(ID No. ES-4 only)</b> 0.31 pounds per million Btu heat input	15A NCAC 2D .0503
Sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 2D .0516
Visible emissions	40 percent opacity	15A NCAC 2D .0521
PM <sub>10</sub> Sulfur dioxide Nitrogen oxide Carbon monoxide Volatile organic compounds	<a href="#">See Section 2.2 A.1</a>	15A NCAC 2Q .0317 (PSD Avoidance)
Hazardous air pollutants	<a href="#">National Emission Standards for Hazardous Air Pollutants for Area Sources: Industrial, Commercial, and Institutional Boilers</a> <a href="#">See Section 2.2 A.2</a>	15A NCAC 2D .1111 (40 CFR 63, Subpart JJJJJ)

**1. 15A NCAC 2D .0503: PARTICULATES FROM FUEL BURNING INDIRECT HEAT EXCHANGERS**

- a. Emissions of particulate matter from the combustion of No. 2 fuel oil that is discharged from this source **(ID No. ES-3)** into the atmosphere shall not exceed 0.33 pounds per million Btu heat input.
- b. Emissions of particulate matter from the combustion of No. 2 fuel oil/natural gas that is discharged from this source **(ID No. ES-4)** into the atmosphere shall not exceed 0.31 pounds per million Btu heat input.

**Testing** [15A NCAC 2Q .0508(f)]

- c. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above any limit given in Section 2.1 B.1.a or b above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0503.

**Monitoring/Recordkeeping/Reporting** [15A NCAC 2Q .0508(f)]

- d. No monitoring/recordkeeping/reporting is required for particulate matter from the firing of No. 2 fuel oil/natural gas in these sources (**ID Nos. ES-3 and ES-4**).

**2. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES**

- a. Emissions of sulfur dioxide from these sources (**ID Nos. ES-3 and ES-4**) shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard.

**Testing** [15A NCAC 2Q .0508(f)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above any limit given in Section 2.1 B.2.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

**Monitoring/Recordkeeping/Reporting** [15A NCAC 2Q .0508(f)]

- c. No monitoring/recordkeeping/reporting is required for sulfur dioxide from the firing of No. 2 fuel oil/natural gas in these sources (**ID Nos. ES-3 and ES-4**).

**3. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS**

- a. Visible emissions from these sources (**ID Nos. ES-3 and ES-4**) shall not be more than 40 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 40 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 90 percent opacity.

**Testing** [15A NCAC 2Q .0508(f)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above any limit given in **Section 2.1 B.3.a** above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

**Monitoring/Recordkeeping/Reporting** [15A NCAC 2Q .0508(f)]

- c. No monitoring/recordkeeping/reporting is required for visible emissions from the firing of No. 2 fuel oil/natural gas in these sources (**ID Nos. ES-3 and ES-4**).

- C. Woodworking operations (ID No. ES-13) with separate group processes controlled by:**
- one cyclone (ID No. CD-11) installed in series with one bagfilter (ID No. CD-17);
  - one cyclone (ID No. CD-54) installed in series with one bagfilter (ID No. CD-17);
  - two cyclones (ID Nos. CD-13 and CD-14) each in series installed in series with one bagfilter (ID No. CD-18)
  - one transfer cyclone (ID No. CD-23) installed in series with one bagfilter (ID No. CD-24) on the dust silo
  - one cyclone (ID No. CD-55) installed in series with one bagfilter (ID No. CD-17)

The following provides a summary of limits and/or standards for the emission source(s) described above.

Regulated Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	Adequate ductwork and properly designed collectors	15A NCAC 2D .0512
Visible emissions	20 percent opacity	15A NCAC 2D .0521
Particulate matter	Compliance Assurance Monitoring	15A NCAC 2D .0614
PM <sub>10</sub> Sulfur dioxide Nitrogen oxide Carbon monoxide Volatile organic compounds	<b>See Section 2.2 A</b>	15A NCAC 2Q .0317 (PSD Avoidance)

**1. 15A NCAC 2D .0512: PARTICULATES FROM MISCELLANEOUS WOOD PRODUCTS FINISHING PLANTS**

- a. The Permittee shall not cause, allow, or permit particulate matter caused by the working, sanding, or finishing of wood to be discharged from any stack, vent, or building into the atmosphere without providing, as a minimum for its collection, adequate ductwork and properly designed collectors. In no case shall the ambient air quality standards be exceeded beyond the property line.

**Monitoring/Recordkeeping** [15A NCAC 2Q .0508(f)]

- b. Particulate matter emissions from the wood material collection systems (ID No. ES-13) shall be controlled by six cyclones (ID Nos. CD-11, CD-13, CD-14, CD-23, CD-54, and CD-55) and three bagfilters (ID Nos. CD-17, CD-18, and CD-24) as described above. To assure compliance, the Permittee shall perform inspections and maintenance as recommended by the manufacturer, if any. As a minimum, the inspection and maintenance program shall include:
  - i. monthly external inspection of the ductwork, cyclones, and bagfilters noting the structural integrity; and
  - ii. an annual (for each 12-month period following the initial inspection) internal inspection of the bagfilters and cyclones noting the structural integrity and the condition of the filters.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0512 if the ductwork, cyclones, and bagfilters are not inspected and maintained.
- c. The results of inspection and maintenance for the cyclones and bagfilters shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
  - i. the date and time of each recorded action;
  - ii. the results of each inspection; and
  - iii. the results of maintenance performed on any control device.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0512 if these records are not maintained.

**Reporting** [15A NCAC 2Q .0508(f)]

- d. The Permittee shall submit the results of any maintenance performed on any control device within 30 days of a written request by the DAQ.
- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

**2. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS**

- a. Visible emissions from this source (**ID No. ES-13**) shall not be more than 20 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 20 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 87 percent opacity.

**Testing** [15A NCAC 2Q .0508(f)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 C.2.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

**Monitoring/Recordkeeping** [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a week while source is operating, the Permittee shall observe the emission points of this source (**ID No. ES-13**) for any visible emissions above normal. The weekly observation must be made for each week of the calendar year period while the source is operating to ensure compliance with this requirement. If visible emissions from this source are observed to be above normal, the Permittee shall either:
  - i. take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or
  - ii. demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 2D .2610 (Method 9) for 12 minutes is below the limit given in Section 2.1 C.2.a above.

If the above-normal emissions are not corrected per i. above or if the demonstration in ii. above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
  - i. the date and time for each recorded action;
  - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
  - iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

**Reporting** [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a report of the observations postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

**3. 15A NCAC 2D .0614: COMPLIANCE ASSURANCE MONITORING**

- a. Within 30-days of resumption of operation of this group of sources (**ID No. ES-13**), the Permittee shall:
  - i. determine applicability of this regulation to each of the control devices listed below;
  - ii. if applicable, establish the “normal” operating range of each applicable control device listed below; and
  - iii. submit an administrative amendment to incorporate the established “normal” operating range of each applicable control device listed above.

The Permittee shall notify the Regional Office Supervisor, ARO, within seven days of resumption of operation of this group of sources (**ID No. ES-13**). The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0614 if any of the requirements in this Paragraph are not met within the timelines specified.

- b. For this group of sources (**ID No. ES-13**), as required by 40 CFR 64 and 15A NCAC 2D .0614, the Permittee shall comply with the following monitoring and recordkeeping requirements for particulate matter, including parameters to be monitored, parameter ranges, and performance criteria.

	<b>Indicator</b>
I. Indicator	Pressure drop
Measurement Approach	Pressure drop across the control device is measured with differential pressure gauges daily.
II. Indicator Range	An excursion is defined as a pressure drop other than normal*. Excursions trigger an inspection, corrective action, and a recordkeeping requirement.
QIP Threshold	None selected.

	<b>Indicator</b>
<b>III. Performance Criteria</b>	
<b>A. Data Representativeness</b>	Pressure taps are located at each control device inlet and outlet. The gauges have a minimum accuracy of 0.5 inches of water.
<b>B. Verification of Operational Status</b>	The pressure gauges are checked daily for operation.
<b>C. QA/QC Practices</b>	Calibrate, maintain, and operate instrumentation using procedures that take into account manufacturer’s specifications.
<b>D. Monitoring Frequency</b>	Pressure drop are recorded daily.
<b>Data Collection Procedures</b>	Readings are manually recorded in a logbook daily.
<b>Averaging Periods</b>	NA

\* “Normal” pressure drop ranges are as follows:

- CD-11 - ### inches of water
- CD-17 - ### inches of water
- CD-54 - ### inches of water
- CD-13 - ### inches of water
- CD-14 - ### inches of water
- CD-18 - ### inches of water
- CD-23 - ### inches of water
- CD-24 - ### inches of water
- CD-55 - ### inches of water

**Reporting** [15A NCAC 2Q .0508(f)]

- c. Once applicability of this regulation is established per the requirements in Section 2.1 C.3.a above, the Permittee shall submit a summary report of monitoring and recordkeeping activities postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified including any monitoring malfunctions as defined in 64.7(c) and required in 64.9(a)(2)(ii).

## 2.2- Multiple Emission Sources and Specific Limitations and Conditions

- A. **One gasified woodwaste-fired boiler (ID No. ES-1) with associated multicyclone (ID No. C1) installed in series with one electrostatic precipitator (ID No. CD-2)**  
**One gasified woodwaste-fired boiler (ID No. ES-2) with associated multicyclone (ID No. C2) installed in series with one bagfilter (ID No. F2)**  
**One No. 2 fuel oil-fired boiler (ID No. ES-3)**  
**One No. 2 fuel oil/natural gas-fired boiler (ID No. ES-4)**

The following provides a summary of limits and/or standards for the emission source(s) described above.

Regulated Pollutant	Limits/Standards	Applicable Regulation
PM <sub>10</sub> Sulfur dioxide Nitrogen oxide Carbon monoxide Volatile organic compounds	Less than 250 tons per 12-month period (each pollutant)	15A NCAC 2Q .0317 (PSD Avoidance)
Hazardous air pollutants	National Emission Standards for Hazardous Air Pollutants for Area Sources: Industrial, Commercial, and Institutional Boilers	15A NCAC 2D .1111 (40 CFR 63, Subpart JJJJJ)

### 1. 15A NCAC 2Q .0317: AVOIDANCE CONDITIONS for 15A NCAC 2D .0530: PREVENTION OF SIGNIFICANT DETERIORATION

- a. In order to avoid applicability of 15A NCAC 2D .0530(g) for major sources, these sources (**ID Nos. ES-1 through ES-4**) shall discharge into the atmosphere less than 250 tons each of PM<sub>10</sub>, sulfur dioxide, nitrogen oxide, carbon monoxide, and volatile organic compounds per consecutive 12-month period.

#### **Testing** [15A NCAC 2Q .0508(f)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limits given in Section 2.2 A.1.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530.

#### **Monitoring/Recordkeeping** [15A NCAC 2Q .0508(f)]

- c. The Permittee shall keep monthly records in a logbook (written or electronic format) of the amount of woodwaste/No. 2 fuel oil/natural gas fired in these sources (**ID Nos. ES-1 through ES-4**). The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530 if the amount of fuel is not monitored.
- d. Each calendar month, the Permittee shall calculate and record the PM<sub>10</sub>, sulfur dioxide, nitrogen oxide, carbon monoxide, and volatile organic compound emissions from these sources (**ID Nos. ES-1 through ES-4**) in accordance with the following equations:
- i. Particulate matter.

$$E_{PM10} = [(Q_{GWa})(EF_{GW1a}) + (Q_{GWb})(EF_{GW1b}) + (Q_{FO})(EF_{FO1})] / 2000$$

ii. Sulfur dioxide.

$$E_{SO_2} = [(Q_{GW})(EF_{GW2}) + (Q_{FO})(EF_{FO2})] / 2000$$

iii. Nitrogen oxides.

$$E_{NO_x} = [(Q_{GW})(EF_{GW3}) + (Q_{FO})(EF_{FO3})] / 2000$$

iv. Carbon monoxide.

$$E_{CO} = [(Q_{GW})(EF_{GW4}) + (Q_{FO})(EF_{FO4})] / 2000$$

v. Volatile organic compounds.

$$E_{VOC} = [(Q_{GW})(EF_{GW5}) + (Q_{FO})(EF_{FO5})] / 2000$$

Where:  $E_{PM_{10}}$  = Particulate matter emissions in tons per month

$E_{SO_2}$  = Sulfur dioxide emissions in tons per month

$E_{NO_x}$  = Nitrogen oxide emissions in tons per month

$E_{CO}$  = Carbon monoxide emissions in tons per month

$E_{VOC}$  = Volatile organic compounds emissions in tons per month

$Q_{GW}$  = Total quantity of gasified wood combusted in million Btu per month

$Q_{GWa}$  = Quantity of gasified wood combusted in **ES-1** in million Btu per month

$Q_{GWb}$  = Quantity of gasified wood combusted in **ES-2** in million Btu per month

$Q_{FO}$  = Quantity of fuel oil combusted in million Btu per month

$EF_{GW1a}$  = 0.084 pounds  $PM_{10}$  per million Btu (based on 7/25/02 Stack test; **ID No. ES-1**)

$EF_{GW1b}$  = 0.0036 pounds  $PM_{10}$  per million Btu (based on 7/24/02 Stack test; **ID No. ES-2**)

$EF_{GW2}$  = 0.00519 pounds  $SO_2$  per million Btu (based on 10/1/98 Stack test)

$EF_{GW3}$  = 0.830 pounds  $NO_x$  per million Btu (based on 7/25/02 Stack test)

$EF_{GW4}$  = 0.162 pounds CO per million Btu (based on 7/25/02 Stack test)

$EF_{GW5}$  = 0.0021 pounds VOC per million Btu (based on 7/25/02 Stack test)

$EF_{FO1}$  = 3.3 pounds  $PM_{10}$  per  $10^3$  gallons [0.024 pounds per million Btu] (based on 9/98 AP42)

$EF_{FO2}$  = 28.4 pounds  $SO_2$  per  $10^3$  gallons [0.204 pounds per million Btu] (based on 9/98 AP42)

$EF_{FO3}$  = 24 pounds  $NO_x$  per  $10^3$  gallons [0.173 pounds per million Btu] (based on 9/98 AP42)

$EF_{FO4}$  = 5 pounds CO per  $10^3$  gallons [0.036 pounds per million Btu] (based on 9/98 AP42)

$EF_{FO5}$  = 0.2 pounds VOC per  $10^3$  gallons [0.001 pounds per million Btu] (based on 9/98 AP42)

Assumptions: Fuel oil heating value = 139,000 Btu per gallon

Wood heating value = 8000 Btu per pound @ 7% moisture

1.242 million Btu per million pounds steam produced (wood combustion)

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530 if these records are not maintained or if the  $PM_{10}$ , sulfur dioxide, nitrogen oxide, carbon monoxide, or volatile organic compound emissions exceed the limits in Section 2.2 A.1.a above.

- e. The Permittee shall submit an application for a permit modification within 30 days of revising any emission factor used in the compliance demonstrations, as provided in Sections 2.2 A.1.d.i through v above (e.g., as a result of stack test results or other information). The emission factor(s) may be updated using an administrative permit amendment as provided in 15A NCAC 2Q .0514. Factors provided in U.S. EPA's AP-42, shall be excluded from this requirement (i.e., no permit modification is required for U.S. EPA's AP-42 updates).

**Reporting** [15A NCAC 2Q .0508(f)]

- f. The Permittee shall submit a summary report of the monitoring and recordkeeping activities postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. The report shall contain the following:
- i. the monthly quantities of wood/No. 2 fuel oil/natural gas combusted for the previous 17 months;
  - ii. the monthly emission totals for PM<sub>10</sub>, sulfur dioxide, nitrogen oxide, carbon monoxide, and volatile organic compound actual emissions for the previous 17 months. The emissions must be calculated for each of the 12-month periods over the previous 17 months; and
  - iii. the rolling 12-month emission totals for PM<sub>10</sub>, sulfur dioxide, nitrogen oxide, carbon monoxide, and volatile organic compound actual emissions for the previous 17 months.
- All instances of deviations from the requirements of this permit must be clearly identified.

## 2. 15A NCAC 2D .1111: MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY

- a. For these sources (**ID Nos. ES-1 through ES-4**), the Permittee shall demonstrate compliance by the dates specified in 40 CFR 63.11196 with all applicable requirements of 15A NCAC 2D .1111 "Maximum Achievable Control Technology" and 40 CFR 63 Subpart JJJJJ "National Emission Standards for Hazardous Air Pollutants for Area Sources: Industrial, Commercial, and Institutional Boilers."

### 2.3- Permit Shield for Non-applicable Requirements

The Permittee is shielded from the following non-applicable requirements as of the date of the issuance of this permit based on information furnished in letters dated **March 30, 2001**, **May 7, 2001** and **June 16, 2002** from Trigen-BioPower, Inc. This shield does not apply to future modifications or changes in the method of operation. [15A NCAC 2Q .0512(a)(1)(B)]:

- a. 15A NCAC 2D .0524 [40 CFR 60.40c (Subpart Dc)] is not applicable to these sources (**ID Nos. ES-3 and ES-4**) because:
- i. Subpart Dc applies to steam generating units that commence construction, modification, or reconstruction after June 9, 1989 and that have a maximum design heat input capacity between 10 and 100 million Btu per hour;
  - ii. This source (**ID No. ES-3**) has a maximum heat input capacity of 97.5 million Btu per hour and was manufactured (constructed) in 1969. This source (**ID No. ES-4**) has a maximum heat input capacity of 23.7 million Btu per hour and was manufactured (constructed) in 1971;
  - iii. These sources (**ID Nos. ES-3 and ES-4**) was purchased or leased by the Permittee and relocated/reassembled at the Lenoir, North Carolina facility in 1993 and 1995, respectively. While some source components were replaced as part of the reassembly, the fixed capital cost of the replacement components did not exceed 50 percent of the fixed capital costs that would be required to construct a comparable entirely new source. Thus these sources cannot be considered "reconstructed" under the definition in 40 CFR 60.15; and

- iv. The design capacities or method of operation were not altered as a result of the reassembly and recommissioning of these sources (**ID Nos. ES-3 and ES-4**). Therefore, there was no increase in the hourly emission rate from these sources and this project cannot be considered a “modification” under 40 CFR 60.14.
- b. 15A NCAC 2D .1111 is not applicable facility-wide because:
  - i. Source testing conducted in July 2002 for hydrogen chloride, formaldehyde, and acetaldehyde and the development of source specific emission factors for these pollutants; and
  - ii. Applying current AP-42 emission factors for the remaining hazardous air pollutants (HAPs) emitted;indicates that the potential emissions for all HAPs emitted from this facility are below the Title III threshold of 10 tons per year for any single HAP or greater than 25 tons per year for all HAPs combined. As such, the facility is classified as a Title III minor source as affirmed by DAQ in its July 11, 2003 letter to the Permittee, and is not subject to Section 112 requirements. The Permittee shall keep a record of the applicability determination on site at the source for a period of five years after the determination, or until the source becomes an affected source. The determination must include the analysis demonstrating why the Permittee believes the source is unaffected pursuant to 40 CFR 63.10(b)(3). The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if these records are not maintained.

### **SECTION 3 - GENERAL CONDITIONS (v3.4)**

This section describes terms and conditions applicable to this Title V facility.

- A. **General Provisions** [NCGS 143-215 and 15A NCAC 2Q .0508(i)(16)]
  1. Terms not otherwise defined in this permit shall have the meaning assigned to such terms as defined in 15A NCAC 2D and 2Q.
  2. The terms, conditions, requirements, limitations, and restrictions set forth in this permit are binding and enforceable pursuant to NCGS 143-215.114A and 143-215.114B, including assessment of civil and/or criminal penalties. Any unauthorized deviation from the conditions of this permit may constitute grounds for revocation and/or enforcement action by the DAQ.
  3. This permit is not a waiver of or approval of any other Department permits that may be required for other aspects of the facility which are not addressed in this permit.
  4. This permit does not relieve the Permittee from liability for harm or injury to human health or welfare, animal or plant life, or property caused by the construction or operation of this permitted facility, or from penalties therefore, nor does it allow the Permittee to cause pollution in contravention of state laws or rules, unless specifically authorized by an order from the North Carolina Environmental Management Commission.
  5. Except as identified as state-only requirements in this permit, all terms and conditions contained herein shall be enforceable by the DAQ, the EPA, and citizens of the United States as defined in the Federal Clean Air Act.
  6. Any stationary source of air pollution shall not be operated, maintained, or modified without the appropriate and valid permits issued by the DAQ, unless the source is exempted by rule. The DAQ may issue a permit only after it receives reasonable assurance that the installation will not cause air pollution in violation of any of the applicable requirements. A permitted installation may only be operated, maintained, constructed, expanded, or modified in a manner that is consistent with the terms of this permit.

**B. Permit Availability** [15A NCAC 2Q .0507(k) and .0508(i)(9)(B)]

The Permittee shall have available at the facility a copy of this permit and shall retain for the duration of the permit term one complete copy of the application and any information submitted in support of the application package. The permit and application shall be made available to an authorized representative of Department of Environment and Natural Resources upon request.

**C. Severability Clause** [15A NCAC 2Q .0508(i)(2)]

In the event of an administrative challenge to a final and binding permit in which a condition is held to be invalid, the provisions in this permit are severable so that all requirements contained in the permit, except those held to be invalid, shall remain valid and must be complied with.

**D. Submissions** [15A NCAC 2Q .0507(e) and 2Q .0508(i)(16)]

Except as otherwise specified herein, two copies of all documents, reports, test data, monitoring data, notifications, request for renewal, and any other information required by this permit shall be submitted to the appropriate Regional Office. Refer to the Regional Office address on the cover page of this permit. For continuous emissions monitoring systems (CEMS) reports, continuous opacity monitoring systems (COMS) reports, quality assurance (QA)/quality control (QC) reports, acid rain CEM certification reports, and NOx budget CEM certification reports, one copy shall be sent to the appropriate Regional Office and one copy shall be sent to:

Supervisor, Stationary Source Compliance  
North Carolina Division of Air Quality  
1641 Mail Service Center  
Raleigh, NC 27699-1641

All submittals shall include the Facility name and Facility ID number (refer to the cover page of this permit).

**E. Duty to Comply** [15A NCAC 2Q .0508(i)(2)]

The Permittee shall comply with all terms, conditions, requirements, limitations and restrictions set forth in this permit. Noncompliance with any permit condition except conditions identified as state-only requirements constitutes a violation of the Federal Clean Air Act. Noncompliance with any permit condition is grounds for enforcement action, for permit termination, revocation and reissuance, or modification, or for denial of a permit renewal application.

**F. Circumvention - STATE ENFORCEABLE ONLY**

The facility shall be properly operated and maintained at all times in a manner that will effect an overall reduction in air pollution. Unless otherwise specified by this permit, no emission source may be operated without the concurrent operation of its associated air pollution control device(s) and appurtenances.

**G. Permit Modifications**

1. Administrative Permit Amendments [15A NCAC 2Q .0514]

The Permittee shall submit an application for an administrative permit amendment in accordance with 15A NCAC 2Q .0514.

2. Transfer in Ownership or Operation and Application Submittal Content [15A NCAC 2Q .0524 and 2Q .0505]

The Permittee shall submit an application for an ownership change in accordance with 15A NCAC 2Q.0524 and 2Q .0505.

3. Minor Permit Modifications [15A NCAC 2Q .0515]  
The Permittee shall submit an application for a minor permit modification in accordance with 15A NCAC 2Q .0515.
4. Significant Permit Modifications [15A NCAC 2Q .0516]  
The Permittee shall submit an application for a significant permit modification in accordance with 15A NCAC 2Q .0516.
5. Reopening for Cause [15A NCAC 2Q .0517]  
The Permittee shall submit an application for reopening for cause in accordance with 15A NCAC 2Q .0517.

#### H. **Changes Not Requiring Permit Modifications**

##### 1. Reporting Requirements.

Any of the following that would result in new or increased emissions from the emission source(s) listed in Section 1 must be reported to the Regional Supervisor, DAQ:

- a. changes in the information submitted in the application;
- b. changes that modify equipment or processes; or
- c. changes in the quantity or quality of materials processed.

If appropriate, modifications to the permit may then be made by the DAQ to reflect any necessary changes in the permit conditions. In no case are any new or increased emissions allowed that will cause a violation of the emission limitations specified herein.

##### 2. Section 502(b)(10) Changes [15A NCAC 2Q .0523(a)]

- a. "Section 502(b)(10) changes" means changes that contravene an express permit term or condition. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.
- b. The Permittee may make Section 502(b)(10) changes without having the permit revised if:
  - i. the changes are not a modification under Title I of the Federal Clean Air Act;
  - ii. the changes do not cause the allowable emissions under the permit to be exceeded;
  - iii. the Permittee notifies the Director and EPA with written notification at least seven days before the change is made; and
  - iv. the Permittee shall attach the notice to the relevant permit.
- c. The written notification shall include:
  - i. a description of the change;
  - ii. the date on which the change will occur;
  - iii. any change in emissions; and
  - iv. any permit term or condition that is no longer applicable as a result of the change.
- d. Section 502(b)(10) changes shall be made in the permit the next time that the permit is revised or renewed, whichever comes first.

##### 3. Off Permit Changes [15A NCAC 2Q .0523(b)]

The Permittee may make changes in the operation or emissions without revising the permit if:

- a. the change affects only insignificant activities and the activities remain insignificant after the change; or
- b. the change is not covered under any applicable requirement.

##### 4. Emissions Trading [15A NCAC 2Q .0523(c)]

To the extent that emissions trading is allowed under 15A NCAC 2D, including subsequently adopted maximum achievable control technology standards, emissions trading shall be allowed without permit revision pursuant to 15A NCAC 2Q .0523(c).

**I.A. Reporting Requirements for Excess Emissions and Permit Deviations**

[15A NCAC 2D .0535(f) and 2Q .0508(f)(2)]

“Excess Emissions” - means an emission rate that exceeds any applicable emission limitation or standard allowed by any rule in Sections .0500, .0900, .1200, or .1400 of Subchapter 2D; or by a permit condition; or that exceeds an emission limit established in a permit issued under 15A NCAC 2Q .0700.

*(Note: Definitions of excess emissions under 2D .1110 and 2D .1111 shall apply where defined by rule.)*

“Deviations” - for the purposes of this condition, any action or condition not in accordance with the terms and conditions of this permit including those attributable to upset conditions as well as excess emissions as defined above lasting less than four hours.

Excess Emissions

1. If a source is required to report excess emissions under NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or the operating permit provides for periodic (e.g., quarterly) reporting of excess emissions, reporting shall be performed as prescribed therein.
2. If the source is not subject to NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or these rules do NOT define "excess emissions," the Permittee shall report excess emissions in accordance with 15A NCAC 2D .0535 as follows:
  - a. Pursuant to 15A NCAC 2D .0535, if excess emissions last for more than four hours resulting from a malfunction, a breakdown of process or control equipment, or any other abnormal condition, the owner or operator shall:
    - i. notify the Regional Supervisor or Director of any such occurrence by 9:00 a.m. Eastern Time of the Division's next business day of becoming aware of the occurrence and provide:
      - name and location of the facility;
      - nature and cause of the malfunction or breakdown;
      - time when the malfunction or breakdown is first observed;
      - expected duration; and
      - estimated rate of emissions;
    - ii. notify the Regional Supervisor or Director immediately when corrective measures have been accomplished; and
    - iii. submit to the Regional Supervisor or Director within 15 days a written report as described in 15A NCAC 2D .0535(f)(3).

Permit Deviations

3. Pursuant to 15A NCAC 2Q .0508(f)(2), the Permittee shall report deviations from permit requirements (terms and conditions) as follows:
  - a. Notify the Regional Supervisor or Director of all other deviations from permit requirements not covered under 15A NCAC 2D .0535 quarterly. A written report to the Regional Supervisor shall include the probable cause of such deviation and any corrective actions or preventative actions taken. The responsible official shall certify all deviations from permit requirements.

**I.B. Other Requirements under 15A NCAC 2D .0535**

The Permittee shall comply with all other applicable requirements contained in 15A NCAC 2D .0535, including 15A NCAC 2D .0535(c) as follows:

1. Any excess emissions that do not occur during start-up and shut-down shall be considered a violation of the appropriate rule unless the owner or operator of the sources demonstrates to the Director, that the excess emissions are a result of a malfunction. The Director shall consider, along with any other pertinent information, the criteria contained in 15A NCAC 2D .0535(c)(1) through (7).
2. 15A NCAC 2D .0535(g). Excess emissions during start-up and shut-down shall be considered a violation of the appropriate rule if the owner or operator cannot demonstrate that excess emissions are unavoidable.

J. **Emergency Provisions** [40 CFR 70.6(g)]

The Permittee shall be subject to the following provisions with respect to emergencies:

1. An emergency means any situation arising from sudden and reasonably unforeseeable events beyond the control of the facility, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation, or operator error.
2. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in 3. below are met.
3. The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that include information as follows:
  - a. an emergency occurred and the Permittee can identify the cause(s) of the emergency;
  - b. the permitted facility was at the time being properly operated;
  - c. during the period of the emergency the Permittee took all reasonable steps to minimize levels of emissions that exceeded the standards or other requirements in the permit; and
  - d. the Permittee submitted notice of the emergency to the DAQ within two working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, steps taken to mitigate emissions, and corrective actions taken.
4. In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
5. This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein.

K. **Permit Renewal** [15A NCAC 2Q .0508(e) and 2Q .0513(b)]

This permit is issued for a fixed term of five years for facilities subject to Title IV requirements and for a term not to exceed five years in the case of all other facilities. This permit shall expire at the end of its term. Permit expiration terminates the facility's right to operate unless a complete renewal application is submitted at least nine months before the date of permit expiration. If the Permittee or applicant has complied with 15A NCAC 2Q .0512(b)(1), this permit shall not expire until the renewal permit has been issued or denied. All terms and conditions of this permit shall remain in effect until the renewal permit has been issued or denied.

L. **Need to Halt or Reduce Activity Not a Defense** [15A NCAC 2Q .0508(i)(4)]

It shall not be a defense for a Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

M. **Duty to Provide Information (submittal of information)** [15A NCAC 2Q .0508(i)(9)]

1. The Permittee shall furnish to the DAQ, in a timely manner, any reasonable information that the Director may request in **writing** to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit.
2. The Permittee shall furnish the DAQ copies of records required to be kept by the permit when such copies are requested by the Director. For information claimed to be confidential, the Permittee may furnish such records directly to the EPA upon request along with a claim of confidentiality.

**N. Duty to Supplement [15A NCAC 2Q .0507(f)]**

The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to the DAQ. The Permittee shall also provide additional information as necessary to address any requirement that becomes applicable to the facility after the date a complete permit application was submitted but prior to the release of the draft permit.

**O. Retention of Records [15A NCAC 2Q .0508(f) and 2Q .0508 (l)]**

The Permittee shall retain records of all required monitoring data and supporting information for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring information, and copies of all reports required by the permit. These records shall be maintained in a form suitable and readily available for expeditious inspection and review. Any records required by the conditions of this permit shall be kept on site and made available to DAQ personnel for inspection upon request.

**P. Compliance Certification [15A NCAC 2Q .0508(n)]**

The Permittee shall submit to the DAQ and the EPA (Air and EPCRA Enforcement Branch, EPA, Region 4, 61 Forsyth Street, Atlanta, GA 30303) postmarked on or before March 1 a compliance certification (for the preceding calendar year) by a responsible official with all federally-enforceable terms and conditions in the permit, including emissions limitations, standards, or work practices. It shall be the responsibility of the current owner to submit a compliance certification for the entire year regardless of who owned the facility during the year. The compliance certification shall comply with additional requirements as may be specified under Sections 114(a)(3) or 504(b) of the Federal Clean Air Act. The compliance certification shall specify:

1. the identification of each term or condition of the permit that is the basis of the certification;
2. the compliance status (with the terms and conditions of the permit for the period covered by the certification);
3. whether compliance was continuous or intermittent; and
4. the method(s) used for determining the compliance status of the source during the certification period.

**Q. Certification by Responsible Official [15A NCAC 2Q .0520]**

A responsible official shall certify the truth, accuracy, and completeness of any application form, report, or compliance certification required by this permit. All certifications shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

**R. Permit Shield for Applicable Requirements [15A NCAC 2Q .0512]**

1. Compliance with the terms and conditions of this permit shall be deemed compliance with applicable requirements, where such applicable requirements are included and specifically identified in the permit as of the date of permit issuance.
2. A permit shield shall not alter or affect:
  - a. the power of the Commission, Secretary of the Department, or Governor under NCGS 143-215.3(a)(12), or EPA under Section 303 of the Federal Clean Air Act;
  - b. the liability of an owner or operator of a facility for any violation of applicable requirements prior to the effective date of the permit or at the time of permit issuance;
  - c. the applicable requirements under Title IV; or
  - d. the ability of the Director or the EPA under Section 114 of the Federal Clean Air Act to obtain information to determine compliance of the facility with its permit.

3. A permit shield does not apply to any change made at a facility that does not require a permit or permit revision made under 15A NCAC 2Q .0523.
4. A permit shield does not extend to minor permit modifications made under 15A NCAC 2Q .0515.

S. **Termination, Modification, and Revocation of the Permit** [15A NCAC 2Q .0519]

The Director may terminate, modify, or revoke and reissue this permit if:

1. the information contained in the application or presented in support thereof is determined to be incorrect;
2. the conditions under which the permit or permit renewal was granted have changed;
3. violations of conditions contained in the permit have occurred;
4. the EPA requests that the permit be revoked under 40 CFR 70.7(g) or 70.8(d); or
5. the Director finds that termination, modification, or revocation and reissuance of the permit is necessary to carry out the purpose of NCGS Chapter 143, Article 21B.

T. **Insignificant Activities** [15A NCAC 2Q .0503]

Because an emission source or activity is insignificant does not mean that the emission source or activity is exempted from any applicable requirement or that the owner or operator of the source is exempted from demonstrating compliance with any applicable requirement. The Permittee shall have available at the facility at all times and made available to an authorized representative upon request, documentation, including calculations, if necessary, to demonstrate that an emission source or activity is insignificant.

U. **Property Rights** [15A NCAC 2Q .0508(i)(8)]

This permit does not convey any property rights in either real or personal property or any exclusive privileges.

V. **Inspection and Entry** [15A NCAC 2Q .0508(l) and NCGS 143-215.3(a)(2)]

1. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow the DAQ, or an authorized representative, to perform the following:
  - a. enter the Permittee's premises where the permitted facility is located or emissions-related activity is conducted, or where records are kept under the conditions of the permit;
  - b. have access to and copy, at reasonable times, any records that are required to be kept under the conditions of the permit;
  - c. inspect at reasonable times and using reasonable safety practices any source, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
  - d. sample or monitor substances or parameters, using reasonable safety practices, for the purpose of assuring compliance with the permit or applicable requirements at reasonable times.Nothing in this condition shall limit the ability of the EPA to inspect or enter the premises of the Permittee under Section 114 or other provisions of the Federal Clean Air Act.
2. No person shall refuse entry or access to any authorized representative of the DAQ who requests entry for purposes of inspection, and who presents appropriate credentials, nor shall any person obstruct, hamper, or interfere with any such authorized representative while in the process of carrying out his official duties. Refusal of entry or access may constitute grounds for permit revocation and assessment of civil penalties.

W. **Annual Fee Payment** [15A NCAC 2Q .0508(i)(10)]

1. The Permittee shall pay all fees in accordance with 15A NCAC 2Q .0200.
2. Payment of fees may be by check or money order made payable to the N.C. Department of Environment and Natural Resources. Annual permit fee payments shall refer to the permit number.

3. If, within 30 days after being billed, the Permittee fails to pay an annual fee, the Director may initiate action to terminate the permit under 15A NCAC 2Q .0519.

X. **Annual Emission Inventory Requirements** [15A NCAC 2Q .0207]

The Permittee shall report by **June 30 of each year** the actual emissions of each air pollutant listed in 15A NCAC 2Q .0207(a) from each emission source within the facility during the previous calendar year. The report shall be in or on such form as may be established by the Director. The accuracy of the report shall be certified by a responsible official of the facility.

Y. **Confidential Information** [15A NCAC 2Q .0107 and 2Q .0508(i)(9)]

Whenever the Permittee submits information under a claim of confidentiality pursuant to 15A NCAC 2Q .0107, the Permittee may also submit a copy of all such information and claim directly to the EPA upon request. All requests for confidentiality must be in accordance with 15A NCAC 2Q .0107.

Z. **Construction and Operation Permits** [15A NCAC 2Q .0100 and .0300]

A construction and operating permit shall be obtained by the Permittee for any proposed new or modified facility or emission source which is not exempted from having a permit prior to the beginning of construction or modification, in accordance with all applicable provisions of 15A NCAC 2Q .0100 and .0300.

AA. **Standard Application Form and Required Information** [15A NCAC 2Q .0505 and .0507]

The Permittee shall submit applications and required information in accordance with the provisions of 15A NCAC 2Q .0505 and .0507.

BB. **Financial Responsibility and Compliance History** [15A NCAC 2Q .0507(d)(4)]

The DAQ may require an applicant to submit a statement of financial qualifications and/or a statement of substantial compliance history.

CC. **Refrigerant Requirements (Stratospheric Ozone and Climate Protection)** [15A NCAC 2Q .0501(e)]

1. If the Permittee has appliances or refrigeration equipment, including air conditioning equipment, which use Class I or II ozone-depleting substances such as chlorofluorocarbons and hydrochlorofluorocarbons listed as refrigerants in 40 CFR Part 82 Subpart A Appendices A and B, the Permittee shall service, repair, and maintain such equipment according to the work practices, personnel certification requirements, and certified recycling and recovery equipment specified in 40 CFR Part 82 Subpart F.
2. The Permittee shall not knowingly vent or otherwise release any Class I or II substance into the environment during the repair, servicing, maintenance, or disposal of any such device except as provided in 40 CFR Part 82 Subpart F.
3. The Permittee shall comply with all reporting and recordkeeping requirements of 40 CFR 82.166. Reports shall be submitted to the EPA or its designee as required.

DD. **Prevention of Accidental Releases - Section 112(r)** [15A NCAC 2Q .0508(h)]

If the Permittee is required to develop and register a Risk Management Plan with EPA pursuant to Section 112(r) of the Clean Air Act, then the Permittee is required to register this plan in accordance with 40 CFR Part 68.

**EE. Prevention of Accidental Releases General Duty Clause - Section 112(r)(1) -**  
**FEDERALLY-ENFORCEABLE ONLY**

Although a risk management plan may not be required, if the Permittee produces, processes, handles, or stores any amount of a listed hazardous substance, the Permittee has a general duty to take such steps as are necessary to prevent the accidental release of such substance and to minimize the consequences of any release.

**FF. Title IV Allowances** [15A NCAC 2Q .0508(i)(1)]

This permit does not limit the number of Title IV allowances held by the Permittee, but the Permittee may not use allowances as a defense to noncompliance with any other applicable requirement. The Permittee's emissions may not exceed any allowances that the facility lawfully holds under Title IV of the Federal Clean Air Act.

**GG. Air Pollution Emergency Episode** [15A NCAC 2D .0300]

Should the Director of the DAQ declare an Air Pollution Emergency Episode, the Permittee will be required to operate in accordance with the Permittee's previously approved Emission Reduction Plan or, in the absence of an approved plan, with the appropriate requirements specified in 15A NCAC 2D .0300.

**HH. Registration of Air Pollution Sources** [15A NCAC 2D .0200]

The Director of the DAQ may require the Permittee to register a source of air pollution. If the Permittee is required to register a source of air pollution, this registration and required information will be in accordance with 15A NCAC 2D .0202(b).

**II. Ambient Air Quality Standards** [15A NCAC 2D .0501(c)]

In addition to any control or manner of operation necessary to meet emission standards specified in this permit, any source of air pollution shall be operated with such control or in such manner that the source shall not cause the ambient air quality standards in 15A NCAC 2D .0400 to be exceeded at any point beyond the premises on which the source is located. When controls more stringent than named in the applicable emission standards in this permit are required to prevent violation of the ambient air quality standards or are required to create an offset, the permit shall contain a condition requiring these controls.

**JJ. General Emissions Testing and Reporting Requirements** [15A NCAC 2Q .0508(i)(16)]

Emission compliance testing shall be by the procedures of Section .2600, except as may be otherwise required in Rules .0524, .0912, .1110, .1111, or .1415 of Subchapter 2D. If emissions testing is required by this permit or the DAQ or if the Permittee submits emissions testing to the DAQ to demonstrate compliance, the Permittee shall perform such testing in accordance with 15A NCAC 2D .2600 and follow the procedures outlined below:

1. The owner or operator of the source shall arrange for air emission testing protocols to be provided to the Director prior to air pollution testing. Testing protocols are not required to be pre-approved by the Director prior to air pollution testing. The Director shall review air emission testing protocols for pre-approval prior to testing if requested by the owner or operator at least **45 days** before conducting the test.
2. Any person proposing to conduct an emissions test to demonstrate compliance with an applicable standard shall notify the Director at least **15 days** before beginning the test so that the Director may at his option observe the test.

3. The owner or operator of the source shall arrange for controlling and measuring the production rates during the period of air testing. The owner or operator of the source shall ensure that the equipment or process being tested is operated at the production rate that best fulfills the purpose of the test. The individual conducting the emission test shall describe the procedures used to obtain accurate process data and include in the test report the average production rates determined during each testing period.
4. Two copies of the final air emission test report shall be submitted to the Director not later than **30 days** after sample collection. The owner or operator may request an extension to submit the final test report. The Director shall approve an extension request if he finds that the extension request is a result of actions beyond the control of the owner or operator.
  - a. The Director shall make the final determination regarding any testing procedure deviation and the validity of the compliance test. The Director may:
    - (1) Allow deviations from a method specified under a rule in this Section if the owner or operator of the source being tested demonstrates to the satisfaction of the Director that the specified method is inappropriate for the source being tested.
    - (2) Prescribe alternate test procedures on an individual basis when he finds that the alternative method is necessary to secure more reliable test data.
    - (3) Prescribe or approve methods on an individual basis for sources or pollutants for which no test method is specified in this Section if the methods can be demonstrated to determine compliance of permitted emission sources or pollutants.
  - b. The Director may authorize the Division of Air Quality to conduct independent tests of any source subject to a rule in this Subchapter to determine the compliance status of that source or to verify any test data submitted relating to that source. Any test conducted by the Division of Air Quality using the appropriate testing procedures described in Section 2D .2600 has precedence over all other tests.

**KK. Reopening for Cause** [15A NCAC 2Q .0517]

1. A permit shall be reopened and revised under the following circumstances:
  - a. additional applicable requirements become applicable to a facility with remaining permit term of three or more years;
  - b. additional requirements (including excess emission requirements) become applicable to a source covered by Title IV;
  - c. the Director or EPA finds that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit; or
  - d. the Director or EPA determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
2. Any permit reopening shall be completed or a revised permit issued within 18 months after the applicable requirement is promulgated. No reopening is required if the effective date of the requirement is after the expiration of the permit term unless the term of the permit was extended pursuant to 15A NCAC 2Q .0513(c).
3. Except for the state-enforceable only portion of the permit, the procedures set out in 15A NCAC 2Q .0507, .0521, or .0522 shall be followed to reissue the permit. If the State-enforceable only portion of the permit is reopened, the procedures in 15A NCAC 2Q .0300 shall be followed. The proceedings shall affect only those parts of the permit for which cause to reopen exists.
4. The Director shall notify the Permittee at least 60 days in advance of the date that the permit is to be reopened, except in cases of imminent threat to public health or safety the notification period may be less than 60 days.

5. Within 90 days, or 180 days if the EPA extends the response period, after receiving notification from the EPA that a permit needs to be terminated, modified, or revoked and reissued, the Director shall send to the EPA a proposed determination of termination, modification, or revocation and reissuance, as appropriate.

**LL. Reporting Requirements for Non-Operating Equipment** [15A NCAC 2Q .0508(i)(16)]

The Permittee shall maintain a record of operation for permitted equipment noting whenever the equipment is taken from and placed into operation. During operation the monitoring recordkeeping and reporting requirements as prescribed by the permit shall be implemented within the monitoring period.

**MM. Fugitive Dust Control Requirement** [15A NCAC 2D .0540] - STATE ENFORCEABLE ONLY

As required by 15A NCAC 2D .0540 "Particulates from Fugitive Dust Emission Sources," the Permittee shall not cause or allow fugitive dust emissions to cause or contribute to substantive complaints or excess visible emissions beyond the property boundary. If substantive complaints or excessive fugitive dust emissions from the facility are observed beyond the property boundaries for six minutes in any one hour (using Reference Method 22 in 40 CFR, Appendix A), the owner or operator may be required to submit a fugitive dust plan as described in 2D .0540(f).

"Fugitive dust emissions" means particulate matter from process operations that does not pass through a process stack or vent and that is generated within plant property boundaries from activities such as: unloading and loading areas, process areas stockpiles, stock pile working, plant parking lots, and plant roads (including access roads and haul roads).

**NN. Specific Permit Modifications** [15A NCAC 2Q .0501 and .0523]

1. For modifications made pursuant to 15A NCAC 2Q .0501(c)(2), the Permittee shall file a Title V Air Quality Permit Application for the air emission source(s) and associated air pollution control device(s) on or before 12 months after commencing operation.
2. For modifications made pursuant to 15A NCAC 2Q .0501(d)(2), the Permittee shall not begin operation of the air emission source(s) and associated air pollution control device(s) until a Title V Air Quality Permit Application is filed and a construction and operation permit following the procedures of Section .0500 (except for Rule .0504 of this Section) is obtained.
3. For modifications made pursuant to 502(b)(10), in accordance with 15A NCAC 2Q .0523(a)(1)(C), the Permittee shall notify the Director and EPA (EPA - Air Planning Branch, 61 Forsyth St., Atlanta, GA 30303) in writing at least seven days before the change is made. The written notification shall include:
  - a. a description of the change at the facility;
  - b. the date on which the change will occur;
  - c. any change in emissions; and
  - d. any permit term or condition that is no longer applicable as a result of the change.

In addition to this notification requirement, with the next significant modification or Air Quality Permit renewal, the Permittee shall submit a page "E5" of the application forms signed by the responsible official verifying that the application for the 502(b)(10) change/modification, is true, accurate, and complete. Further note that modifications made pursuant to 502(b)(10) do not relieve the Permittee from satisfying preconstruction requirements.

**OO. Third Party Participation and EPA Review** [15A NCAC 2Q .0521, .0522 and .0525(7)]

For permits modifications subject to 45-day review by the federal Environment Protection Agency (EPA), EPA's decision to not object to the proposed permit is considered final and binding on the EPA and absent a third party petition, the failure to object is the end of EPA's decision-making process with respect to the revisions to the permit. The time period available to submit a public petition pursuant to 15A NCAC 2Q .0518 begins at the end of the 45-day EPA review period.

ATTACHMENT

**List of Acronyms**

<b>AOS</b>	Alternate Operating Scenario
<b>BACT</b>	Best Available Control Technology
<b>Btu</b>	British thermal unit
<b>CEM</b>	Continuous Emission Monitor
<b>CFR</b>	Code of Federal Regulations
<b>CAA</b>	Clean Air Act
<b>CAIR</b>	<b>Clean Air Interstate Rule</b>
<b>DAQ</b>	Division of Air Quality
<b>DENR</b>	Department of Environment and Natural Resources
<b>EMC</b>	Environmental Management Commission
<b>EPA</b>	Environmental Protection Agency
<b>FR</b>	Federal Register
<b>GACT</b>	Generally Available Control Technology
<b>HAP</b>	Hazardous Air Pollutant
<b>MACT</b>	Maximum Achievable Control Technology
<b>NAA</b>	<b>Non-Attainment Area</b>
<b>NCAC</b>	North Carolina Administrative Code
<b>NCGS</b>	North Carolina General Statutes
<b>NESHAPS</b>	National Emission Standards for Hazardous Air Pollutants
<b>NO<sub>x</sub></b>	Nitrogen Oxides
<b>NSPS</b>	New Source Performance Standard
<b>OAH</b>	Office of Administrative Hearings
<b>PM</b>	Particulate Matter
<b>PM<sub>10</sub></b>	Particulate Matter with Nominal Aerodynamic Diameter of 10 Micrometers or Less
<b>POS</b>	Primary Operating Scenario
<b>PSD</b>	Prevention of Significant Deterioration
<b>RACT</b>	<b>Reasonable Available Control Technology</b>
<b>SIC</b>	Standard Industrial Classification
<b>SIP</b>	State Implementation Plan
<b>SO<sub>2</sub></b>	Sulfur Dioxide
<b>tpy</b>	Tons Per Year
<b>VOC</b>	Volatile Organic Compound